

Aquaproof Tape SA

Self-adhesive non-woven elastomeric sealing tape



Description

Aquaproof Tape SA is a high performance waterproofing tape manufactured from two layers of non-woven polypropylene sheets coated with highly elastic self-adhesive butyl rubber with excellent ageing resistance.

Aquaproof Tape SA is designed to be used in joints and corners in conjunction with the Setseal Range of waterproofing and other systems from DCP.

Applications

Aquaproof Tape SA can be applied for waterproofing of joints and corners at indoor areas subjected to nonpressurized water such as kitchens, shower rooms and bathrooms.

Advantages

- ▲ Easy to install, self-adhesive tape.
- ▲ Provides an excellent waterproofing and sealing for joints.
- ▲ Withstands medium to high loads.
- ▲ Good chemical resistant.

Method of Use

Substrate Preparation

Surfaces should be clean, sound and free from oil, grease, dirt or loose particles. Substrate should be dry, with no standing water. Spalled, cracked or defected substrate should be repaired. New concrete substrates should be at least 28 days old.

Contact DCP technical department for more information about the products which can be used in conjunction with Aquaproof Tape SA.

Application

Trim Aquaproof Tape SA to a proper size to the applied area. Remove the release liner from the back side of the tape and place it over the prepared area. Using a plastic roller, press with firm pressure the tape to ensure that it is fully adhere to the surface

Technical Properties @ 25°C:

Colour:	Grey (Other colours can be supplied upon request)
Temperature resistance:	- 5 to 60°C
Total width:	120 ± 5 mm
Total thickness:	0.70 ± 0.15 mm
Total weight:	800 ± 60 g
Tensile strength: EN ISO 527-3	Longitudinal ≥ 20 N/15 mm Transverse ≥ 15 N/15 mm
Elongation at break: EN ISO 527-3	Longitudinal ≥ 40% Transverse ≥ 55%
Watertightness: EN 1928, Version B	≥ 0.2 bar



Aquaproof Tape SA

Cleaning

All tools and equipment should be cleaned following the manufacturer recommendations of the adhesive or waterproofing product which was used.

Packaging

Aquaproof Tape SA is available in 25 meters rolls.

Storage

Aquaproof Tape SA has a shelf life of 12 months from the date of manufacturer if stored in its original packaging, away from direct sunlight, rain and snow.

Cautions

Health and Safety

Aquaproof Tape SA is not directly associated with any known hazard during normal use.

For further information refer to the Material Safety Data Sheet.

Fire

Aquaproof Tape SA is nonflammable.

More from Don Construction Products

A wide range of construction chemical products are manufactured by DCP which include:

- ▲ Concrete admixtures.
- ▲ Surface treatments
- ▲ Grouts and anchors.
- ▲ Concrete repair.
- ▲ Flooring systems.
- ▲ Protective coatings.
- ▲ Sealants.
- ▲ Waterproofing.
- ▲ Adhesives.
- ▲ Tile adhesives and grouts.
- ▲ Building products.
- ▲ Structural strengthening.

Note:

We endeavor to ensure that any advice, recommendation or information we may give in product literature is accurate and correct. However, due to the fact that we have no direct or continuous control over where or how the products are applied, DCP cannot accept any liability either directly or indirectly arising from the use of DCP products, whether or not in accordance with any advice, specification, recommendation or information given by us.

www.dcp-int.com



expertise



quality



full range