



Aquathane R100 Black

High-performance polyurethane liquid membrane for waterproofing of wet rooms and non-exposed applications

DESCRIPTION

Single component low solvents polyurethane coating that cures by reacting with the humidity in the atmosphere to form an elastic strong film with excellent adhesion to different substrates.

The product is based on elastomeric hydrophobic polyurethane resin with a special filler that provides the material with excellent waterproofing performance for wet areas, substructures and any application not exposed to UV.

The excellent rheology of Aquathane R100 Black allows an easy application process even on vertical surfaces.

APPLICATIONS

Waterproofing and protection of:

- » Flat roofs under tiles or screed.
- » Irrigation channels.
- » Verandas and balconies (under protection).
- » Bathrooms.
- » Foundation walls.

ADVANTAGES

- » Excellent adhesion to almost any surface when primed with the suitable primer.
- » Excellent service temperatures between -40 up to 60°C.
- » Excellent mechanical properties.
- » Breathable so as there is no accumulation of humidity under the coat.
- » Non-toxic after full cure.

LIMITATIONS

Do not use Aquathane R100 Black in the following areas:

- » UV exposure.
- » For waterproofing of swimming pools in contact with chemically treated water.
- » Not recommended for waterproofing under dark color tiles (outdoors) or on thermo-insulating materials.

STANDARDS

Aquathane R100 Black complies with ASTM C836 and EN 1504-2.

TECHNICAL PROPERTIES @ 25°C, 55% RH:

Colour:	Black
Specific gravity:	1.55 ± 0.05
Final full cure:	7 days
Service temperature:	-40 to 60°C
Shore A hardness: ASTM D2240	48 ± 5
Bond strength: ASTM D4541 BS EN ISO 4624	≥ 1.0 MPa @ 7 days
Tensile strength: ASTM D412	≥ 1.8 MPa @ 7 days
Elongation: ASTM D412	≥ 530% @ 7 days
Water vapour transmission: ASTM E96	0.8 g/m ² .hr

METHOD OF USE

SURFACE PREPARATION

The surface should be clean, dry, sound and free from oil, grease and wax contamination. Cement laitance, loose particles, mould release agent or curing membranes must be removed. Fill surfaces irregularities with a suitable product. Maximum moisture content should not exceed 5%. New concrete structures need to dry for at least 28 days.

Important: Do not wash surface with water.

PRIMING

In general, Aquathane R100 Black can be applied directly over well-prepared and sound concrete substrates. However, for highly porous surfaces, it is recommended to prime the substrate using water-based epoxy primer Aquathane Primer W or solvent-based polyurethane primer Aquathane Primer PU.

For applications on other types of substrates, please contact DCP Technical Department for best priming option.



Aquathane R100 Black

APPLICATION

Apply Aquathane R100 Black using roller, brush or airless spray machine. The product should be applied at a minimum of two coats, do not leave more than 48 hours between coats.

CONSUMPTION

- » First coat: minimum of 0.7 - 0.8 kg/m².
- » Second coat: minimum of 0.7 - 0.8 kg/m².
- » Total consumption: minimum of 1.4 - 1.6 kg/m².

CLEANING

All tools should be cleaned after finishing with paper towels and then wipe by using DCP Solvent PU. Do not try to clean rollers.

PACKAGING

Aquathane R100 Black is available in 25 kg packs.

STORAGE

Aquathane R100 Black has a shelf life of 12 months from date of manufacture if stored in the original unopened pails at temperatures between 5°C and 25°C.

If these conditions are exceeded, contact DCP Technical Department for advice.

CAUTIONS

HEALTH AND SAFETY

Apply in well ventilated areas. Do not smoke. Do not apply near naked flames. In closed areas use force ventilation and carbon active masks. Keep in mind that solvents are heavier than air so vapour concentration is higher in air closer to floor.

For further information, refer to the Material Safety Data Sheet.

FIRE

Aquathane R100 Black contains volatile flammable solvents.

MORE FROM DON CONSTRUCTION PRODUCTS

A wide range of construction chemical products are manufactured by DCP which include:

- » Concrete admixtures.
- » Surface treatments
- » Grouts and anchors.
- » Concrete repair.
- » Flooring systems.
- » Protective coatings.
- » Sealants.
- » Waterproofing.
- » Adhesives.
- » Tile adhesives and grouts.
- » Building products.
- » Structural strengthening.

Don Construction Products Qatar W.L.L

New Industrial Area,
Doha, Qatar
info.qatar@dcp-int.com
www.dcp-int.com

Note:

We endeavour to ensure that any information, advice or recommendation we may give in product literature is accurate and correct. However, because we have no control over where and how products are applied, we cannot accept any liability arising from the use of the products.

www.dcp-int.com

DCP Building Excellence