

Bituproof 50

Water based bitumen coating



DESCRIPTION

Bituproof 50 is a black/brown emulsified cold applied bitumen liquid, acting as damp-proof, vapour barrier for concrete and masonry, and as a general purpose primer for bituminous membranes.

APPLICATIONS

Bituproof 50 provides a vapour barrier, protective coating, and curing compound for:

- » Under ground concrete foundations.
- » Concrete and masonry block walls.
- » Walls below cladding systems.
- » Concrete slabs.
- » Basement walls.
- » Works as a primer for concrete, masonry surfaces, before applying waterproofing bituminous membranes.

ADVANTAGES

- » Resists attack by chlorides and sulphate ions present in ground water.
- » Easy to use.
- » Economical.
- » Water base, has no solvents.
- » Does not rot.

STANDARDS

Bituproof 50 complies with ASTM D1227-13, Type II, Class 1.

METHOD OF USE

SURFACE PREPARATION

Surface preparation is very important to get the highest performance of Bituproof 50. Any surface to be coated must be clean, sound and free of oil or grease. Any oil or grease contamination should be removed with a chemical degreaser.

All holes should be filled with a suitable cementitious mortar before application of Bituproof 50.

TECHNICAL PROPERTIES @ 25°C:

Form:	Liquid
Density:	1.0 ± 0.1 g/cm ³
Overcoating time:	2 - 4 hr
Solid content:	50 ± 3%
Application temperature:	5 - 45°C
Drying time*:	
porous surfaces	15 - 30 min
non-porous surfaces	1 - 2 hr
VOC:	< 40 g/ltr

Note: Depending on humidity and temperature, drying time may vary.

APPLICATION

It is recommended that two coats of Bituproof 50 be applied. The second coat should be applied at right angle to the first coat. Allow a minimum of 2 hours between coats. Stir well before use.

When used as a general purpose primer for bituminous membranes, apply Bituproof 50 in one coat at a rate of approximately 5 m²/litre.

Bituproof 50 may be applied by brush, broom or squeegee.

CLEANING

Tools and equipment can be cleaned with water when still wet. Dried Bituproof 50 may be removed with DCP Solvent.

PACKAGING

Bituproof 50 is available in 5, 18 and 200 litre drums.

COVERAGE

3.5 - 5 m²/litre per coat, to achieve a dry film thickness of around 90 - 145 microns per coat, depending on surface roughness.

DCP Saudi Co.

Sulay, Industrial Area, Istanbul St., Riyadh
Industrial City 3, Jeddah
Saudi Arabia
info.saudi@dcp-int.com
www.dcp-int.com





Bituproof 50

STORAGE

Store away from direct sunlight, and protect from freezing.

SHELF LIFE

Bituproof 50 has a shelf life of 12 months from date of manufacture if stored in proper conditions.

If these conditions are exceeded, DCP Technical Department should be contacted for advise.

CAUTIONS

HEALTH AND SAFETY

As with all bituminous products, care should be taken during use and storage to avoid contact with skin, eyes and mouth. Wear suitable protective clothing, gloves and eye/face protection.

Should accidental skin contact occur, remove immediately with plenty of clean water. If swallowed, seek medical attention immediately - do not induce vomiting.

For further information refer to the Material Safety Data Sheet.

FIRE

Bituproof 50 is nonflammable.

DCP Solvent is flammable. Ensure adequate ventilation. Do not use near a naked flame and do not smoke during use.

Flash Point:

DCP Solvent: 37°C.

MORE FROM DON CONSTRUCTION PRODUCTS

A wide range of construction chemical products are manufactured by DCP which include:

- » Concrete admixtures.
- » Surface treatments
- » Grouts and anchors.
- » Concrete repair.
- » Flooring systems.
- » Protective coatings.
- » Sealants.
- » Waterproofing.
- » Adhesives.
- » Tile adhesives and grouts.
- » Building products.
- » Structural strengthening.

DCP Saudi Co.

Sulay, Industrial Area, Istanbul St., Riyadh

Industrial City 3, Jeddah

Saudi Arabia

info.saudi@dcp-int.com

www.dcp-int.com

Note:

We endeavour to ensure that any information, advice or recommendation we may give in product literature is accurate and correct. However, because we have no control over where and how products are applied, we cannot accept any liability arising from the use of the products.

www.dcp-int.com

DCP Building Excellence



08-0162-B-2022