

Material SAFETY DATA SHEET Bituproof FLX

1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Bituproof FLX

Description: Water based elastomeric rubberized bitumen waterproof coating

Manufacturer: Ayla for Building Materials Industry & Trade

Al-Karadeh, Arsat Al-Hindia, Baghdad

Tel.: +964 790 1488 730

www.dcp-int.com

Date Prepared: 08.11.16

MSDS Number: DCP/08/01/103

2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition: Rubberized bitumen emulsion.

Hazardous Ingredient(s) Symbol Risk Phrases Cas No. %

Bitumen 64742-93-4 60

Refer to Section 8 for Occupational Exposure Limits.

3: HAZARDS IDENTIFICATION

Long term skin contact may cause health problems.

4: FIRST AID MEASURES

Eyes: Irrigate immediately with copious quantities of water for 15 minutes.

Obtain medical attention if irritation persists.

Skin: Wash thoroughly with soap and water or suitable skin cleanser as soon as

possible.

Inhalation: Remove from exposure – unlikely to occur.

Ingestion: Wash out mouth with water. Don't induce vomiting. Obtain medical

attention.

Issue No.: 01 **Rev. No.:** 01 Bituproof FLX **Page** 1 of 4



5: FIRE FIGHTING MEASURES

Flash Point: None. Special Exposure Hazards:

Extinguishing Media: Same as surrounding fire.

Personal Protective Equipment: None.

6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Wear suitable protective clothing, gloves and eye/face protection.

Environmental Precautions: Prevent entry into drains, sewers and water courses.

None.

Decontamination Procedures: Soak up with inert absorbent like sand and remove by best available

means. Gather into containers. Dispose off as waste.

HANDLING AND STORAGE

Handling: Avoid skin and eye contact.

Storage: Store in cool and dry area. Protect from frost.

8: **EXPOSURE CONTROLS AND PERSONAL PROTECTION**

Ingestion: Prevent eating, drinking or smoking in the area of product use.

Eye Contact: Safety glasses/goggles.

Skin Contact: Impervious gloves (e.g. PVC).

Engineering Controls: No specific ventilation requirement noted.

Exposure Guidelines: None assigned.

PHYSICAL AND CHEMICAL PROPERTIES

Form: Liquid Colour: Black Odour: **Typical** pH (concentrate): 9 - 11 Boiling Point (°C): 100°C Flash Point (closed cup) (°C): None

Autoflammability (°C): Not determined Explosive Properties (%): Not known Vapor Pressure (KPa @20°C): 2.3 (water) Relative Density (@25°C): 1.04 - 1.10Water Solubility: Emulsifiable

Issue No.: Rev. No.: 01 Bituproof FLX Page 2 of 4



10: STABILITY AND REACTIVITY

Stability: Stable.

Conditions to Avoid: Temperature below 2°C and above 80°C.

Chemical Incompatibility: Strong acids.

Hazardous Decomposition Products: Thermal decomposition may yield Sulfur compounds including hydrogen

sulfide.

11: TOXICOLOGICAL INFORMATION

The following toxicological assessment is based on knowledge of the toxicity of the product's components. Expected oral LD50, rat > 2 mg/kg.

Health Effects

On Eyes: Irritation.

On Skin: Unlikely to irritate on brief occasional exposure.

By Inhalation: Low volatility makes inhalation unlikely at ambient temperatures.

By Ingestion: Low order of acute toxicity. May cause irritation of mouth, throat and

digestive tract.

Chronic: Repeated and prolonged contact, allied to poor personal hygiene practices

may result in skin cancer.

12: ECOLOGICAL INFORMATION

Environmental Assessment: When used and disposed off as intended, no adverse environmental

effects are foreseen.

Mobility: Mobile liquid. Emulsifiable in water.

Degradability: Inherently biodegradable.

Bioaccumulation: Not expected to be bioaccumulative.

Acute Fish Toxicity: Ecotoxic to fish/ daphnia/ algae.

13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

Unused Product: Dispose off through an authorized waste contractor to a licensed site. Do

not empty into drains, sewers or water courses.

Used/ Contaminated Product: As for unused product.

Packaging: May be steam cleaned and recycled.

14: TRANSPORT INFORMATION

This product is **not** classified as dangerous for transport.

Issue No.: 01 **Rev. No.:** 01 Bituproof FLX **Page** 3 of 4



15: REGULATORY INFORMATION

Hazard Label Data:

This product is **not** classified as dangerous for supply.

Safety Phrases:

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with

plenty of water and seek medical advice.

16: OTHER INFORMATION

Issue Date: 08.11.16 Revised Date: 23.08.2020

Disclaimer: The information contained herein is derived from the best available sources and is

believed to be accurate. However, no guarantee is expressed or implied regarding

the accuracy of the data given in the use of this product.

Issue No.: 01 **Rev. No.:** 01 Bituproof FLX **Page** 4 of 4