

Cemamil G340

Grinding aid to reduce grinding energy and to enhance cement early and late strength



DESCRIPTION

Cemamil G340 is a liquid additive formulated from selected polymers, designed to serve as both a grinding aid and a pack set inhibitor in cement production. Cemamil G340 is specially designed to enhance the early and late strength of cement.

APPLICATIONS

Cemamil G340 has been formulated as a cement grinding aid and strength improvement additive for the cement production process. It is suitable for use in various milling methods, including Ball Mills, Vertical Mills, and others.

ADVANTAGES

- » Improved early and late strength of cement.
- » Enhanced efficiency in cement factory operations.
- » Lower energy costs in the grinding process due to reduced grinding time required to achieve the desired cement fineness.
- » Reduction in CO₂ emissions resulting from decreased energy consumption during grinding.
- » Cost savings in cement production through reduced production costs.
- » Better mill output and increased cement throughput by minimizing cement agglomeration.

COMPATIBILITY

Cemamil G340 can be used for all types of cement.

METHOD OF USE

Cemamil G340 should be added to the clinker by using automatic dispensers to dispense the correct quantity of Cemamil G340 when added to the clinker mill feed or when added directly to the mill.

DOSAGE

The recommended dosage of Cemamil G340 is 0.02 - 0.10% of cement weight (0.2 kg - 1.0 kg per ton of cement).

Laboratory trials and cement mills trials should be conducted to determine the optimum dosage of Cemamil G340 to meet the performance requirements by using the materials and conditions in actual use.

TECHNICAL PROPERTIES @ 25°C:

Colour:	Dark brown liquid
Specific gravity:	1.10 ± 0.02
Viscosity: N ₃ S ₅₀	30 - 40 cP
pH:	8 - 10

SPECIFICATION COMPLIANCE

Cemamil G340 has been tested and used in the cement industry. It complies with ASTM C465-22 as a non-harmful processing addition.

CLEANING

Cemamil G340 can be washed with fresh cold water.

PACKAGING

Cemamil G340 is available in 210 litre drums and 1000 litre tanks or in bulk delivery trucks.

STORAGE

Cemamil G340 has a shelf life of 12 months from date of manufacture if stored in unopened containers, at temperatures above 5°C.

If these conditions are exceeded, contact DCP technical department for advice.

CAUTIONS

HEALTH AND SAFETY

Cemamil G340 is not classified as a hazardous material. Cemamil G340 should not come into contact with skin and eyes.

In case of contact with eyes, immediately flush with plenty of water and seek medical attention.

For further information, refer to the Material Safety Data Sheet.

FIRE

Cemamil G340 is nonflammable.



Cemamil G340

MORE FROM DON CONSTRUCTION PRODUCTS

A wide range of construction chemical products are manufactured by DCP which include:

- » Concrete admixtures.
- » Surface treatments
- » Grouts and anchors.
- » Concrete repair.
- » Flooring systems.
- » Protective coatings.
- » Sealants.
- » Waterproofing.
- » Adhesives.
- » Tile adhesives and grouts.
- » Building products.
- » Structural strengthening.

Note:

We endeavour to ensure that any information, advice or recommendation we may give in product literature is accurate and correct. However, because we have no control over where and how products are applied, we cannot accept any liability arising from the use of the products.