

DECLARATION OF PERFORMANCE



According to Annex III of the Regulation (EU) No 305/2011
Amended by Commissions delegated Regulation (EU) No 574/2014
No.: DCDoP/005 - 070072 - C01 - 025A

- | | |
|--|---|
| 1. Unique identification code of the product type: | Donseal PU440 |
| 2. Intended uses: | Nonstructural polyurethane sealant intended for internal and external use in facade elements and cold climates |
| 3. Manufacturer: | Don Construction Products/Jordan
Khalda Street, Al-Burooj Building # 272
P.O. Box 1117 Amman 11118 Jordan |
| 4. Authorized representative: | Not Relevant |
| 5. System of AVCP: | System 4 |
| 6. Harmonised standard: | BS EN 15651 -1 :2017 F-EXT-INT-CC (25HM & 20HM) |
| Notified body: | Not Relevant |

DECLARATION OF PERFORMANCE



7. Declared performance:

Conditioning: Method A (According to ISO 8340)
Substrate: Mortar without primer

Essential Characteristics	Performance	Harmonized Technical Specification
Tensile Properties at Maintained Extension	NF	BS EN 15651-1:2017 (20HM)
Loss of volume	$\leq 10\%$	
Elastic recovery	$\geq 60\%$	
Secant Tensile Modulus	$> 0.4 \text{ N/mm}^2$ at 23°C or $> 0.6 \text{ N/mm}^2$ at -20°C	
Adhesion/Cohesion properties at maintained extension after water immersion	NF – Primer is recommended	
Adhesion and Cohesion properties at Variable Temperature	NF – 25% Movement Accommodation Factor	

DECLARATION OF PERFORMANCE



Conditioning: Method A (According to ISO 8340)
Substrate: Aluminum without primer
Glass without primer

Essential Characteristics	Performance	Harmonized Technical Specification
Tensile Properties at Maintained Extension	NF	BS EN 15651-1:2017 (25HM)
Loss of volume	$\leq 10\%$	
Elastic recovery	$\geq 70\%$	
Secant Tensile Modulus	$> 0.4 \text{ N/mm}^2$ at 23°C or $> 0.6 \text{ N/mm}^2$ at -20°C	
Adhesion/Cohesion properties at maintained extension after water immersion	NF	
Adhesion and Cohesion properties at Variable Temperature	NF – 25% Movement Accommodation Factor	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Name: *Mohammad Hammoudeh*

Place and date of issue:

Amman - Jordan

14/10/2025

Signature:

