

Doncoat

Ready to use putty for smooth finishing



DESCRIPTION

Doncoat is a ready to use, PVA based, smooth finishing putty for all common construction substrates including concrete surfaces, cementitious plaster, gypsum, wood and plaster boards. The unique composition of Doncoat makes it ideally suitable to provide an even and smooth surface ready for final paint application.

APPLICATIONS

Doncoat is designed for use internally for fairing and smoothing concrete, cementitious plaster, wood, gypsum and plaster boards prior to applying finishing coats.

ADVANTAGES

- › Excellent adhesion on a variety of substrates.
- › Easy to apply, ready to use single component.
- › Easy to smoothen after drying using fine sandpaper.
- › Excellent drying time.
- › Environmentally friendly, water based material.

METHOD OF USE

SUBSTRATE PREPARATION

All surfaces should be sound and clean from dust, oil and foreign matter. Ridges and trowel marks should be removed by abrasion. Surface should be dry before application.

APPLICATION

Doncoat shall be applied using a proper stainless steel putty knife or trowel to provide a smooth and level surface. Depending on the substrate condition, 2 - 3 coats of Doncoat should be applied before the final finishing coat.

Allow the first layer of Doncoat to dry prior to applying the next layer. The final layer should be lightly sanded using fine sandpaper before applying the finishing coat.

TECHNICAL PROPERTIES @ 25°C

Colour:	Creamy paste
Density:	1.7 ± 0.1 g/cm ³
Skin over time:	20 - 25 min @ 25°C
Drying time:	3 - 4 hr for full dry, depending on ambient temperature
VOC: ASTM D2369	≤ 10 g/ltr (comply with LEED)

PACKAGING

Doncoat is available in 20 kg packages.

COVERAGE

Approximately 1.5 - 2.0 m²/kg.

STORAGE

Keep tightly sealed, store under cover in a dry area at room temperature, protect from freezing, exposure to extreme heat and direct sunlight.

SHELF LIFE

Doncoat has a shelf life of 12 months from date of manufacture if stored in original unopened bags.

If these conditions are exceeded, DCP Technical Department should be contacted for advice.

DCP Saudi Co.

Sulay, Industrial Area, Istanbul St., Riyadh
Industrial City 3, Jeddah
Saudi Arabia
info.saudi@dcp-int.com
www.dcp-int.com





Doncoat

CAUTIONS

HEALTH AND SAFETY

Wear suitable protective clothing, gloves and eye/face protection. Should accidental skin contact occur, remove immediately with clean water.

For further information refer to the Material Safety Data Sheet.

FIRE

Doncoat is nonflammable.

MORE FROM DON CONSTRUCTION PRODUCTS

A wide range of construction chemical products are manufactured by DCP which include:

- » Concrete admixtures.
- » Surface treatments
- » Grouts and anchors.
- » Concrete repair.
- » Flooring systems.
- » Protective coatings.
- » Sealants.
- » Waterproofing.
- » Adhesives.
- » Tile adhesives and grouts.
- » Building products.
- » Structural strengthening.

DCP Saudi Co.

Sulay, Industrial Area, Istanbul St., Riyadh

Industrial City 3, Jeddah

Saudi Arabia

info.saudi@dcp-int.com

www.dcp-int.com

Note:

We endeavour to ensure that any information, advice or recommendation we may give in product literature is accurate and correct. However, because we have no control over where and how products are applied, we cannot accept any liability arising from the use of the products.

www.dcp-int.com

DCP Building Excellence

