

Donseal® AS111

Universal silicone sealant (Formerly known as Flexseal AS111)



DESCRIPTION

Donseal AS111 is a universal one-part acetoxy cure silicone sealant, which cures rapidly on exposure to moisture to form a resilient elastic silicone rubber.

APPLICATIONS

Recommended for use in sanitary applications, sealing wall joints formed in ceramic tiles in bathrooms and kitchens, perimeter joints around uPVC frames as well as general industrial sealing.

ADVANTAGES

- » UV resistant.
- » Mould resistance.
- » Non-sag sealant.
- » Easy to apply, one component sealant.
- » Long service life with stable colour.
- » Remains flexible at wide temperature range.
- » Excellent adhesion strength to non-porous substrates such as aluminum, glass, ceramic etc.

STANDARDS

Donseal AS111 complies with:

- » BS EN ISO 11600 F25 LM.
- » ASTM C920, Type S, Grade NS, Class 25, Use G, A, O and NT.

METHOD OF USE

JOINT PREPARATION

The joint surfaces must be clean, dry and free from all contamination. Primers may be required on some substrates.

It is recommended to use masking tape on each side of the joint to maintain clean and uniform joint sides.

JOINT BACKING

Where applicable, appropriate joint filler e.g. closed cell polyethylene foam, should be used to provide the correct joint depth.

TECHNICAL PROPERTIES @ 25°C, 50% RH:

Consistency:	Soft paste
Colour:	White & translucent
Specific gravity:	0.98 ± 0.05
Tensile strength:	> 1 MPa
Elongation:	> 250%
UV resistance:	Very good
Skinning time:	20 min @ 20°C
Shore A hardness:	20 ± 5
Service temperature:	-40 up to 100°C
Application temperature:	5 to 40°C
Chemical resistance:	Resistant to most alkalis and dilute acids. Organic solvents may cause the sealant to swell and lose adhesion, but do not directly dissolve the sealant
Service life:	+25 years
Curing rate:	2 mm/24 hr
VOC:	< 110 g/ltr

APPLICATION

Donseal AS111 is supplied in cartridges and can be applied into the joint using caulk gun.

Apply Donseal AS111 into the joint starting from the bottom, ensure that the joint is completely filled. Tool the surface of the sealant within 15 minutes of the application using a spatula or suitable smoothing liquid.

This will provide a smooth finish and will ensure good contact between the sealant and the substrate. Remove the masking tape directly after tooling the sealant.



Donseal® AS111

PACKAGING

Donseal AS111 is available in 280 ml cartridges. Polyethylene nozzles are included in each box.

SEALANT QUANTITY ESTIMATOR

Joint size mm	Meters per Ltr
6 x 6	27.75 m
9 x 6	18.50 m
12 x 9	9.25 m
18 x 10	5.55 m
25 x 10	4.0 m

LIMITATIONS

- » Not recommended on porous substrates such as concrete, stone and marble.
- » Not recommended to be used on bituminous substrates or substrates based on natural rubber and EPDM.
- » Donseal AS111 can corrode mirror, silver, copper, brass and lead.
- » Not recommended to be used in submerged joints.

STORAGE

Donseal AS111 has a shelf life of 9 months from date of manufacture if stored in original unopened packages stored in a cool, dry place out of direct sunlight.

If these conditions are exceeded, contact DCP Technical Department for advice.

CAUTIONS

HEALTH AND SAFETY

Avoid prolonged contact with the skin. If sealant comes into contact with the eyes, flush with copious volumes of cold water and obtain medical attention.

For further information, refer to the Material Safety Data Sheet.

MORE FROM DON CONSTRUCTION PRODUCTS

A wide range of construction chemical products are manufactured by DCP which include:

- » Concrete admixtures.
- » Surface treatments
- » Grouts and anchors.
- » Concrete repair.
- » Flooring systems.
- » Protective coatings.
- » Sealants.
- » Waterproofing.
- » Adhesives.
- » Tile adhesives and grouts.
- » Building products.
- » Structural strengthening.

Don Construction Products Bulgaria EAD

Tsvetan Lazarov 152
Techno Park, Sofia 1582
Bulgaria
info.bulgaria@dcp-int.com
www.dcp.bg

Note:

We endeavour to ensure that any information, advice or recommendation we may give in product literature is accurate and correct. However, because we have no control over where and how products are applied, we cannot accept any liability arising from the use of the products.

www.dcp-int.com

DCP Building Excellence



07-0093-BG-A-2025