

# Donseal® GA777

General purpose acrylic sealant



## DESCRIPTION

Donseal GA777 is a one-part, general purpose acrylic sealant which can be used internally or externally. It cures on exposure to the atmosphere to form a flexible sealant. Donseal GA777 does not need primer when applied to concrete stone, marble and aluminum surfaces.

## APPLICATIONS

Donseal GA777 is used for sealing joints in the building industry in many applications such as:

- » Concrete, wood, anodized aluminum, blockwork, marble and natural stone.
- » Around windows and door frames.
- » Cladding panels.
- » Galvanized metal sheets.
- » Ducts.

Also it can be used as an adhesive to fix light weight building materials (Adhesion test is recommended before use).

## ADVANTAGES

- » Single component ready for use.
- » 10% movement accommodation factor.
- » UV resistant.
- » Excellent adhesion to most building substrates.
- » Can be painted.

## STANDARDS

Donseal GA777 complies with ASTM C834, Type OP, Grade NF and EN 15651-1:2017, Classes 12.5P and 7.5P.

## METHOD OF USE

### JOINT SURFACE PREPARATION

Surfaces must be clean, dry and free from dust, grease, oils and all other contaminants.

### JOINT BACKING

Where applicable, appropriate joint backing rod such as closed cell polyethylene foam, should be used to provide the correct joint depth.

## TECHNICAL PROPERTIES:

Movement accommodation:	10%
UV resistance:	Excellent
Sag resistance:	Excellent
Service temperature:	-5 to 60°C
Application temperature:	10 to 50°C
Elongation: ASTM D412	> 200%
Curing rate:	3 mm/day @ 20°C
VOC:	< 50 g/ltr

## APPLICATION

Donseal GA777 is supplied in cartridges and can be applied into the joint using a skeleton Gun.

Cut off cartridge top, cut nozzle to required size, attach the nozzle to the cartridge. Extrude the sealant firmly against the joint surfaces to ensure complete contact.

Tool the sealant into the joint to compact and achieve a good surface finish. Tool within 10 minutes after sealant is applied.

It is recommended to use masking tape on each side of the joint to maintain clean and uniform joint sides. Remove the masking tape directly after tooling the sealant.

## REMARKS

Donseal GA777 is not recommended for joints subjected to limited movements or for joints subjected to water splashing.

## CLEANING

Uncured sealant can be removed using clean water, cured sealant should be removed mechanically.

## PACKAGING

Donseal GA777 is available in 280 ml cartridges.

## Don Construction Products Bulgaria EAD

Tsvetan Lazarov 152  
Techno Park, Sofia 1582  
Bulgaria  
[info.bulgaria@dcp-int.com](mailto:info.bulgaria@dcp-int.com)  
[www.dcp.bg](http://www.dcp.bg)





# Donseal® GA777

## SEALANT QUANTITY ESTIMATOR

Joint size mm	Meters per 280 ml cartridge
3 x 5	18.67
5 x 5	11.20
10 x 5	5.60
10 x 10	2.80
20 x 10	1.40
20 x 20	0.70
25 x 12	0.93

## JOINT SIZE SUITABILITY

*Joint width\*:*

- » 3 mm minimum.
- » 25 mm maximum.

*Joint depth:*

- » Half the joint width.

## STORAGE

Store in a dry and cool conditions away from humidity.

## SHELF LIFE

Donseal GA777 has a shelf life of 12 months from date of manufacture in original unopened package away from humidity.

If these conditions are exceeded, contact DCP Technical Department for advice.

## CAUTIONS

### HEALTH AND SAFETY

If Donseal GA777 comes into contact with eyes, flush with copious volumes of cold water and obtain medical attention.

For further information, refer to the Material Safety Data Sheet.

## FIRE

Donseal GA777 is nonflammable.

## MORE FROM DON CONSTRUCTION PRODUCTS

A wide range of construction chemical products are manufactured by DCP which include:

- » Concrete admixtures.
- » Surface treatments
- » Grouts and anchors.
- » Concrete repair.
- » Flooring systems.
- » Protective coatings.
- » Sealants.
- » Waterproofing.
- » Adhesives.
- » Tile adhesives and grouts.
- » Building products.
- » Structural strengthening.

## Don Construction Products Bulgaria EAD

Tsvetan Lazarov 152  
Techno Park, Sofia 1582  
Bulgaria  
[info.bulgaria@dcp-int.com](mailto:info.bulgaria@dcp-int.com)  
[www.dcp.bg](http://www.dcp.bg)

Note:

We endeavour to ensure that any information, advice or recommendation we may give in product literature is accurate and correct. However, because we have no control over where and how products are applied, we cannot accept any liability arising from the use of the products.

[www.dcp-int.com](http://www.dcp-int.com)

DCP Building Excellence



07-0090-BG-A-2025