

Flexfoam Cleaner

Cleaner for PU-foam application guns



DESCRIPTION

Flexfoam Cleaner is a highly effective cleaner for PU-foam gun applicators, can valves, and grease. It is also suitable for removing uncured polyurethane foam and adhesives.

APPLICATIONS

- » Cleaning and maintenance of construction tools and equipment used with polyurethane foam or adhesives.
- » Removal of fresh, uncured foam and adhesive residues from surfaces such as windows, doors, insulation materials, and construction joints.
- » Preparation of surfaces prior to the application of sealants, adhesives, or coatings by effectively degreasing metal surfaces.

ADVANTAGES

- » Efficiently removes uncured foam and adhesive residues, reducing manual scraping or abrasive methods.
- » Versatile for various cleaning tasks related to polyurethane foam and adhesives.
- » Maintains PU-foam guns for optimal performance and longevity.

METHOD OF USE

SURFACE PREPARATION

When used for degreasing surfaces, ensure the surface is clean and free of debris. Also, mechanically remove any cured PU foam.

It is also recommended to perform a test on a small area to ensure compatibility with the surface.

APPLICATION

Manual Application

- » Attach the enclosed spraying nozzle to the cleaner valve.
- » Spray the cleaner onto the can valve and any fresh stains of PU foam or adhesive.
- » Wipe away the stains with a dry cloth.



TECHNICAL PROPERTIES:

Colour:	Transparent
Composition:	Solvent-based cleaning agent
Can size:	500 ml

Gun Application

- » Unscrew the can of foam/adhesive from the gun.
- » Press the gun trigger to remove any foam residue.
- » Attach the enclosed spraying nozzle to the cleaner valve.
- » Spray the cleaner onto the can valve and the gun adapter.
- » Remove the nozzle and screw the can of cleaner onto the gun.
- » Press the gun trigger several times.

REMARKS

- » Flexfoam Cleaner dissolves only uncured one-component PU-foams and adhesives.
- » Flexfoam Cleaner can damage polystyrene, PVC and some other plastics.
- » It is recommended to test the cleaner on a small area of the surface before use.

PACKAGING

The Flexfoam Cleaner is available in a pressurized can size of 500 ml.

Don Construction Products Bulgaria EAD

Tsvetan Lazarov 152
Techno Park, Sofia 1582
Bulgaria
info.bulgaria@dcp-int.com
www.dcp.bg



Flexfoam Cleaner

STORAGE

Flexfoam Cleaner has a shelf life of 24 months from date of manufacture if stored in dry and cool conditions at temperatures range between 5°C and 35°C in its original unopened packing, away from fire resources.

If these conditions are exceeded, DCP Technical Department should be contacted for advice.

CAUTIONS

HEALTH AND SAFETY

Apply in well-ventilated areas. Avoid direct contact with skin and eyes. Wear appropriate personal protective equipment such as gloves and safety glasses. Keep the product away from children and pets.

Notes:

- » *It is not allowed to store cans of Cleaner in temperature exceeding +50°C.*
- » *Do not store in the passenger compartment. Transported only in the trunk.*

For further information refer to the Material Safety Data Sheet.

MORE FROM DON CONSTRUCTION PRODUCTS

A wide range of construction chemical products are manufactured by DCP which include:

- » Concrete admixtures.
- » Surface treatments
- » Grouts and anchors.
- » Concrete repair.
- » Flooring systems.
- » Protective coatings.
- » Sealants.
- » Waterproofing.
- » Adhesives.
- » Tile adhesives and grouts.
- » Building products.
- » Structural strengthening.

Don Construction Products Bulgaria EAD

Tsvetan Lazarov 152
Techno Park, Sofia 1582
Bulgaria
info.bulgaria@dcp-int.com
www.dcp.bg

Note:

We endeavour to ensure that any information, advice or recommendation we may give in product literature is accurate and correct. However, because we have no control over where and how products are applied, we cannot accept any liability arising from the use of the products.

www.dcp-int.com

DCP Building Excellence