

Material SAFETY DATA SHEET Flexseal PU650

1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Flexseal PU650

Description: High-movement, high-performance, one component, non-sag

polyurethane sealant

Manufacturer: Ayla for Building Materials Industry & Trade

Al-Karadeh, Arsat Al-Hindia, Baghdad

Tel.: +964 790 1488 730

www.dcp-int.com

Date Prepared: 16.10.17

MSDS Number: DCP/07/03/64

2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition: Polyurethane polymer.

Hazardous Ingredient(s) Symbol Risk Phrases CAS No. %

Xylene, mixture of isomers Xi, Xn R10, 20/21, 38 1330-20-7 2 - 5

Refer to Section 8 for Occupational Exposure Limits.

3: HAZARDS IDENTIFICATION

Hazard Information: Flammable.

Harmful by inhalation and in contact with skin.

Classification: No specific hazards because the product is fully polymerized by

atmospheric humidity to a solid rubber like material.

4: FIRST AID MEASURES

Eyes: Rinse immediately with soap and plenty of water. Obtain medical advice if

there are persistent symptoms.

Skin: Wash Wash immediately with alkool, soap and plenty of water. If rapid

removal does not occur, remove it after its fully polymerized.

Inhalation: No specific hazards. Not important volatile substances.

Ingestion: Do not induce vomiting. Give nothing by mouth. Obtain medical attention.

Advice to physicians: Symptomatic treatment and supportive therapy as indicated. Following

severe exposure the patient should be kept under medical review for at

least 48 hours.

Issu	e No.:	01	Rev. No.:	00	Flexseal PU650	Page	1 01	f 4	
------	--------	----	-----------	----	----------------	------	------	-----	--



5: FIRE FIGHTING MEASURES

Flash Point: None.

Special Exposure Hazards: None.

Extinguishing Media: Sand, dry extinguishing media, foam and carbon dioxide.

Personal Protective Equipment: Gloves and self- protective clothing.

6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Wear suitable protective clothing, gloves and eye/face protection.

Environmental Precautions: No specific hazards because the product is fully polymerized by

atmospheric humidity to a solid rubber like material.

Decontamination Procedures: Transfer the product to a tank for suitable incineration in accordance with

local regulations.

7: HANDLING AND STORAGE

Handling: Avoid skin and eye contact.

Storage: In the original containers tightly sealed in a dry place. It is not flammable

product. Keep out of the reach of children.

8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ingestion: Prevent eating, drinking or smoking in the area of product use.

Eye Contact: Safety glasses/goggles.

Skin Contact: Impervious gloves (e.g. PVC).

Respiratory Protection: In case of insufficient ventilation wear suitable equipment. Change

contaminated clothing and clean before re-use.

Engineering Controls: No specific ventilation requirement noted.

Exposure Guidelines: None assigned.

Issue No.: 01 **Rev. No.:** 00 Flexseal PU650 **Page** 2 of 4



9: PHYSICAL AND CHEMICAL PROPERTIES

Form: Pasty

Colour: Various

Odour: Characteristic

Boiling Point (°C): None

Flash Point (closed cup) (°C): 40 - 55°C Relative Density (@25°C): 1.1 - 1.2

Water Solubility: Insoluble

Soluble in: Organic solvents

Viscosity: Thyrotrophic

Active solids content percent: 99%w/w

10: STABILITY AND REACTIVITY

Stability: Minimum self-life in sealed containers 12 months under conditions without

humidity and temperature up 30°C.

Conditions to Avoid: Humidity, long term studies at the sun and high temperature (> 30°C).

Chemical Incompatibility: Amines, alcohols and water.

Hazardous Decomposition Products: None expected.

11: TOXICOLOGICAL INFORMATION

Health Effects

On Eyes: May cause serious damage.

On Skin: Irritant.

By Inhalation: Not important volatile substances.

By Ingestion: Serious damage at very high concentrations. Do not delay. Go

immediately to hospital.

Issue No.: 01 **Rev. No.:** 00 Flexseal PU650 **Page** 3 of 4



12: ECOLOGICAL INFORMATION

Mobility: None expected because of the fully polymerization of the product to a

solid rubber like material.

Degradability: None known.

Bioaccumulation: It is like the rubbers.

Acute Fish Toxicity: The product does not contain heavy metals or other harmful ingredients.

The fillers are physical materials. The contained isocyanates are fully polymerized by atmospheric humidity to a solid rubber like material, which is familiar to the environment. The product is packaged in sausages of aluminum, which is an ecological material instead of the containers of the

polyethylene.

13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

14: TRANSPORT INFORMATION

This product is **not** classified as dangerous for transport.

15: REGULATORY INFORMATION

Hazard Label Data: Xn



Harmful

Named Ingredients: Xylene, mixture of isomers

Risk Phrases:

R10 Flammable.

R20/21 Harmful by inhalation and in contact with skin.

R38 Irritating to skin.

Safety Phrases:

S23 Do not breath fumes/vapour/spray.

16: OTHER INFORMATION

Issue Date: 16/10/2017 Revised Date:

Disclaimer: The information contained herein is derived from the best available sources and is

believed to be accurate. However, no guarantee is expressed or implied regarding

the accuracy of the data given in the use of this product.

Issue No.: 01 **Rev. No.:** 00 Flexseal PU650 **Page** 4 of 4