

# Material SAFETY DATA SHEET Flo-Add HF

# 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name:	Flo-Add HF
Description:	Hydrogen free expansive and plasticising grout additive
Manufacturer:	Ayla for Building Materials Industry & Trade
	Al-Karadeh, Arsat Al-Hindia, Baghdad
	Tel.: +964 790 1488 730
	www.dcp-int.com
Date Prepared:	31.05.2011
MSDS Number:	DCP/03/01/03

## 2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition:	Silica sand, additiv	es.		
Hazardous Ingredient(s)	Symbol	Risk Phrases	CAS No.	%
Sodium salt of poly-naphthalen	e		2/200 04 7	45 (0
Sulphonic acid	-	R36/37/38	36290-04-7	45 - 60
Hydrazine sulphate	Τ, C, N	R23/24/25, 34, 43, R45, 50/53	10034-93-2	10 - 18
Copper carbonate	Xn	R22, 36	1184-64-1	5 - 10

Refer to Section 8 for Occupational Exposure Limits.

# 3: HAZARDS IDENTIFICATION

Hazard Information:	Harmful if swallowed. Toxic by inhalation, in contact with skin and if swallowed. Causes burns. Irritating to eyes, skin and respiratory system. May cause sensitization by skin contact. May cause cancer. Very toxic to aquatic organism, may cause long-term affects in the aquatic environment.
Classification:	Xn, T, C, N. R22, 23/24/25, 34, 36/37/38, 43, 45, 50/53.

Issue No.:	01	Rev. No.:	00	Flo-Add HF	Page 1 of 6



# 4: FIRST AID MEASURES

Eyes:	Irrigate immediately with copious quantities of water for 15 minutes. Obtain medical attention urgently.
Skin:	Wash immediately with soap and water or suitable skin cleanser, Dab with polyethylene glycol 400. Remove contaminated clothes and shoes. Obtain medical advice if skin disorders develop.
Inhalation:	Remove from exposure; obtain medical attention if respiratory irritation develops or if breathing becomes difficult.
Ingestion:	Rinse mouth thoroughly. Drink plenty of water. Induce vomiting. Obtain medical attention, administer: activated charcoal (20 – 40 g in 10% slurry) Keep airways free. Beware of aspiration if vomiting occurs.

# 5: FIRE FIGHTING MEASURES

Flash Point (Closed Cup):	Not applicable.
Extinguishing Media:	Carbon dioxide, powder, foam or water.
Personal Protective Equipment:	Self-contained breathing apparatus.
Special Exposure Hazards:	Products of combustion are: Sulfur oxides (SO <sub>2</sub> , SO <sub>3</sub> ) and Carbon oxides (CO,CO <sub>2</sub> ).

#### 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Wear suitable protective clothing, gloves, eye/face protection and dust respirator. Avoid generation and inhalation of dusts in all circumstances.
Environmental Precautions:	Do not allow to enter drainage system, surface or ground water. Danger to drinking water if even small quantities leak into soil.
Decontamination Procedures:	Use a shovel to put the spilled solid in a convenient waste disposal container. Avoid dust generation.

7: HANDLING ANI	D STORAGE
Handling:	Maintain good standards of personal hygiene. Avoid skin and eye contact. Do not eat, drink or smoke whilst using this product. Ensure adequate ventilation. Wear suitable respiratory equipment. Avoid dust generation.
Storage:	Keep containers tightly closed, keep in a cool, well-ventilated place. Avoid contact with strong oxidizing agents.

Issue No.: 01 Rev. No.: 00 Flo-Add HF	1 <b>Rev. No.:</b> 00 Flo-Add HF
---------------------------------------	----------------------------------



# 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Eye Protection:	Tightly sealed safety glassesor face shield.
Skin Protection:	Impervious gloves (e.g. PVC). Suitable protective clothing.
Respiratory Protection:	Organic chemical cartridge respirator.
Hygiene Measures:	Change contaminated clothing and clean before re-use.
Engineering Controls:	Use only in well ventilated areas. Local exhaust ventilation is recommended.

# 9: PHYSICAL AND CHEMICAL PROPERTIES

Form:	Powder
Colour:	Brown
Odour:	Odourless
pH (concentrate):	Not applicable
Boiling Point (°C):	Not applicable
Flash Point (closed cup) (°C):	NA Not applicable
Autoflammability (°C):	Not applicable
Explosive Properties (%):	Not applicable
Relative Density (@25°C):	1.90 – 2.10
Water Solubility:	Soluble

#### **10: STABILITY AND REACTIVITY**

Stability:	Stable in normal conditions.
Conditions to Avoid:	Strong Heating.
Chemical Incompatibility:	Strong oxidizing agents, Metallic Oxides, Mercury Compounds,
Hazardous Decomposition Products:	Thermal decomposition yield oxides of carbon, toxic fumes, refer to section 5.

Issue No.: 01 Rev. No.: 00 Flo-Add HF	Page 3 of 6
---------------------------------------	-------------



#### **11: TOXICOLOGICAL INFORMATION**

The following toxicological assessment is based on knowledge of the toxicity of the product's components. Acute Oral effect LD50 = 600 mg/kg.

#### **Health Effects**

On Eyes:	Irritant.
On Skin:	Irritant.
By Inhalation:	Irritant.
By Ingestion:	Irritant.
Chronic:	Repeated and prolonged skin contact may lead to toxic effect on: Kidneys, liver.

### 12: ECOLOGICAL INFORMATION

Environmental Assessment:	Contains compounds that are dangerous for the environment.
Mobility:	Powder.
Degradability:	Not readily biodegradable.
Bioaccumulation:	Not expected to be bioaccumulate.
Acute Fish Toxicity:	Ecotoxic to fish/ daphnia/ algae.

#### **13: DISPOSAL CONSIDERATION**

Disposal must be in accordance with local and national legislation.

Unused Product:	Dispose off through an authorized waste contractor to a licensed site.
Used/ Contaminated Product:	As for unused product.
Packaging:	Must be disposed off through an authorized waste contractor.

Issue No.:	01	Rev. No.:	00	Flo-Add HF Page	4 of 6



6

## **14: TRANSPORT INFORMATION**



UN Number:

Transport Name:

3288

Toxic solid, inorganic, n.o.s. (Hydrazine sulphate).

Transport Type:		Class:	Pack Group:	Marine Pollutant
At Sea	IMO/IMDG	6.1	111	Yes
Air Transport	ΙΑΤΑ	6.1	111	
At land	RID/ADR	6.1	111	

|--|



#### **15: REGULATORY INFORMATION**

Hazard Label Data:		N T C Toxic C Corrosive		
Named Ingredients:	Sodium salt o copper carbona	f poly-naphthalene sulphonic acid, hydrazine sulphate, te.		
UN Number:	3288			
Risk Phrases:				
	R22	Harmful if swallowed.		
	R23/24/25	Toxic by inhalation, in contact with skin and if swallowed.		
	R34	Causes burns.		
	R36/37/38	Irritating to eyes, skin and respiratory system.		
	R43	May cause sensitization by skin contact.		
	R45	May cause cancer.		
	R50/53	Very toxic to aquatic organism, may cause long-term affects in the aquatic environment.		
Safety Phrases:				
	S24/25	Avoid contact with skin and eyes.		
	S36/37/39	Wear suitable protective clothing, gloves and eye/face protector.		
	S45	In case of accident or if you feel unwell seek medical advice immediately.		
	S53	Avoid exposure - obtain special instructions before use.		
16: OTHER INFORMATION				
Issue Date:	31/05/2011 Revised Date:			
Disclaimer:	The information contained herein is derived from the best available sources and is believed to be accurate. However, no guarantee is expressed or implied regarding the accuracy of the data given in the use of this product.			