

# Material SAFETY DATA SHEET Flo-Grout EPCG - Hardener

# 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Flo-Grout EPCG - Hardener

Description: Hardener component of three part high strength pourable epoxy

foundation resin grout

Manufacturer: DCP Saudi Co

P.O. Box 66241, Riyadh 11576 Kingdom of Saudi Arabia

Tel. + 966 11 4612003 Fax: + 966 11 2792059

www.dcp-int.com

Date Prepared: 01.10.15

MSDS Number: DCP/03/03/28-H

#### 2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition: Epoxy resin hardening agent.

Hazardous Ingredient(s) Symbol Risk Phrases CAS No. % Polyoxypropylendiamin C, Xn R22, 34 9046-10-0 10 - 65 R22, 34, 62, 50/53, 63 10 - 55 nonylphenol C, Xn, N 25154-52-3 2-piperazin-1-ylethylamine C, Xn R21/22, 34, 43, 52/53 140-31-8 10 - 35

Refer to Section 8 for Occupational Exposure Limits.

#### 3: HAZARDS IDENTIFICATION

Hazard Information: Corrosive.

Harmful if swallowed.

Causes burns.

Irritating to eyes and skin.

May cause sensitisation by skin contact.

Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Possible risk of impaired fertility.

Possible risk of harm to the unborn child.

Classification: C, Xn, N. R22, 34, 36/38, 43, 51/53, 62, 63.

Issue No.: 01 Rev. No.: 00 Flo-Grout EPCG – Hardener Page 1 of 6



### 4: FIRST AID MEASURES

Eyes: Irrigate opened eye immediately with copious quantities of water for 15

minutes. Obtain medical attention immediately.

Skin: Wash immediately with soap and water or suitable skin cleanser. Remove

contaminated clothes and shoes. Obtain medical advice if irritation

persists.

Inhalation: Remove from exposure; obtain medical attention if respiratory irritation

develops or if breathing becomes difficult.

Ingestion: Drink plenty of water. Do not induce vomiting. Obtain medical attention.

Beware of aspiration if vomiting occurs.

General: Symptoms of poisoning may even occur after several hours; therefore

medical observation for at least 48 hours after the accident.

### 5: FIRE FIGHTING MEASURES

Flash Point (Closed Cup): > 100°C.

Extinguishing Media: CO<sub>2</sub>, extinguishing powder or water jet. Fight larger fires with water jet or

alcohol-resistant foam. For safety reasons do not use Water with a full

water jet.

Personal Protective Equipment: Self-contained breathing apparatus. Standard aluminized suit.

Special Exposure Hazards: Toxic fumes. Carbon monoxide (CO), nitrogen oxides (NOx).

# **6: ACCIDENTAL RELEASE MEASURES**

Personal Precautions: Ensure adequate ventilation immediately issue NO SMOKING and NO

NAKED FLAMES warnings. Wear suitable protective clothing, gloves and

eye/face protection.

Environmental Precautions: Prevent entry into drains, sewers and water courses.

Decontamination Procedures: Soak up with inert absorbent like sand. Gather into labeled containers.

Dispose off as applicable regulations.

# 7: HANDLING AND STORAGE

Handling: Maintain good standards of personal hygiene. Avoid skin and eye contact.

Do not eat, drink or smoke whilst using this product. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory

equipment.

Storage: Keep container tightly closed in a cool dry area away from sources of heat

and out of direct sunlight to avoid pressure build up. Store in conformity with local fire regulations. Store away from sources of ignition. Keep away

from food containers. Store at 15 - 25°C.

**Issue No.:** 01 **Rev. No.:** 00 Flo-Grout EPCG – Hardener **Page** 2 of 6



# 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Eye Protection: Tightly sealed safety glasses/goggles.

Skin Protection: Impervious gloves (e.g. PVC). Suitable protective clothing.

Respiratory Protection: Breathing filters apparatus.

Hygiene Measures: Change contaminated clothing and clean before re-use.

Engineering Controls: Use only in well ventilated area. Local exhaust ventilation is

recommended.

Exposure Guidelines: None assigned.

# 9: PHYSICAL AND CHEMICAL PROPERTIES

Form: Liquid

Colour: Yellowish
Odour: Amine-like

Boiling Point (°C): > 200

Flash Point (closed cup) (°C): > 100

Autoflammability (°C): Product is not selfigniting

Explosive Properties (%): Product is not explosive

Relative Density (@25°C): 0.98 – 1.00

Water Solubility: Not miscible or difficult to mix

#### 10: STABILITY AND REACTIVITY

Stability: Contains volatile solvent. Stable if used as directed.

Conditions to Avoid: Any source of ignition. Temperature above 35°C.

Chemical Incompatibility: Strong acids. Strong alkalis. Strong oxidizing agents.

Hazardous Decomposition Products: Thermal decomposition yield oxides of carbon, nitrogen compounds.

**Issue No.:** 01 **Rev. No.:** 00 Flo-Grout EPCG – Hardener **Page** 3 of 6



#### 11: TOXICOLOGICAL INFORMATION

The following toxicological assessment is based on knowledge of the toxicity of the product's components. Expected oral LD50, rat > 1000 mg/kg. Classified as skin sensitizer.

#### **Health Effects**

On Eyes: Strong caustic effect.

On Skin: Corrosive - causes burns. May cause sensitization.

By Inhalation: Harmful by inhalation. May cause respiratory irritation.

By Ingestion: Harmful if swallowed. May cause irritation of mouth, throat and digestive

tract. Ingestion of significant amounts may result in severe systemic

effects.

Chronic: Repeated and prolonged skin contact will result in severe irritation leading

to burns.

# 12: ECOLOGICAL INFORMATION

Environmental Assessment: When used and disposed as intended, no adverse environmental effects

are foreseen.

Mobility: Mobile liquid. Insoluble in water.

Degradability: Not readily biodegradable.

Bioaccumulation: Not Known.

Acute Fish Toxicity: Expected to be ecotoxic to fish/ daphnia/ algae.

# 13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

Unused Product: Classified as a special waste. May be reacted with base component to give

an inert polymeric material.

Used/ Contaminated Product: Classified as a special waste. Dispose off through an authorized waste

contractor to a licensed site.

Packaging: Must be disposed off through an authorized waste contractor.

Issue No.: 01 Rev. No.: 00 Flo-Grout EPCG – Hardener Page 4 of 6



# 14: TRANSPORT INFORMATION



UN Number: 1760

Transport Name: Corrosive substances.

Transport Type:		Class:	Pack Group:	Marine Pollutant
At Sea	IMDG	8	II	Yes
Air Transport	IATA/ICAO	8	П	
At land	RID/ADR	8	Ш	



#### 15: REGULATORY INFORMATION

**Hazard Label Data:** 





Corrosive

**Dangerous for** the environment

Named Ingredients: 2-piperazin-1-ylethylamine

Nonylphenol

**UN Number:** 1760

Risk Phrases: Harmful if swallowed. R22

> R34 Causes burns.

Irritating to eyes and skin. R36/38

R43 May cause sensitisation by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.

R62 Possible risk of impaired fertility.

R63 Possible risk of harm to the unborn child.

Safety Phrases:

S26 In case of contact with eyes, rinse immediately with

plenty of water and seek medical advice.

S28 After contact with skin, wash immediately with plenty of

S36/37/39 Wear suitable protective clothing, gloves and eye/face

protection.

**S45** In case of accident or if you feel unwell, seek medical

advice immediately (show the label where possible).

This material and its container must be disposed of as S60

hazardous waste.

# **16: OTHER INFORMATION**

Revised Date: Issue Date: 01/10/2015

Disclaimer: The information contained herein is derived from the best available sources and is

believed to be accurate. However, no guarantee is expressed or implied regarding

the accuracy of the data given in the use of this product.

Issue No.: 01 Rev. No.: 00 Flo-Grout EPCG - Hardener 6 of 6 Page