

# Material SAFETY DATA SHEET Flo-Grout UW

# 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Flo-Grout UW

Description: Non-shrink cementitious grout for underwater application

Manufacturer: Ayla for Building Materials Industry & Trade

Al-Karadeh, Arsat Al-Hindia, Baghdad

Tel.: +964 790 1488 730

www.dcp-int.com

Date Prepared: 27.11.14

MSDS Number: DCP/03/02/25

# 2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition: Portland cements, silica sand, additives.

 Hazardous Ingredient(s)
 Symbol
 Risk Phrases
 CAS No.
 %

 Portland cement
 Xi
 R20/21/22, 36/37/38, 43, 66
 65997-15-1
 25-45

Refer to Section 8 for Occupational Exposure Limits.

#### 3: HAZARDS IDENTIFICATION

Hazard Information: Harmful by inhalation, in contact with skin and if swallowed.

Irritating to eyes, skin and respiratory system. May cause sensitisation by skin contact.

Repeated exposure may cause skin dryness or cracking.

Classification: Xi. R20/21/22, 36/37/38, 43, 66

#### 4: FIRST AID MEASURES

Eyes: Irrigate immediately with copious quantities of water for several minutes.

Obtain medical attention if necessary.

Skin: Remove contaminated clothing immediately. Wash immediately with

copious quantities of water. Obtain medical advice if skin disorders

develop.

Inhalation: Remove from dust contaminated zone, obtain medical attention if

necessary.

Ingestion: Wash out mouth with water. Obtain medical attention. Do not induce

vomiting.

<b>Issue No.:</b> 0	1 <b>Rev. No.:</b> (	00 Flo-	-grout UW F	Page 1	ıuı	4	
---------------------	----------------------	---------	-------------	--------	-----	---	--



## 5: FIRE FIGHTING MEASURES

Flash Point: None.

Lower Explosive Limit: None.

Extinguishing Media: Same as surrounding fire.

Personal Protective Equipment: None.

## **6: ACCIDENTAL RELEASE MEASURES**

Personal Precautions: Wear rubber boots in addition to the recommended protective clothing.

Environmental Precautions: Prevent entry into drains, sewers and water courses.

Decontamination Procedures: Avoid the creation of dust in atmosphere. Gather into containers.

# 7: HANDLING AND STORAGE

Handling: Avoid creating dust. Avoid breathing dust. In case of insufficient

ventilation, wear suitable respiratory equipment. Avoid skin and eye

contact.

Storage: Store in cool and dry area.

## 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ingestion: Prevent eating, drinking or smoking in the area of product use.

Eye Contact: Safety glasses/goggles which can be tightly sealed.

Skin Contact: Protective gloves. Dustproof working clothes.

Respiratory Protection: Approved dust mask.

Engineering Controls: Use only in well ventilated areas. Local exhaust ventilation is

recommended.

Hygiene Measures: Avoid skin and eye contact.

**Exposure Limits:** 

Component	CAS	OSHA PEL	ACGIH TLV-
	number	(8-Hour TWA)	TWA
Portland Cement	65997-15-1	5 mg respirable dust/m3 15 mg total dust/m3	10 mg total dust/m3

**Issue No.:** 01 **Rev. No.:** 00 Flo-grout UW **Page** 2 of 4



## 9: PHYSICAL AND CHEMICAL PROPERTIES

Form: Powder

Colour: White/Grey

Odour: Odourless

pH (concentrate): Not applicable

Boiling Point (°C): Not applicable

Flash Point (closed cup) (°C): None

Autoflammability (°C): Not determined

Water Solubility: Can be mixed with water

# 10: STABILITY AND REACTIVITY

Stability: Stable.

Conditions to Avoid: Exposure to air. Contamination with water.

Chemical Incompatibility: Strong acids.

Hazardous Decomposition Products: None.

#### 11: TOXICOLOGICAL INFORMATION

#### **Health Effects**

Degradability:

On Eyes: Irritating and may injure eye tissue if not removed promptly.

On Skin: Irritation, See "chronic" effects.

By Inhalation: Irritation to respiratory system. Inflammation of the nasal mucous

membrane by exposure to cement dust.

By Ingestion: May cause irritation of mouth, throat and digestive tract.

Chronic: Cement, cementitious grouts and mortars are known to cause both irritant

and allergic contact dermatitis. Prolonged skin contact can result in

chemical burns.

#### 12: ECOLOGICAL INFORMATION

Environmental Assessment: Little detailed information is available on the ecological effects of this

Not readily biodegradable.

product, but its overall environmental impact is not regarded as

significant.

Mobility: Can be mixed with water.

Bioaccumulation: Not expected to be bioaccumulate.

Acute Fish Toxicity: Not expected to be ecotoxic to fish/daphnia/algae.

**Issue No.:** 01 **Rev. No.:** 00 Flo-grout UW **Page** 3 of 4



#### 13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

Unused Product: Dispose off in an approved manner. Small quantities maybe mixed with

water, allowed to harden and dispose of as low hazard waste.

Used/ Contaminated Product: As for unused product.

Packaging: The method of disposal must be acceptable to the local authority.

## 14: TRANSPORT INFORMATION

This product is **not** classified as dangerous for transport.

#### 15: REGULATORY INFORMATION

Hazard Label Data: Xi

×

**Irritant** 

Named Ingredients: Cement powders

Symbol (s): Xi

Risk Phrases:

R20/21/22 Harmful by inhalation, in contact with skin and if

swallowed.

R36/37/38 Irritating to eyes, skin and respiratory system.

R43 May cause sensitization by skin contact.

R66 Repeated exposure may cause skin dryness or cracking.

Safety Phrases:

S22 Do not breathe dust.

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with

plenty of water and seek medical advice.

S29 Do not empty into drains.

S36/37/39 Wear suitable protective clothing, gloves and eye/face

protection.

## **16: OTHER INFORMATION**

Issue Date: 27/11/2014 Revised Date:

Disclaimer: The information contained herein is derived from the best available sources and is

believed to be accurate. However, no guarantee is expressed or implied regarding

the accuracy of the data given in the use of this product.

**Issue No.:** 01 **Rev. No.:** 00 Flo-grout UW **Page** 4 of 4