

# Flocrete SP341

High range water reducing admixture with workability retention properties



## Description

Flocrete SP341 is a liquid concrete admixture formulated from selected polymers specially designed to enable the water content of the concrete to perform more effectively.

This effect can be used to improve workability, to increase ultimate strengths or to facilitate a reduction in the cement content while sustaining mix properties.

## Applications

- ▲ To increase workability retention of fresh concrete.
- ▲ To improve cohesion, minimizing segregation and improving surface finish.
- ▲ To produce high quality concrete of improved durability and water tightness.

## Advantages

- ▲ Higher strength with same cement content.
- ▲ Minimising segregation problems by improving cohesion.
- ▲ Improved workability reduces placing and compaction problems.
- ▲ Saving cement without affecting strength specifications.
- ▲ More durable concrete by considerable reduction in permeability.

## Compatibility

Flocrete SP341 can be used with all types of Portland cement and cement replacement materials. Flocrete SP341 is compatible with other DCP admixtures used in the same concrete mix.

If more than one type of admixture will be used in the concrete mix, they must be dispensed to the concrete separately.

## Standards

Flocrete SP341 complies with EN 934, Part 2, Tables 3.1 and 3.2 and ASTM C494, Type F and G, according to the dosage.

## Technical Properties @ 25°C:

Colour:	Brown liquid
Freezing point:	≈ -2°C
Specific gravity:	1.19 ± 0.03
Chloride content: EN 934, Part 2	Nil
Air entrainment:	Typically less than 2% additional air is entrained above control mix at normal dosages

## Method of Use

Flocrete SP341 should be added to the concrete with the mixing water to achieve optimum performance.

An automatic dispenser should be used to dispense the correct quantity of Flocrete SP341 to the concrete mix.

## Dosage

The guidance dosage of Flocrete SP341 is 0.3 - 1.5 kg per 100 kg of cementitious materials in the mix, including GGBFS, PFA or microsilica.

Representative trials should be conducted to determine the optimum dosage of Flocrete SP341 to meet the performance requirements by using the materials and conditions that will be experienced in use.

## Effects of Over Dosage

Flocrete SP341 over dosage will cause the following:

- ▲ Significant increase in retardation.
- ▲ Increase in workability.

Ultimate concrete strength will not be adversely affected and will generally be increased provided that proper concrete curing is maintained.

# Flocrete SP341

## Setting Time

Although the setting time is dependent on the dosage of Flocrete SP341, the following factors should be considered:

- i. Retardation is increased with a lower level of tricalcium in the cement.
- ii. Lower temperatures will delay the setting time.
- iii. Sulfate resisting cement gives higher retardation level than ordinary cement.
- iv. Using more than one type of admixture in the same concrete mix could affect the setting time.
- v. Retardation level is increased when cement replacement materials are used in the concrete mix.

## Cleaning

Flocrete SP341 can be washed immediately by cold water.

## Packaging

Flocrete SP341 is available in 25 litre pails, 210 litre drums and 1000 litre bulks supply.

## Storage

Flocrete SP341 has a shelf life of 12 months from date of manufacture if stored at a temperature within 2°C to 50°C.

If these conditions are exceeded, DCP Technical Department should be contacted for advice.

## Cautions

### Health and Safety

Flocrete SP341 is not classified as hazard material. Flocrete SP341 should not come into contact with skin and eyes.

In case of contact with eyes wash immediately with plenty of water and seek medical advice promptly.

For further information refer to the Material Safety Data Sheet.

### Fire

Flocrete SP341 is nonflammable.

## More from Don Construction Products

A wide range of construction chemical products are manufactured by DCP which include:

- ▲ Concrete admixtures.
- ▲ Surface treatments
- ▲ Grouts and anchors.
- ▲ Concrete repair.
- ▲ Flooring systems.
- ▲ Protective coatings.
- ▲ Sealants.
- ▲ Waterproofing.
- ▲ Adhesives.
- ▲ Tile adhesives and grouts.
- ▲ Building products.
- ▲ Structural strengthening.

#### Note:

We endeavour to ensure that any information, advice or recommendation we may give in product literature is accurate and correct. However, because we have no control over where and how products are applied, we cannot accept any liability arising from the use of the products.