

Material SAFETY DATA SHEET Gripdeck Flexcoat 100 - Base

1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Gripdeck Flexcoat 100 - Base

Description: Base component of two part elastomeric crack-bridging membrane for

Gripdeck system

Manufacturer: DCP Saudi Co

P.O. Box 66241, Riyadh 11576 Kingdom of Saudi Arabia

Tel. + 966 11 4612003 Fax: + 966 11 2792059

www.dcp-int.com

Date Prepared: 11.10.2020

MSDS Number: DCP/05/08/117-B

2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition: Epoxy/polyurethane resin with additives and fillers.

Hazardous Ingredient(s) Symbol Risk Phrases CAS No. %

Polyurethane-prepolymers - - 40 - 50 with blocked isocyante-groups

reaction product:

bisphenol-A-(epichlorhydrin) Xi, N R36/38, 43, 51/53 25068-38-6 7 - 15

epoxy resin

(number average molecular weight = 700)

Bisphenol F- Epoxyresin Xi, N R38, 43, 51/53 28064-14-4 5 - 10

Refer to Section 8 for Occupational Exposure Limits.

3: HAZARDS IDENTIFICATION

Hazard Information: Irritating to eyes and skin.

May cause sensitization by skin contact.

Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Classification: Xi, N. R36/38, 43, 51/53.

Tssue No.: 0	1 Rev. No.:	00	Grindeck Flexcoat 100 - Base	Page 1 of 5
1 155UE NO.: U	. Rev. 140.:	()()	CHIDDECK FIEXCOAL TOO - DASE	PAUE 1013



4: **FIRST AID MEASURES**

Eyes: Rinse opened eye for several minutes under running water. Then consult

doctor.

Skin: Instantly wash with water and soap and rinse thoroughly. If skin irritation

continues, consult a doctor.

Inhalation: Take affected persons into the open air and position comfortably.

Seek medical treatment in case of complaints.

Ingestion: Rinse mouth thoroughly. Do not induce vomiting. Never give anything by

mouth to an unconscious person. Get medical attention.

FIRE FIGHTING MEASURES

Flash Point: > 150 °C.

Special Exposure Hazards: Formation of toxic gases is possible during heating or in case of fire.

Extinguishing Media: CO₂, extinguishing powder or water jet. Fight larger fires with water jet or

alcohol-resistant foam - Do not use full water jets.

Personal Protective Equipment: Wear protective clothing and use self-contained breathing apparatus.

6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Wear protective clothing. Use breathing protection against the effects of

fumes/dust/aerosol.

Environmental Precautions: Do not allow product to reach sewage system or water bodies. Do not

allow to enter the ground/soil.

Decontamination Procedures: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust). Dispose of contaminated material as waste

according to item 13. Ensure adequate ventilation.

HANDLING AND STORAGE

Handling: Maintain good standards of personal hygiene. Do not use near sources of

> ignition. Avoid breathing fumes. Avoid skin and eye contact. Do not eat, drink or smoke whilst using this product. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.

Storage: Store only in the original container. Store in cool location. Provide floor

trough without outlet. Store away from foodstuffs. Keep container tightly

sealed.



8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ingestion: Prevent eating, drinking or smoking in the area of product use.

Eye Contact: Safety glasses or chemical goggles.

Skin Contact: Impervious gloves (e.g. PVC).

Respiratory Protection: In case of insufficient ventilation, wear suitable equipment.

Engineering Controls: Use only in well ventilated areas. Local exhaust ventilation is

recommended.

9: PHYSICAL AND CHEMICAL PROPERTIES

Form: Liquid

Colour: Yellowish

Odour: Weak, characteristic

Flash Point (closed cup) (°C): > 150 Boiling Point (°C): > 200

Explosive Properties (%): Not applicable Freezing Point ($^{\circ}$ C): Not applicable Relative Density (@25 $^{\circ}$ C): 1.00 ± 0.05

Water Solubility: Not miscible

10: STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to Avoid: Excessive heating. Humidity. Air exposure.

Chemical Incompatibility: Strong oxidizing agents, alkali, amines and acids.

Hazardous Decomposition Products: Formation of toxic gases is possible during heating or in case of fire.

11: TOXICOLOGICAL INFORMATION

The following toxicological assessment is based on knowledge of the toxicity of the product's components. Expected oral LD50, rat > 2000 mg/ kg

Health Effects

On Eyes: Causes serious eye damage.

On Skin: Causes severe skin burns and eye damage.

By Inhalation: Irritant.
By Ingestion: Irritant.

Chronic: Not applicable.

Tecus No.	Λ1	Doy No.	00	Gripdeck Flexcoat 100 - Base	Dago	2 of E
Issue No.:	01	Rev. No.:	UU	Gripdeck Flexcoat 100 - Base	Page	3 of 5



12: ECOLOGICAL INFORMATION

Environmental Assessment: When used and disposed off as intended, no adverse environmental

effects are foreseen.

Mobility: Insoluble in water.

Degradability: No information available.

Bioaccumulation: No information available.

Acute Fish Toxicity: Toxic to aquatic organisms.

13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

Unused Product: Dispose off through an authorized waste contractor to a licensed site.

Used/ Contaminated Product: As for unused product.

Packaging: Disposal must be made according to official regulations.

14: TRANSPORT INFORMATION



UN/SI Number: 3082

Transport Name: Environmentally hazardous substance, liquid, n.o.s.

Transport Type:		Class:	Pack Group:	Item:	Marine Pollutant:
At Sea	IMO/IMDG	9	III		Yes
Air Transport	IATA/ICAO	9	III		
At land	RID/ADR	9	III		



15: REGULATORY INFORMATION

Hazard Label Data:

Xn

N Y

Harmful

Dangerous for the environment

Risk Phrases:

R36/38 Irritating to eyes and skin.

R43 May cause sensitization by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.

Safety Phrases:

S23 Don not breather fumes.

S24/25 Avoid contact with skin and eyes.

S36/37 Wear suitable protective clothing and gloves.

S38 In case of insufficient ventilation, wear suitable

respiratory equipment.

S45 In case of accident or if you feel unwell, seek medical

advice immediately (show the label where possible).

S53 Avoid exposure - obtain special instructions before use.

S61 Avoid release to the environment. Refer to special

instructions/safety data sheets.

S63 In case of accident by inhalation, remove casualty to

fresh air and keep at rest.

16: OTHER INFORMATION

Issue Date: 11.10.2020

Revised Date:

Disclaimer: The information contained herein is derived from the best available sources and is

believed to be accurate. However, no guarantee is expressed or implied regarding

the accuracy of the data given in the use of this product.