

Grundix® STOP STAIN

Stain blocking primer



DESCRIPTION

Grundix STOP STAIN is a ready to use, water based acrylic primer with excellent adhesion to a variety of construction surfaces specially designed to block and isolate substrate grease and different dried stains before applying finishing paints.

Grundix STOP STAIN acts as an undercoat and can be used under any type of acrylic and latex paint. It dries to provide a uniform matte coating that covers very well and perfectly isolates discoloration, enabling a uniform surface.

APPLICATIONS

Grundix STOP STAIN blocks and isolates discoloration, substrate grease, and different oil and water dried stains before painting walls and ceilings inside residential, office and public buildings.

ADVANTAGES

- » Excellent adhesion to the concrete.
- » One-component, ready to use material.
- » Easy application.
- » Perfectly isolates discoloration, enabling a uniform surface.
- » Blocks variety of stains on various substrates.
- » Improves the subsequent top finish by sealing stains underneath.
- » Can be used under any type of acrylic and latex paints.
- » Excellent adhesion to a variety of construction surfaces.

METHOD OF USE

SURFACE PREPARATION

Surfaces should be clean, sound, dry, as well as free from dirt, dust, fungus, and wax and loose particles. Remnants of paint, plaster, or other layers not adhered to the substrate should be removed.

APPLICATION

Stir Grundix STOP STAIN thoroughly before use. Grundix STOP STAIN can be applied by brush or roller. Do not dilute the material.

It is recommended to apply a minimum of two coats of Grundix STOP STAIN for optimum performance and stain blocking.

TECHNICAL PROPERTIES:

Colour:	White
Density:	1.40 ± 0.05 g/cm ³
Solid content:	56 ± 2%
Drying time: EN ISO 3678	2 - 4 hr
pH:	7 - 9
VOC:	≤ 20 g/ltr (comply with LEED)

Apply the first coat at coverage of 10 m²/litre per coat and leave to dry for approximately 2 hours (depending on the specific conditions) before applying the second coat. In cool, damp weather drying may last longer.

Notes:

- » Grundix STOP STAIN is used only at temperatures of the surface, air and material itself above 5°C.
- » Not apply on wet, frozen or covered with condensation surfaces.

CLEANING

All tools should be cleaned immediately after finishing by clean water and detergent. Hardened materials can be cleaned mechanically.

PACKAGING

Grundix STOP STAIN is available in 1.2 kg packs.

COVERAGE

Approximately 10m²/ litre per coat, depending on substrate.

STORAGE

Grundix STOP STAIN has a shelf life of 12 months from date of manufacture if stored in proper conditions, at temperatures range between 5°C and 35°C in its original unopened packing. Keep away from frost.

If these conditions are exceeded, DCP Technical Department should be contacted for advise.

Don Construction Products Bulgaria EAD

Tsvetan Lazarov 152
Techno Park, Sofia 1582
Bulgaria
info.bulgaria@dcp-int.com
www.dcp.bg



Grundix® STOP STAIN

CAUTIONS

HEALTH AND SAFETY

Grundix STOP STAIN does not fall within the list of dangerous substances according to current regulations. Avoid contact with skin and eyes. Sprayed places on the skin should immediately be washed with water. In case of contact with eyes wash immediately with plenty of water and seek medical advice.

For further information refer to the Material Safety Data Sheet.

FIRE

Grundix STOP STAIN is nonflammable.

MORE FROM DON CONSTRUCTION PRODUCTS

A wide range of construction chemical products are manufactured by DCP which include:

- » Concrete admixtures.
- » Surface treatments
- » Grouts and anchors.
- » Concrete repair.
- » Flooring systems.
- » Protective coatings.
- » Sealants.
- » Waterproofing.
- » Adhesives.
- » Tile adhesives and grouts.
- » Building products.
- » Structural strengthening.

Don Construction Products Bulgaria EAD

Tsvetan Lazarov 152
Techno Park, Sofia 1582
Bulgaria
info.bulgaria@dcp-int.com
www.dcp.bg

Note:

We endeavour to ensure that any information, advice or recommendation we may give in product literature is accurate and correct. However, because we have no control over where and how products are applied, we cannot accept any liability arising from the use of the products.

www.dcp-int.com

DCP Building Excellence