

Hyperplast ES250W

Premium quality plasticising admixture for concrete masonry products



DESCRIPTION

Hyperplast ES250W is a chloride free, premium quality high range water reducing admixture based on polycarboxylic polymers with selective additives which are especially formulated for factory-line concrete production such as concrete blocks and bricks.

Hyperplast ES250W can significantly assist in the production of a more uniform and consistent quality mixes in factory-line concrete products, it can be also used for light weight concrete production.

APPLICATIONS

Hyperplast ES250W can be successfully used in the following applications:

- » Concrete blocks and bricks.
- » Dry cast concrete.
- » Concrete roofing tiles.
- » Concrete pipes.

ADVANTAGES

- » Improves the cohesion of the concrete mix.
- » Extends the moulds life.
- » Improves compressive strength.
- » Reduces water absorption.

COMPATIBILITY

Hyperplast ES250W is suitable for use with all types of Portland cement and cement replacement materials. Hyperplast ES250W should not be used in conjunction with other admixtures unless DCP's Technical Department approval is obtained.

STANDARDS

Hyperplast ES250W complies with IS 9103:1999 and ASTM C494 as Type A and F, depending on dosage used.

METHOD OF USE

Hyperplast ES250W should be added to the concrete with the mixing water to achieve optimum performance.

An automatic dispenser should be used to dispense the correct quantity of Hyperplast ES250W to the concrete mix.

TECHNICAL PROPERTIES @ 21°C:

Colour:	Pale yellowish to brownish liquid
Freezing point:	≈ -5°C
Specific gravity:	1.02 ± 0.02
pH:	6 - 7
Chloride content:	Chloride free

DOSAGE

The recommended dosage of Hyperplast ES250W is 0.5 - 3.5 litre per 100 kg of cement or cementitious materials in the mix including GGBFS, PFA or micro-silica.

Representative trials should be first conducted to determine the optimum dosage of Hyperplast ES250W to meet the performance requirements by using the materials and conditions in actual use.

EFFECTS OF OVER DOSAGE

Overdosage of Hyperplast ES250W will cause the following:

- » Increase in retardation.
- » Increase in workability.

CLEANING

Clean Hyperplast ES250W with fresh cold water.

PACKAGING

Hyperplast ES250W is available in 25 litre jerrycan, 210 litre drums and 1000 litre bulks supply.

STORAGE

Hyperplast ES250W has a shelf life of 12 months from date of manufacturing if stored at temperatures between 2°C and 50°C.

If these conditions are exceeded, contact DCP Technical Department for advice.



Hyperplast ES250W

CAUTIONS

HEALTH AND SAFETY

Hyperplast ES250W is not classified as a hazardous material. Hyperplast ES250W should not come into contact with skin and eyes.

In case of contact with eyes, immediately flush with plenty of water and seek medical attention.

For further information, refer to the Material Safety Data Sheet.

FIRE

Hyperplast ES250W is nonflammable.

MORE FROM DON CONSTRUCTION PRODUCTS

A wide range of construction chemical products are manufactured by DCP which include:

- » Concrete admixtures.
- » Surface treatments
- » Grouts and anchors.
- » Concrete repair.
- » Flooring systems.
- » Protective coatings.
- » Sealants.
- » Waterproofing.
- » Adhesives.
- » Tile adhesives and grouts.
- » Building products.
- » Structural strengthening.

Don Construction Chemicals India Private Limited

Kaveripettai, Thiruvallur Dist., Chennai, Tamil Nadu

RIICO Industrial Area, Manda Chomu, Jaipur

India

info.india@dcp-int.com; marketing.india@dcp-int.com

www.dcp-int.com

Note:

We endeavour to ensure that any information, advice or recommendation we may give in product literature is accurate and correct. However, because we have no control over where and how products are applied, we cannot accept any liability arising from the use of the products.