

Hyperplast PC853

New generation hyperplasticising admixture for extended slump retention



Description

Hyperplast PC853 is a new generation hyperplasticiser for concrete, specially designed to produce concrete with extensive workability.

This effect can be used to produce low viscosity concrete for mid-to-high scale projects or when pumping concrete over long distances is required.

Applications

- ▲ For high levels of concrete pumping.
- ▲ Suitable for long distances with extended slump retention.
- ▲ Low viscosity concrete with Enhanced compressive strength.
- ▲ Structures with congested reinforcement.
- ▲ Pre-stressed concrete.
- ▲ Improved cohesion allows for use in mass concrete pours and piling.

Compatibility

Hyperplast PC853 can be used with all types of Portland cement and cement replacement materials. Hyperplast PC853 is compatible with other DCP admixtures used in the same concrete mix.

If more than one type of admixture will be used in the concrete mix, they must be dispensed to the concrete separately.

Method of Use

Hyperplast PC853 should be added to the concrete with the mixing water to achieve optimum performance.

An automatic dispenser should be used to dispense the correct quantity of Hyperplast PC853 to the concrete mix.

Dosage

The guidance dosage of Hyperplast PC853 is 1.0 - 3.5 litre per 100 kg of cementitious materials in the mix, including GGBFS, PFA or microsilica.

Representative trials should be conducted to determine the optimum dosage of Hyperplast PC853 to meet the performance requirements by using the materials and conditions in actual use.

Technical Properties @ 27°C:

Colour:	Light yellow
Specific gravity:	1.07 ± 0.02
pH:	5 - 7

Effects of Over Dosage

Overdosage of Hyperplast PC853 will cause the following:

- ▲ Increase in workability.

Ultimate concrete strength will not be adversely affected and will generally be increased provided that proper concrete curing is maintained.

Cleaning

Clean Hyperplast PC853 with fresh cold water.

Packaging

Hyperplast PC853 is available in 25 litre jerrycan, 210 litre drums and 1000 litre bulk supply.

Storage

Hyperplast PC853 has a shelf life of 12 months from date of manufacture if stored at temperatures between 2°C and 50°C.

If these conditions are exceeded, contact DCP Technical Department for advice.

Cautions

Health and Safety

Hyperplast PC853 is not classified as a hazardous material. Hyperplast PC853 should not come into contact with skin and eyes.

In case of contact with eyes, immediately flush with plenty of water and seek medical attention.

For further information, refer to the Material Safety Data Sheet.

Hyperplast PC853

Fire

Hyperplast PC853 is nonflammable.

More from Don Construction Products


A wide range of construction chemical products are manufactured by DCP which include:


- ▲ Concrete admixtures.
- ▲ Surface treatments
- ▲ Grouts and anchors.
- ▲ Concrete repair.
- ▲ Flooring systems.
- ▲ Protective coatings.
- ▲ Sealants.
- ▲ Waterproofing.
- ▲ Adhesives.
- ▲ Tile adhesives and grouts.
- ▲ Building products.
- ▲ Structural strengthening.

Note:

We endeavor to ensure that any advice, recommendation or information we may give in product literature is accurate and correct. However, due to the fact that we have no direct or continuous control over where or how the products are applied, DCP cannot accept any liability either directly or indirectly arising from the use of DCP products, whether or not in accordance with any advice, specification, recommendation or information given by us.

 expertise

 quality

 full range

www.dcp-int.com