

NEOPRENE PRIMER

General purpose neoprene primer



TECHNICAL DATA SHEET PUBLISHED NOV 2021

PRODUCT FEATURES

Neoprene Primer is designed to be used as a general purpose primer for dusty or absorbent surfaces to promote adhesion and to prevent unacceptably rapid drying of adhesive and smoothing underlayments. It is nonflammable, suitable for use over normal underfloor heating installations and is coloured green to provide the user with visual control of coverage uniformity.

For use on absorbent surfaces such as concrete, sand/cement and synthetic anhydrite screeds; plywood, hardboard and chipboard.

MATERIALS SUPPLIED

Single component 5 litre bottle.

STORAGE

Protect from frost and store under dry warehouse conditions at a temperature between 10°C and 30°C.

SHELF LIFE

12 months in unopened containers and stored under good conditions.

COVERAGE

5 litres of Neoprene Primer mixed with 20 litres of water will cover approximately 100m².

TECHNICAL INFORMATION

Colour	Green
Solids Content%	32 – 36%
Drying time @ 20°C	1 hour

APPLICATION INSTRUCTIONS

SURFACE PREPARATION

Floor surfaces must be sound, smooth, dry and free from contaminants that may prevent adhesion. Concrete and sand/cement screeds must be fully cured and any laitance or surface treatments must be removed. Existing adhesive should be mechanically removed until only a minimal firmly bonded residue remains.

The temperature of the surface must be above 10°C when the primer is applied to the subfloor and underfloor heating must be off for at least 48 hours before and after application. Ensure the subfloor is dry and incorporates an effective damp proof membrane.

MIXING

SHAKE WELL BEFORE USE. For absorbent surfaces add one part Neoprene Primer to 4 parts of clean cold water and stir until thoroughly dispersed. Apply the Neoprene Primer evenly to the whole surface using a soft broom/brush and allow it to dry completely. Apply a further applications, adding one part Neoprene Primer to 3 parts clean cold water and allow to dry thoroughly. Ensure sufficient coats of Neoprene primer are installed to reduce the risk of air transfer from dry, porous substrates.

Refer to General Guidance notes below.

CLEANING

Wash with warm water immediately after use.

PRECAUTIONS

Avoid excessive trafficking of the subfloor once the primer has dried.

HEALTH & SAFETY

Please consult the appropriate Material Safety Data Sheets prior to using Neoprene Primer.

GENERAL GUIDANCE

This data sheet is for general guidance purposes only and may contain information that is inappropriate for certain conditions of use. Accordingly, all recommendations and suggestions are made without guarantee. Further information is available from our Technical Department

Don Construction Products Ltd.
Helions Bumpstead Road, Haverhill CB9
United Kingdom

info@dcp-int.co.uk

Don Construction Products Ltd.
Helions Bumpstead Road, Haverhill CB9
United Kingdom


info@dcp-int.co.uk


Don Construction Products Ltd Hawthorn House, Helions Bumpstead Road,
Haverhill, Suffolk CB9 7AA, UK T: +44 (0) 1440 766360


Note:

We endeavour to ensure that any information, advice or recommendation we may give in product literature is accurate and correct. However, because we have no control over where and how products are applied, we cannot accept any liability arising from the use of the products.

www.dcp-int.com

 expertise

 quality

 full range

05-0135-A-2021