

Plasti-board Method Statement (Waterproofing protection board)

Section A : General Comments

Equipment

It is suggested that the following list of equipment is adopted as a minimum requirement:

<i>Personal protection</i>	:	<i>Protective overalls</i>
	:	<i>gloves and goggles</i>
<i>Equipment</i>	:	<i>Cutting knife</i>

Section B : Application

1.0 Application

- 1.1 Plasti-board should be laid over the waterproofing material continuously by tightly fitting all edges together.
- 1.2 For application over hot applied liquid membrane, Plasti-board is simply laid on top of the hot liquid asphalt while it is tacky.
- 1.3 For application over torch applied membranes, the exposed side of the membrane should be lightly torched in separate spots, when the top exposed layer of the membrane changes into a sticky shiny layer, Plasti-board is applied on to it by gentle pressure.
- 1.4 For application over rubber based waterproof membrane, an adhering agent should be used between the waterproof membrane and the protection board to insure boards are fixed in place.
- 1.5 A 3 – 5 cm is the recommended overlap.
- 1.6 Alternatively you can use bituminous sealant as adhesive for Plasti-board

Section C : Approval and variations

This method statement is offered by DCP as a 'standard proposal' for the application of **Plati-board**. It remains the responsibility of the Engineer to determine the correct method for any given application. Where alternative methods are to be used, these must be submitted to DCP for approval, in writing, prior to commencement of any work. DCP will not accept responsibility or liability for variations to the above method statement under any other condition.