

# Probuild PF200

Ready to use acrylic pinhole filler and smooth finishing paste



## Description

Probuild PF200 is a ready to use high performance acrylic coat specially designed to level surfaces and fill pinholes prior to the application of protective coatings.

## Applications

- ▲ Probuild PF200 is designed to be used in conjunction with Repcoat to completely fill pinholes and irregular surfaces to produce a smooth even finish.
- ▲ Probuild PF200 can also be applied over other existing coats. However, it is always recommended to conduct adhesion tests to ensure the compatibility of Probuild PF200 and the coated surface.

For more information, please refer to the Technical Department in DCP.

## Advantages

- ▲ Excellent adhesion to the substrates.
- ▲ Can be applied on vertical and horizontal surfaces.
- ▲ Easy to apply, ready to use single component.
- ▲ Suitable drying time.
- ▲ Environmentally friendly, water based material.

## Method of Use

### Surface Preparation

All surfaces should be sound and free from dust, oil and foreign matter. Normally, no primer is required for the application of Probuild PF200.

### Application

Probuild PF200 should be firmly applied using a proper trowel onto the prepared surfaces so that all irregularities and pinholes are filled with the material and produce a smooth finish.

Probuild PF200 should be free from any contamination such as grease, dust, cement or any loose materials prior to applying the topcoat to ensure high adhesion between the topcoat and Probuild PF200.

## Technical Properties:

Appearance:	White lump-free paste
Density:	$1.7 \pm 0.1 \text{ g/cm}^3$
Application thickness:	Up to 1.5 mm per coat
Solid content:	$70 \pm 5\%$ (by weight)
pH:	8 - 9

## Packaging

Probuild PF200 is available in 5 and 25 kg packs.

## Coverage

Approximately  $1.70 \text{ kg/m}^2$  at 1 mm thickness.

## Storage

Keep tightly sealed, store under cover in a dry area at room temperature, protect from freezing, exposure to extreme heat and direct sunlight.

## Shelf Life

Probuild PF200 has a shelf life of 12 months from date of manufacturing if stored in original unopened packaging.

If these conditions are exceeded, DCP Technical Department should be contacted for advice.

## Cautions

### Health and Safety

Wear suitable protective clothing, gloves and eye/face protection. Should accidental skin contact occur, wash immediately with clean water.

For further information refer to the Material Safety Data sheet.

### Fire

Probuild PF200 is nonflammable.

# Probuild PF200

## More from Don Construction Products

A wide range of construction chemical products are manufactured by DCP which include:

- ▲ Concrete admixtures.
- ▲ Surface treatments
- ▲ Grouts and anchors.
- ▲ Concrete repair.
- ▲ Flooring systems.
- ▲ Protective coatings.
- ▲ Sealants.
- ▲ Waterproofing.
- ▲ Adhesives.
- ▲ Tile adhesives and grouts.
- ▲ Building products.
- ▲ Structural strengthening.

### Note:

We endeavor to ensure that any advice, recommendation or information we may give in product literature is accurate and correct. However, due to the fact that we have no direct or continuous control over where or how the products are applied, DCP cannot accept any liability either directly or indirectly arising from the use of DCP products, whether or not in accordance with any advice, specification, recommendation or information given by us.

[www.dcp-int.com](http://www.dcp-int.com)

