

Material SAFETY DATA SHEET Profiber CW System

1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Profiber CW System

Chemical Family: Heavy duty carbon fibre reinforced polymer wrap structural

strengthening system.

Manufacturer: Don Construction Chemicals India LTD

Tel. +914426185340/41/42

www.dcp-int.com

Date Prepared: 24.11.2013

MSDS Number: DCP-IND/12/02

2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition: Carbon fiber.

Hazardous ingredient(s) Symbol Risk Phrases CAS No. %

Carbon fiber Xi R36/38, 43 7440-44-0 98 - 99

Refer to Section 8 for Occupational Exposure Limits.

3: HAZARDS IDENTIFICATION

Hazard information: Irritating to eyes and skin.

May cause sensitization by skin contact.

Classification: Xi, N. R36/38, 43

4: FIRST AID MEASURES

Eyes: Irrigate immediately with copious quantities of water for 15 minutes.

Obtain medical attention urgently.

Skin: Wash immediately with soap and water or suitable skin cleanser. Remove

contaminated clothes and shoes. Obtain medical advice if skin disorders

develop.

Inhalation: Remove from exposure, obtain medical attention if respiratory irritation

develops or if breathing becomes difficult.

Ingestion: Rinse mouth thoroughly. Drink plenty of water. Induce vomiting. Obtain

medical attention. Beware of aspiration if vomiting occurs.

Issue No.: 01 **Rev. No.:** 00 Profiber CW System **Page** 1 of 23



5: FIRE FIGHTING MEASURES

Flash point (Closed Cup): >1000°C.

Extinguishing media: Carbon dioxide, powder, foam or water.

Personal protective equipment: Self-contained breathing apparatus and protective clothing.

Special Exposure hazards: Toxic fumes. Carbon Oxides.

6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Wear suitable protective clothing, gloves and eye/face protection.

Environmental Precautions: Prevent entry into drains, sewers and water courses.

Decontamination Procedures: Soak up with inert absorbent such as sand. Gather into labeled

containers. Dispose off as applicable regulations.

7: HANDLING AND STORAGE

Handling: Maintain good standards of personal hygiene. Avoid skin and eye contact.

Do not eat, drink or smoke whilst using this product. Ensure adequate

ventilation.

Storage: Keep container tightly closed in a cool dry area.

8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Eye protection: Safety glasses/goggles.

Skin protection: Impervious gloves (e.g. PVC). Suitable protective clothing.

Respiratory protection: Organic chemical cartridge respirator, if needed.

Hygiene measures: Change contaminated clothing and clean before re-use.

Engineering controls: No specific ventilation requirements noted.

Exposure guidelines: None assigned.

Issue No.: 01 **Rev. No.:** 00 Profiber CW System **Page** 2 of 23



9: PHYSICAL AND CHEMICAL PROPERTIES

Form: Resin impregnated

Color: Black

Odour: Odourless

pH (concentrate): Not applicable

Boiling Point ($^{\circ}$ C): >1000 Flash Point (closed cup) ($^{\circ}$ C): >1000

Autoflammability (°C): Not determined

Explosive Properties (%): Not Known

Relative Density (@25°C): N/A Water Solubility: N/A

10: STABILITY AND REACTIVITY

Stability: Stable: reacts with compounds containing amino, hydroxyl or carboxyl

groups to give stable, cross linked materials.

Conditions to Avoid: Excess heat.

Chemical incompatibility: Strong acids. Bases. Strong oxidizing agents.

Hazardous Decomposition Products: Toxic materials, avoid inhalation.

11: TOXICOLOGICAL INFORMATION

Health Effects

On Eyes: May cause irritation.

On Skin: Moderate irritation (rabbit).

By Inhalation: May cause respiratory irritation.

By Ingestion: May cause irritation of mouth, throat and digestive tract.

Chronic: Repeated and prolonged skin contact may lead to skin disorders.

Issue No.: 01 **Rev. No.:** 00 Profiber CW System **Page** 3 of 23



12: ECOLOGICAL INFORMATION

Environmental Assessment: When used and disposed as intended, no adverse environmental effects

are foreseen.

Mobility: Viscous liquid. Insoluble in water.

Degradability: Not readily biodegradable.

Bioaccumulation: Not expected to be bioaccumulate.

Acute fish toxicity: Ecotoxic to fish/ daphnia/ algae.

13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

Unused Product: Dispose off through an authorized waste contractor to a licensed site.

Used/ Contaminated Product: As for unused product.

Packaging: Must be disposed off through an authorized waste contractor.

14: TRANSPORT INFORMATION

The product is **not** classified as dangerous for transport.

15: REGULATORY INFORMATION

The product is **not** classified as dangerous for use.

Risk Phrases:

R36/38 Irritating to eyes and skin.

R43 May cause sensitization by skin contact.

Safety Phrases:

S24/25 Avoid contact with skin and eyes.

Wear suitable gloves and eye/face protection.

16: OTHER INFORMATION

Issue Date: 24/11/2013 Revised Date:

Disclaimer: The information contained herein is derived from the best available sources and is

believed to be accurate. However, no guarantee is expressed or implied regarding

the accuracy of the data given in the use of this product.

Issue No.: 01 **Rev. No.:** 00 Profiber CW System **Page** 4 of 23



Material SAFETY DATA SHEET Profiber CW System

1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Quickmast CW Primer

Chemical Family: Base component of two part Epoxy primer.

Manufacturer: Don Construction Chemicals India LTD

Tel. +914426185340/41/42

www.dcp-int.com

Date Prepared: 24.11.2013

MSDS Number: DCP-IND/12/02-B

2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition: Epoxy resin, epoxy diluent.

Hazardous ingredient(s) Symbol Risk Phrases CAS No. %
Epoxy resin Xi, N R36/38, 43, 51/53 25068-38-6 70

(Number average molecular weight <700)

Refer to Section 8 for Occupational Exposure Limits.

3: HAZARDS IDENTIFICATION

Hazard information: Irritating to eyes and skin.

May cause sensitization by skin contact.

Toxic to aquatic organism, may cause long-term affects in the aquatic

Environment.

Classification: Xi, N. R36/38, 43, 51/53

4: FIRST AID MEASURES

Eyes: Irrigate immediately with copious quantities of water for 15 minutes.

Obtain medical attention urgently.

Skin: Wash immediately with soap and water or suitable skin cleanser. Remove

contaminated clothes and shoes. Obtain medical advice if skin disorders

develop.

Inhalation: Remove from exposure, obtain medical attention if respiratory irritation

develops or if breathing becomes difficult.

Ingestion: Rinse mouth thoroughly. Drink plenty of water. Do not induce vomiting.

Obtain medical attention. Beware of aspiration if vomiting occurs.

Issue No.: 01 **Rev. No.:** 00 Profiber CW System **Page** 5 of 23



5: FIRE FIGHTING MEASURES

Flash point (Closed Cup): >200°C.

Extinguishing media: Carbon dioxide, powder, foam or water.

Personal protective equipment: Self-contained breathing apparatus.

Special Exposure hazards: Toxic fumes. Carbon Oxides.

6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Wear suitable protective clothing, gloves and eye/face protection.

Environmental Precautions: Prevent entry into drains, sewers and water courses.

Decontamination Procedures: Soak up with inert absorbent such as sand. Gather into labeled

containers. Dispose off as applicable regulations.

7: HANDLING AND STORAGE

Handling: Maintain good standards of personal hygiene. Avoid skin and eye contact.

Do not eat, drink or smoke whilst using this product. Ensure adequate

ventilation.

Storage: Keep container tightly closed in a cool dry area.

8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Eye protection: Safety glasses/goggles.

Skin protection: Impervious gloves (e.g. PVC). Suitable protective clothing.

Respiratory protection: Organic chemical cartridge respirator, if needed.

Hygiene measures: Change contaminated clothing and clean before re-use.

Engineering controls: No specific ventilation requirements noted.

Exposure guidelines: None assigned.

Issue No.: 01 **Rev. No.:** 00 Profiber CW System **Page** 6 of 23



9: PHYSICAL AND CHEMICAL PROPERTIES

Form: Liquid
Color: Clear
Odour: Mild

PH (concentrate): Not applicable

Boiling Point ($^{\circ}$ C): >200 Flash Point (closed cup) ($^{\circ}$ C): >200

Autoflammability (°C): Not determined

Explosive Properties (%): Not Known

Relative Density (@25°C): 1.12

Water Solubility: Insoluble

10: STABILITY AND REACTIVITY

Stability: Stable: reacts with compounds containing amino, hydroxyl or carboxyl

groups to give stable, cross linked materials.

Conditions to Avoid: None Known.

Chemical incompatibility: Strong acids. Strong alkalis. Strong oxidizing agents.

Hazardous Decomposition Products: Thermal decomposition yield oxides of carbon, toxic fumes.

11: TOXICOLOGICAL INFORMATION

The following toxicological assessment is based on knowledge of the toxicity of the product's components. Acute Oral effect (LD50)>5000mg/kg. Classified as moderate sensitizer.

Health Effects

On Eyes: Slight irritation (rabbit).

On Skin: Moderate irritation (rabbit).

By Inhalation: May cause respiratory irritation.

By Ingestion: May cause irritation of mouth, throat and digestive tract.

Chronic: Repeated and prolonged skin contact may lead to skin disorders.

Issue No.: 01 **Rev. No.:** 00 Profiber CW System **Page** 7 of 23



12: ECOLOGICAL INFORMATION

Environmental Assessment: When used and disposed as intended, no adverse environmental effects

are foreseen.

Mobility: Viscous liquid. Insoluble in water.

Degradability: Not readily biodegradable.

Bioaccumulation: Not expected to be bioaccumulate.

Acute fish toxicity: Ecotoxic to fish/ daphnia/ algae.

13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

Unused Product: Dispose off through an authorized waste contractor to a licensed site.

Used/ Contaminated Product: As for unused product.

Packaging: Must be disposed off through an authorized waste contractor.

14: TRANSPORT INFORMATION

This product is NOT classified as dangerous for transport.

15: REGULATORY INFORMATION

Hazard Label Data:

Risk Phrases:

R36/38 Irritating to eyes and skin.

R43 May cause sensitization by skin contact.

Safety Phrases:

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with

plenty of water and seek medical advice.

Wear suitable gloves and eye/face protection.

16: OTHER INFORMATION

Issue Date: 24/11/2013 Revised Date:

Disclaimer: The information contained herein is derived from the best available sources and is

believed to be accurate. However, no guarantee is expressed or implied regarding

the accuracy of the data given in the use of this product.

Issue No.: 01 **Rev. No.:** 00 Profiber CW System **Page** 8 of 23



Material SAFETY DATA SHEET Quickmast CW Primer - Hardener

1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Quickmast CW Primer- Hardener

Chemical Family: Hardener component of two part Epoxy primer.

Manufacturer: Don Construction Chemicals India LTD

Tel. +914426185340/41/42

www.dcp-int.com

Date Prepared: 24.11.2013

MSDS Number: DCP-IND/12/02

2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition: Epoxy curing agent and plasticizer.

Hazardous ingredient(s) Symbol Risk Phrases CAS No. %

Epoxy curing agent C R21/22, 34, 43, 52/53 2855-13-2 80

Refer to Section 8 for Occupational Exposure Limits.

3: HAZARDS IDENTIFICATION

Hazard information: Causes burns.

Harmful by inhalation, in contact with skin and if swallowed.

May cause sensitization by skin contact.

Harmful to aquatic organism, may cause long-term affects in the aquatic

Environment.

Classification: C, R21/22, 34, 43, 52/53

4: FIRST AID MEASURES

Eyes: Irrigate immediately with copious quantities of water for 15 minutes.

Obtain medical attention immediately.

Skin: Wash immediately with soap and water or suitable skin cleanser. Remove

contaminated clothes and shoes. Obtain medical advice if irritation

persists.

Inhalation: Remove from exposure, obtain medical attention if respiratory irritation

develops or if breathing becomes difficult.

Ingestion: Drink plenty of water. Do not induce vomiting. Obtain medical attention.

Beware of aspiration if vomiting occurs.

Issue No.: 01 **Rev. No.:** 00 Profiber CW System **Page** 9 of 23



5: FIRE FIGHTING MEASURES

Flash point (Closed Cup): >100°C.

Extinguishing media: Carbon dioxide, powder, foam or water.

Personal protective equipment: Self-contained breathing apparatus. Standard aluminized suit.

Special Exposure hazards: Toxic fumes. Nitrogen compounds.

6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Wear suitable protective clothing, gloves and eye/face protection.

Environmental Precautions: Prevent entry into drains, sewers and water courses.

Decontamination Procedures: Soak up with inert absorbent like sand. Gather into labeled containers.

Dispose off as applicable regulations.

7: HANDLING AND STORAGE

Handling: Maintain good standards of personal hygiene. Avoid skin and eye contact.

Do not eat, drink or smoke whilst using this product. Ensure adequate

ventilation.

Storage: Keep container tightly closed in a cool dry area. Keep away from food

containers.

8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Eye protection: Tightly sealed safety glasses/goggles.

Skin protection: Impervious gloves (e.g. PVC). Suitable protective clothing.

Respiratory protection: Breathing filters apparatus.

Hygiene measures: Change contaminated clothing and clean before re-use.

Engineering controls: Use only in well ventilated area. Local exhaust ventilation is

recommended.

Exposure guidelines: None assigned.

Issue No.: 01 Rev. No.: 00 Profiber CW System Page 10 of 23



9: PHYSICAL AND CHEMICAL PROPERTIES

Form: Liquid

Color: Yellowish to clear

Odour: Amine
PH (concentrate): 11.5
Boiling Point (°C): >200
Flash Point (closed cup) (°C): >100

Autoflammability (°C): Autoignition temperature>300

Explosive Properties (%): Lower Explosive Limit (LEL): 1.3% (by volume).

Upper Explosive Limit (UEL): 13% (by volume).

Relative Density (@25°C): 0.99

Water Solubility: Insoluble

10: STABILITY AND REACTIVITY

Stability: Stable if used as directed.

Conditions to Avoid: Any source of ignition. Temperature below 0°C.

Chemical incompatibility: Strong acids. Strong alkalis. Strong oxidizing agents.

Hazardous Decomposition Products: Thermal decomposition yield oxides of Carbon, Nitrogen compounds.

11: TOXICOLOGICAL INFORMATION

The following toxicological assessment is based on knowledge of the toxicity of the product's components. Expected oral LD50, rat >1030mg/kg. Classified as skin sensitizer.

Health Effects

On Eyes: Strong caustic effect.

On Skin: Corrosive - causes burns. May cause sensitization.

By Inhalation: Harmful by inhalation. May cause respiratory irritation.

By Ingestion: Harmful if swallowed. May cause irritation of mouth, throat and digestive

tract. Ingestion of significant amounts may result in severe systemic

effects.

Chronic: Repeated and prolonged skin contact will result in severe irritation leading

to burns.

Issue No.: 01 Rev. No.: 00 Profiber CW System Page 11 of 23



12: ECOLOGICAL INFORMATION

Environmental Assessment: When used and disposed as intended, no adverse environmental effects

are foreseen.

Mobility: Insoluble in water.

Degradability: Not readily biodegradable.

Bioaccumulation: Not Known.

Acute fish toxicity: Expected to be ecotoxic to fish/ daphnia/ algae.

13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

Unused Product: Classified as a special waste. May be reacted with base component to give

an inert polymeric material.

Used/ Contaminated Product: Classified as a special waste. Dispose off through an authorized waste

contractor to a licensed site.

Packaging: Must be disposed off through an authorized waste contractor.

14: TRANSPORT INFORMATION



UN Number: 1760

Transport Name: Corrosive liquids, n.o.s.

Transport Type:		Class:	Pack Group:	Marine Pollutant
At Sea	IMO	8	Ш	No
Air Transport	IATA/ICAO	8	Ш	
At land	RID/ADR	8	Ш	

Issue No.: 01 **Rev. No.:** 00 Profiber CW System **Page** 12 of 23



15: REGULATORY INFORMATION

Hazard Label Data: C



Corrosive

Named Ingredients: Isophorone diamine

Benzyl alcohol

UN Number: 1760

Risk Phrases:

R34 Causes burns.

R20/21/22 Harmful by inhalation, in contact with skin and if

swallowed.

R43 May cause sensitization by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term

adverse in the aquatic environment.

Safety Phrases:

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with

plenty of water and seek medical advice.

S37/39 Wear suitable gloves and eye/face protection.

In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

16: OTHER INFORMATION

Issue Date: 24/11/2013 Revised Date:

Disclaimer: The information contained herein is derived from the best available sources and is

believed to be accurate. However, no guarantee is expressed or implied regarding

the accuracy of the data given in the use of this product.

Issue No.: 01 **Rev. No.:** 00 Profiber CW System **Page** 13 of 23



Material SAFETY DATA SHEET Quickmast ER350 - Base

1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Quickmast ER350 - Base

Chemical Family: Base component of heavy duty carbon fiber reinforced polymer wrap

structural strengthening system.

Manufacturer: Don Construction Chemicals India LTD

Tel. +914426185340/41/42

www.dcp-int.com

Date Prepared: 24.11.13

MSDS Number: DCP-IND/12/02-B

2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition: Modified epoxy resin, nonreactive additives.

Hazardous ingredient(s) Symbol Risk Phrases CAS No. %

 Bisphenol-A epoxy resin
 Xi
 R36/38, 43
 25068-38-6
 > 85

 Alkyl(C12-C14)glycidylether
 Xi, N
 R36/38, 43, 51/53
 68609-97-2
 < 15</td>

Refer to Section 8 for Occupational Exposure Limits.

3: HAZARDS IDENTIFICATION

Hazard information: Irritating to eyes and respiratory system.

May cause sensitization by skin contact.

Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Classification: Xi, N. R36/38, 43, 51/53.

4: FIRST AID MEASURES

Eyes: Irrigate immediately with copious quantities of water for 15 minutes,

Eyelids should be held away from the eyeball to ensure thorough rinsing.

Obtain medical attention if irritation persists.

Skin: Wash thoroughly with soap and water or suitable skin cleanser as soon as

possible. Remove contaminated clothing. Obtain medical advice if skin

disorder develops.

Inhalation: Move to fresh air. Obtain medical attention if needed.

Ingestion: Immediately give plenty of water (if possible charcoal slurry). If a person

vomits when lying on his back, place him in a recovery position. Do not

induce vomiting. Obtain medical advice.

Issue No.: 01 Rev. No.: 00 Profiber CW System Page 14 of 23



5: FIRE FIGHTING MEASURES

Flash point: > 150°C

Special Exposure Hazards: Formation of toxic gases is possible during heating or in case of fire.

Extinguishing media: Foam, dry powder, carbon dioxide, water spray jet.

Personal protective equipment: Wear protective clothing and use self-contained breathing apparatus.

6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Put on adequate protective equipment.

Environmental Precautions: Keep away from drains, surface-water, ground-water and soil.

Decontamination Procedures: Collect as much as possible in a container for disposal. Soak up the

remainder with inert absorbent. Disposal according to local regulations.

7: HANDLING AND STORAGE

Handling: Do not breathe vapour. Avoid contact with skin and eyes.

Storage: Keep in a dry cool ventilated place. Direct sunshine should be avoided.

Keep away from ignition sources - No smoking.

Keep container tightly closed.

Keep away from food, drinks and animal food.

8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ingestion: Prevent eating, drinking or smoking in the area of product use.

Eye contact: Safety glasses or chemical goggles.

Skin contact: Impervious gloves (e.g. PVC).

Inhalation: When mist occurs during spraying operations, wear suitable respiratory

protective equipment.

Respiratory protection: In case of insufficient ventilation, wear suitable equipment.

Engineering controls: Use only in well ventilated areas. Local exhaust ventilation is

recommended.

Issue No.: 01 Rev. No.: 00 Profiber CW System Page 15 of 23



9: PHYSICAL AND CHEMICAL PROPERTIES

Form: Viscous liquid

Color: White

Odour: Weak

Flash Point (closed cup) (°C): >150

Boiling point (°C): N/A

Explosive Properties (%): N/A

Freezing point (°C): N/A

Relative Density (@25°C): 1.15 ± 0.05 Water Solubility: Insoluble

10: STABILITY AND REACTIVITY

Stability: Stable.

Conditions to Avoid: Excessive heating. Direct sunshine should be avoided. Electric discharge.

Chemical incompatibility: Strong acid, strong base, strong oxidizer and amines.

Hazardous Decomposition Products: Formation of toxic gases is possible during heating or in case of fire.

11: TOXICOLOGICAL INFORMATION

The following toxicological assessment is based on knowledge of the toxicity of the product's components. Expected oral LD50, rat >3,000mg/kg

Health Effects

On Eyes: Irritant.
On Skin: Irritant.
By Inhalation: Irritant.
By Ingestion: Irritant.
Chronic: N/A.

12: ECOLOGICAL INFORMATION

Environmental Assessment: When used and disposed off as intended, no adverse environmental

effects are foreseen.

Mobility: N/A.

Degradability: Not biodegradable.

Bioaccumulation: N/A.

Acute fish toxicity: Toxic to aquatic organisms.

Issue No.: 01 **Rev. No.:** 00 Profiber CW System **Page** 16 of 23



13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

Unused Product: Dispose off through an authorized waste contractor to a licensed site.

Used/ Contaminated Product: As for unused product.

Packaging: May be steam cleaned and recycled.

14: TRANSPORT INFORMATION



UN/SI Number: 3082

Transport Name: Environmentally hazardous substance, liquid, n.o.s.

Transport Type:		Class:	Pack Group:	Item:	Marine Pollutant:
At Sea	IMO/IMDG	9	Ш		No
Air Transport	IATA/ICAO	9	Ш		
At land	RID/ADR	9	Ш		

15: REGULATORY INFORMATION

Hazard Label Data: Xi N





Irritant

Dangerous for the environment

Contains: Modified epoxy resin.

Risk Phrases:

R36/38 Irritating to eyes and respiratory system.
R43 May cause sensitization by skin contact.
R51/53 Toxic to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.

Safety Phrases:

S24 Avoid contact with skin.

S28 After contact with skin, wash immediately with plenty of

water.

S37/39 Wear suitable gloves and eye/face protection.

S60 This material and its container must be disposed of as

hazardous waste.

Issue No.: 01 **Rev. No.:** 00 Profiber CW System **Page** 17 of 23



16: OTHER INFORMATION

Issue Date: 24/11/2013 Revised Date:

Disclaimer: The information contained herein is derived from the best available sources and is

believed to be accurate. However, no guarantee is expressed or implied regarding

the accuracy of the data given in the use of this product.

Issue No.: 01 **Rev. No.:** 00 Profiber CW System **Page** 18 of 23



Material SAFETY DATA SHEET Quickmast ER350 - Hardener

1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Quickmast ER350 - Hardener

Chemical Family: Hardener component of heavy duty carbon fiber reinforced polymer wrap

structural strengthening system.

Manufacturer: Don Construction Chemicals India LTD

Tel. +914426185340/41/42

www.dcp-int.com

Date Prepared: 24.11.13

MSDS Number: DCP-IND/12/02-H

2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition: Polyamide resin.

Hazardous ingredient(s) Symbol Risk Phrases CAS No. %

 Polyamide resin
 Xi
 R36/38, 43, 52/53
 > 85

 Free amines, Triethylene tetramine
 Xn, C
 R21, 34, 43, 52/53
 112-24-3
 < 15</td>

Refer to Section 8 for Occupational Exposure Limits.

3: HAZARDS IDENTIFICATION

Hazard information: Harmful in contact with skin.

Causes burns.

Irritating to eyes and respiratory system. May cause sensitization by skin contact.

Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Classification: Xn, C. R21, 34, 36/38, 43, 52/53.

Issue No.: 01 **Rev. No.:** 00 Profiber CW System **Page** 19 of 23



4: FIRST AID MEASURES

Eyes: Irrigate immediately with copious quantities of water for 15 minutes,

Eyelids should be held away from the eyeball to ensure thorough rinsing.

Obtain medical attention if irritation persists.

Skin: Wash thoroughly with soap and water or suitable skin cleanser as soon as

possible. Remove contaminated clothing. Obtain medical advice if skin

disorder develop.

Inhalation: Move to fresh air. Obtain medical attention if needed.

Ingestion: Immediately give plenty of water (if possible charcoal slurry). If a person

vomits when lying on his back, place him in a recovery position. Administer oxygen or artificial respiration if needed. Do not induce

vomiting. Obtain medical advice.

5: FIRE FIGHTING MEASURES

Flash point: > 200°C

Special Exposure Hazards: In case of fire toxic fumes will be formed (amines), Carbon oxides and

Nitrogen oxides.

Extinguishing media: Powder, carbon dioxide, foam, water mist (only large amounts).

Personal protective equipment: Wear protective clothing and use self-contained breathing apparatus.

6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Put on adequate protective equipment.

Environmental Precautions: Keep away from drains, surface-water, ground-water and soil.

Decontamination Procedures: Collect as much as possible in a container for disposal. Cover the

remainder with inert absorbent. Disposal according to local regulations.

7: HANDLING AND STORAGE

Handling: Do not breathe vapour. Avoid contact with skin and eyes.

Storage: Keep in a dry cool ventilated place. Direct sunshine should be avoided.

Keep away from ignition sources - No smoking.

Keep container tightly closed.

Keep away from food, drinks and animal food. Keep at temperatures between 2°C and 40°C

Issue No.: 01 **Rev. No.:** 00 Profiber CW System **Page** 20 of 23



8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ingestion: Prevent eating, drinking or smoking in the area of product use.

Eye contact: Safety glasses or chemical goggles.

Skin contact: Impervious gloves (e.g. PVC).

Inhalation: When mist occurs during spraying operations, wear suitable respiratory

protective equipment.

Respiratory protection: In case of insufficient ventilation, wear suitable equipment.

Engineering controls: Use only in well ventilated areas. Local exhaust ventilation is

recommended.

9: PHYSICAL AND CHEMICAL PROPERTIES

Form: Viscous liquid

Color: Brown

Odour: Mild amines

Flash Point (closed cup) (°C): >200

Boiling point (°C): N/A

Explosive Properties (%): N/A

Freezing point (°C): N/A

Relative Density (@25°C): 0.96 ± 0.05

Water Solubility: Insoluble

10: STABILITY AND REACTIVITY

Stability: Stable.

Conditions to Avoid: Excessive heating. Direct sunshine should be avoided.

Chemical incompatibility: Acids, Reacts violently with oxidizing agents.

Hazardous Decomposition Products: Noxious fumes, carbon oxides, nitrogen oxides.

Issue No.: 01 Rev. No.: 00 Profiber CW System Page 21 of 23



11: TOXICOLOGICAL INFORMATION

The following toxicological assessment is based on knowledge of the toxicity of the product's components. Expected oral LD50, rat >15 g/kg

Health Effects

On Eyes: Irritant.
On Skin: Irritant.
By Inhalation: Irritant.
By Ingestion: Irritant.
Chronic: N/A.

12: ECOLOGICAL INFORMATION

Environmental Assessment: When used and disposed off as intended, no adverse environmental

effects are foreseen.

Mobility: NA.
Degradability: NA.

Bioaccumulation: Bioaccumulative potential.

Acute fish toxicity: May cause long-term adverse effects in the aquatic environment.

13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

Unused Product: Dispose off through an authorized waste contractor to a licensed site.

Used/ Contaminated Product: As for unused product.

Packaging: May be steam cleaned and recycled.

14: TRANSPORT INFORMATION

This product is NOT classified as dangerous for transport.

Issue No.: 01 Rev. No.: 00 Profiber CW System Page 22 of 23



15: REGULATORY INFORMATION

Hazard Label Data: Xn C





Harmful Corrosive

Contains: Polyamide resin

Risk Phrases:

R21 Harmful in contact with skin.

R34 Causes burns.

R36/38 Irritating to eyes and respiratory system.
R43 May cause sensitization by skin contact.

R52/53 Harmful to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.

Safety Phrases:

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with

plenty of water and seek medical advice.

S36/37/39 Wear suitable protective clothing, gloves and eye/face

protection.

16: OTHER INFORMATION

Issue Date: 24/11/2013 Revised Date:

Disclaimer: The information contained herein is derived from the best available sources and is

believed to be accurate. However, no guarantee is expressed or implied regarding

the accuracy of the data given in the use of this product.

Issue No.: 01 **Rev. No.:** 00 Profiber CW System **Page** 23 of 23