

Material SAFETY DATA SHEET Profix PST

1: PRODUCT AND COMPANY IDENTIFICATION

Product Name:	Profix PST	
Description:	Ready to use interior grade ceramic tile adhesive based on organic binder	
	with extended open time	
Manufacturer:	Ayla Construction Chemicals	
	P.O. Box 1117, Amman 11118 Jorda	an
	Tel. + 962 6 5338891	Fax: + 962 6 5338829
	www.dcp-int.com	
Date Prepared:	27.08.08	
MSDS Number:	DCP/10/01/01	

2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition: Organic polymer, inorganic fillers, pigment.

Refer to Section 8 for Occupational Exposure Limits.

3: HAZARDS IDENTIFICATION

No significant hazard.

4: FIRST AID MEASURES

Eyes:	Irrigate immediately with copious quantities of water for several minutes. Obtain medical attention if necessary.
Skin:	Remove contaminated clothing immediately. Wash immediately with copious quantities of water. Obtain medical advice if skin disorders develop.
Inhalation:	Remove from exposure. Unlikely to occur.
Ingestion:	Wash out mouth with water. Obtain medical attention. Do not induce vomiting.

Issue No.:	01	Rev. No.:	01	Profix PST Page	1 of 4



5: FIRE FIGHTING MEASURES

Flash Point:	None.
Lower Explosive Limit:	None.
Extinguishing Media:	Carbon dioxide, powder, foam or water fog – Do not use water jets.
Personal Protective Equipment:	Self-contained breathing apparatus.

6: ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Wear suitable protective clothing, gloves and eye/face protection.
Environmental Precautions:	Prevent entry into drains, sewers and water courses.
Decontamination Procedures:	Soak up with inert absorbent. Gather into containers.

7: HANDLING AND STORAGE

Handling:	Avoid skin and eye contact.
Storage:	Store in cool and dry area.

8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Eye Contact:	Safety glasses.
Skin Contact:	Wear impervious gloves (e.g. PVC).
Engineering Controls:	No specific ventilation requirement noted.
Hygiene Measures:	Clean up hands after using the product.
Occupational Exposure Limits:	None assigned.

9: PHYSICAL AND CHEMICAL PROPERTIES

Form:	Lump free paste
Colour:	white
Odour:	Slight/faint
Boiling Point (°C):	Not applicable
Flash Point (closed cup) (°C):	81.5
Autoflammability (°C):	Not determined
Relative Density (@25°C):	1.75
Water Solubility:	soluble

Issue No.:	01	Rev. No.:	01	Profix PST	Page 2 of 4



10: STABILITY AND REACTIVITY

Stability:Stable.Conditions to Avoid:Temperatures below 5 °C.Chemical Incompatibility:Strong acids. Strong oxidizing agents.Hazardous Decomposition Products:Thermal decomposition yields nitrogen compounds, oxides of carbon.

11: TOXICOLOGICAL INFORMATION

Health Effects

On Eyes:	Causes transient irritation.
On Skin:	Unlikely to irritate on brief or occasional exposure.
By Inhalation:	Low volatility makes inhalation unlikely at ambient temperatures.
By Ingestion:	Low order of acute toxicity. May cause irritation of mouth, throat and digestive tract.

12: ECOLOGICAL INFORMATION

Mobility:	Thick paste.
Degradability:	Not readily biodegradable.
Bioaccumulation:	Not expected to be bioaccumulate.
Acute Fish Toxicity:	Not expected to be ecotoxic to fish/daphnia/algae.

13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

Unused Product:	Dispose off through an authorized waste contractor to a licensed site. Do not empty into drains, sewers or water courses.
Used/ Contaminated Product:	As for unused product.
Packaging:	The method of disposal must be acceptable to the local authority.

14: TRANSPORT INFORMATION

This product is **not** classified as dangerous for transport.

15: REGULATORY INFORMATION

This product is **not** classified as dangerous for supply.

Issue No.:	01	Rev. No.:	01	Profix PST
------------	----	-----------	----	------------



16: OTHER INFORMATION

Issue Date:

27/08/2008

Revised Date: 0

09.02.2016

Disclaimer: The information contained herein is derived from the best available sources and is believed to be accurate. However, no guarantee is expressed or implied regarding the accuracy of the data given in the use of this product.

Profix PST

Issue No.:	01	Rev. No.:	01	
------------	----	-----------	----	--