

# **Material SAFETY DATA SHEET Quickmast 108 - Hardener**

#### 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Quickmast 108 - Hardener

Description: Hardener component of epoxy bonding agent

Manufacturer: Don Construction Chemicals India LTD

Tel. +914426185340/41/42

www.dcp-int.com

Date Prepared: 22.09.2012

MSDS Number: DCP-IND/09/H-A

## 2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition: Aromatic amine curing agent, accelerator and additives.

Hazardous Ingredient(s) Symbol Risk Phrases CAS No. %

Epoxy curing agent T, Xn R20/21/22, 23/24/25, 39, 43, 45

48, 51/53

<sup>'53</sup> > 80

Epoxy accelerator Xn R22, 36/38 90-72-2 < 10

Refer to Section 8 for Occupational Exposure Limits.

#### 3: HAZARDS IDENTIFICATION

Hazard Information: Harmful by inhalation, in contact with skin and if swallowed.

Toxic by inhalation, in contact with skin and if swallowed.

Irritating to eyes and skin.

Danger of very serious irreversible effects. May cause sensitization by skin contact.

May cause cancer.

Danger of serious damage to health by prolonged exposure.

Toxic to aquatic organism, may cause long-term affects in the aquatic

environment.



#### 4: FIRST AID MEASURES

Eyes: Irrigate immediately with copious quantities of water for 15 minutes.

Obtain medical attention immediately.

Skin: Remove contaminated clothes and shoes. Wash immediately with running

water. Obtain medical advice if there are burns or symptoms of poisoning.

Inhalation: Remove from exposure, check for breathing and apply artificial respiration

if necessary. Transfer to hospital as soon as possible.

Ingestion: Drink plenty of water. Do not induce vomiting. Obtain medical attention.

Beware of aspiration if vomiting occurs.

#### 5: FIRE FIGHTING MEASURES

Extinguishing Media: Carbon dioxide.

Personal Protective Equipment: Self-contained breathing apparatus. Standard aluminized suit.

Special Exposure Hazards: Toxic fumes.

#### **6: ACCIDENTAL RELEASE MEASURES**

Personal Precautions: Wear suitable protective clothing, gloves and eye/face protection. Turn

leaking containers leak-side up to prevent the escape of liquid.

Environmental Precautions: Prevent entry into drains, sewers and water courses.

Decontamination Procedures: Soak up with inert absorbent like sand. Gather into labeled containers.

Dispose off as applicable regulations.

#### 7: HANDLING AND STORAGE

Handling: Maintain good standards of personal hygiene. Avoid skin and eye contact.

Do not eat, drink or smoke whilst using this product. Ensure adequate

ventilation.

Storage: Keep container tightly closed in a cool dry area. Keep away from food

containers.

#### 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Eye Protection: Tightly sealed safety glasses/goggles.

Skin Protection: Impervious gloves (e.g. PVC). Suitable protective clothing.

Respiratory Protection: Breathing filters apparatus.

Hygiene Measures: Change contaminated clothing and clean before re-use.

Engineering Controls: Use only in well ventilated area. Local exhaust ventilation is

recommended.

Exposure Guidelines: None assigned.

**Issue No.:** 01 **Rev. No.:** 00 Quickmast 108 – Hardener **Page** 2 of 5



#### 9: PHYSICAL AND CHEMICAL PROPERTIES

Form: Liquid
Colour: Green
Odour: Amine
Relative Density (@25°C): 1.3

Water Solubility: Not miscible or difficult to mix.

#### 10: STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

#### 11: TOXICOLOGICAL INFORMATION

The following toxicological assessment is based on knowledge of the toxicity of the product's components.

Ingredient: 1,2–Epoxy–3–Phenoxypropane; SKN GPG LD50 1665mg/ kg.

# 12: ECOLOGICAL INFORMATION

Environmental Assessment: No information.

Mobility: No information.

Degradability: No information.

Bioaccumulation: No information.

Acute Fish Toxicity: No information.

### 13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

Unused Product: Classified as a special waste. May be reacted with base component to give

an inert polymeric material.

Used/ Contaminated Product: Classified as a special waste. Dispose off through an authorized waste

contractor to a licensed site.

Packaging: Must be disposed off through an authorized waste contractor.



# **14: TRANSPORT INFORMATION**



UN Number: 2810

Transport Name: Toxic liquids, n.o.s.

Transport Type:		Class:	Pack Group:	Marine Pollutant
At Sea	IMO	6.1	III	No
Air Transport	IATA/ICAO	6.1	III	
At land	RID/ADR	6.1		



#### 15: REGULATORY INFORMATION

**Hazard Label Data:** 

T

Toxic

Ν



Dangerous for the environment

UN Number: 2810

Risk Phrases:

R20/21/22 Harmful by inhalation, in contact with skin and if

swallowed.

R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.

R36/38 Irritating to eyes and skin.

R39 Danger of very serious irreversible effects.

R43 May cause sensitization by skin contact.

R45 May cause cancer.

R48 Danger of serious damage to health by prolonged

exposure.

R51/53 Toxic to aquatic organisms, may cause long-term adverse

in the aquatic environment.

Safety Phrases:

S24 Avoid contact with skin.

S37 Wear suitable gloves.

S45 In case of accident or if you feel unwell, seek medical

advice immediately (show the label where possible).

S53 Avoid exposure – obtain special instructions before use.

#### **16: OTHER INFORMATION**

Issue Date: 22.09.2012 Revised Date:

Disclaimer: The information contained herein is derived from the best available sources and is

believed to be accurate. However, no guarantee is expressed or implied regarding

the accuracy of the data given in the use of this product.

**Issue No.:** 01 **Rev. No.:** 00 Quickmast 108 – Hardener **Page** 5 of 5