

# Material SAFETY DATA SHEET Quickmast EP200 - Base

## 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name:	Quickmast EP200 - Base	
Description:	Base component of epoxy tile grout	
Manufacturer:	Ayla Lebanon	
	Port, Jamarek Street (Face Port Pharmacy),	Rbeiz Bldg
	Beirut, Lebanon	
	Tel.: +961 1 444 562	Fax: +961 1 444 563
	www.dcp-int.com	
Date Prepared:	04.09.2008	
MSDS Number:	DCP/10/02/21-B	

#### 2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition:	Epoxy resin, hydrod	carbon resin and diluent.		
Hazardous Ingredient(s)	Symbol	Risk Phrases	CAS No.	%
Epoxy resin (Number average molecular weigh	Xi, N t < 700)	R36/38, 43, 51/53	25068-38-6	70 - 75
Hydrocarbon resin	Xn	R22	71302-91-5	15 - 20

Refer to Section 8 for Occupational Exposure Limits.

## 3: HAZARDS IDENTIFICATION

Hazard Information:	Harmful if swallowed. Irritating to eyes and skin.
	May cause sensitization by skin contact.
	Toxic to aquatic organism, may cause long-term affects in the aquatic environment.
Classification:	Xi, N. R22, 36/38, 43, 51/53



#### 4: **FIRST AID MEASURES**

Eyes:	Irrigate immediately with copious quantities of water for 15 minutes. Obtain medical attention urgently.
Skin:	Wash immediately with soap and water or suitable skin cleanser. Remove contaminated clothes and shoes. Obtain medical advice if skin disorders develop.
Inhalation:	Remove from exposure; obtain medical attention if respiratory irritation develops or if breathing becomes difficult.
Ingestion:	Rinse mouth thoroughly. Drink plenty of water. Do not induce vomiting. Obtain medical attention. Beware of aspiration if vomiting occurs.

#### 5: **FIRE FIGHTING MEASURES**

Flash Point (Closed Cup) :	> 200°C.
Extinguishing Media:	Carbon dioxide, powder, foam or water.
Personal Protective Equipment:	Self-contained breathing apparatus.
Special Exposure Hazards:	Toxic fumes. Carbon oxides.

#### **6: ACCIDENTAL RELEASE MEASURES**

Personal Precautions:	Wear suitable protective clothing, gloves and eye/face protection.
Environmental Precautions:	Prevent entry into drains, sewers and water courses.
Decontamination Procedures:	Soak up with inert absorbent such as sand. Gather into labeled containers. Dispose off as applicable regulations.

#### HANDLING AND STORAGE 7:

Handling:	Maintain good standards of personal hygiene. Avoid skin and eye contact. Do not eat, drink or smoke whilst using this product. Ensure adequate ventilation.
Storage:	Keep container tightly closed in a cool dry area.
8: EXPOSURE CONTROLS A	ND PERSONAL PROTECTION
Eye Protection:	Safety glasses/goggles.
Skin Protection:	Impervious gloves (e.g. PVC). Suitable protective clothing.
Respiratory Protection:	Organic chemical cartridge respirator, if needed.

Hygiene Measures: Change contaminated clothing and clean before re-use. Engineering Controls:

No specific ventilation requirements noted.

None assigned. **Exposure Guidelines:** 

	Issue No.:	01	Rev. No.:	00	Quickmast EP200 - Base	Page	2 of 5
--	------------	----	-----------	----	------------------------	------	--------



#### 9: PHYSICAL AND CHEMICAL PROPERTIES

Form:	Liquid
Colour:	White
Odour:	Mild
pH (concentrate):	Not applicable
Boiling Point (°C):	> 200
Flash Point (closed cup) (°C) :	> 200
Autoflammability (°C):	Not determined
Explosive Properties (%):	Not Known
Relative Density (@25°C):	1.185
Water Solubility:	Insoluble

#### **10: STABILITY AND REACTIVITY**

Stability:	Stable: reacts with compounds containing amino, hydroxyl or carboxyl groups to give stable, cross linked materials.
Conditions to Avoid:	None Known.
Chemical Incompatibility:	Strong acids. Strong alkalis. Strong oxidizing agents.
Hazardous Decomposition Products:	Thermal decomposition yield oxides of carbon, toxic fumes.

#### **11: TOXICOLOGICAL INFORMATION**

The following toxicological assessment is based on knowledge of the toxicity of the product's components. Acute Oral effect LD50 > 5000 mg/kg. Classified as moderate sensitizer.

#### Health Effects

On Eyes:	Slight irritation (rabbit).
On Skin:	Moderate irritation (rabbit).
By Inhalation:	May cause respiratory irritation.
By Ingestion:	May cause irritation of mouth, throat and digestive tract.
Chronic:	Repeated and prolonged skin contact may lead to skin disorders.



## **12: ECOLOGICAL INFORMATION**

Environmental Assessment:	When used and disposed as intended, no adverse environmental effects are foreseen.
Mobility:	Viscous liquid. Insoluble in water.
Degradability:	Not readily biodegradable.
Bioaccumulation:	Not expected to be bioaccumulate.
Acute Fish Toxicity:	Ecotoxic to fish/daphnia/algae.

#### **13: DISPOSAL CONSIDERATION**

Disposal must be in accordance with local and national legislation.

Unused Product:	Dispose off through an authorized waste contractor to a licensed site.
Used/ Contaminated Product:	As for unused product.
Packaging:	Must be disposed off through an authorized waste contractor.

#### 14: TRANSPORT INFORMATION



#### UN Number:

3082

Transport Name:

Environmentally hazardous substance, liquid n.o.s (epoxy resin).

Transport Type:		Class:	Pack Group:	Marine Pollutant
At Sea	IMO	9	III	No
Air Transport	IATA/ICAO	9	Ш	
At land	RID/ADR	9	Ш	



## **15: REGULATORY INFORMATION**

Hazard Label Data:	Xi Trritant	N Dangerous for the environment	
Named Ingredients:	Epoxy resin (Number average molecular weight < 700).		
UN Number:	3082		
Risk Phrases:			
	R22	Harmful if swallowed.	
	R36/38	Irritating to eyes and skin.	
	R43	May cause sensitization by skin contact.	
	R51/53	Toxic to aquatic organisms, may cause long-term adverse in the aquatic environment.	
Safety Phrases:			
	S24/25	Avoid contact with skin and eyes.	
	S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.	
	S37/39	Wear suitable gloves and eye/face protection.	
<b>16: OTHER INFORMATION</b>			

**Revised Date:** Issue Date: 04/09/2008 Disclaimer: The information contained herein is derived from the best available sources and is believed to be accurate. However, no guarantee is expressed or implied regarding the accuracy of the data given in the use of this product.