

Material SAFETY DATA SHEET Quickmast EP500 - Hardener

1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Quickmast EP500 - Hardener

Description: Hardener component of three component high performance

solvent free epoxy ceramic tile and stone adhesive and grout

specially designed to grout narrow joints between tiles.

Manufacturer: Ayla Construction Chemicals

P.O. Box 1117, Amman 11118 Jordan

Tel. + 962 6 5338891 Fax: + 962 6 5338829

www.dcp-int.com

Date Prepared: 04.09.08

MSDS Number: DCP/10/01/11-H

2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition: Epoxy resin hardening agent, inert fillers and additives.

Hazardous Ingredient(s)	Symbol	Risk Phrases	CAS No.	%
Polyaminoamide adduct Phenol, methylstyrenated Polyoxypropylendiamin Nonylphenol 2-piperazin-1-ylethylamine	Xi Xi C, Xn, Xi C, Xn, N C, Xn	R41 R38, 43 R22, 34, 41, 52/53, 65 R22, 34, 62, 63, 50/53 R21/22, 34, 43, 52/53	- 68512-30-1 9046-10-0 25154-52-3 140-31-8	15 - 30 15 - 20 5 - 15 1 - 10 1 - 10
Triethylene tetramine 4,4'-methylenedianiline	C, XII C, Xn, Xi T, Xn, N	R21/22, 34, 43, 52/53 R21, 34, 43, 52/53 R39, 43, 45, 48, 68, 41/53	112-24-3 101-77-9	1 – 10 1 – 10 1 – 5
4,4'-Isopropylidenediphenol, oligomeric reaction products w 1-chloro-2,3-epoxypropane	Xi, N vith	R36/38, 43, 51/53	25068-38-6	1 - 5
Xylene	Xn, Xi	R10, 20/21, 38	1330-20-7	1 - 5

Refer to Section 8 for Occupational Exposure Limits.



3: HAZARDS IDENTIFICATION

Hazard Information: Harmful in contact with skin and if swallowed.

Causes burns.

Irritating to eyes and skin. Risk of serious damage to eyes.

May cause sensitization by skin contact.

Possible risk of impaired fertility.

Possible risk of harm to the unborn child.

Very toxic to aquatic organisms, may cause long-term adverse effects in

the aquatic environment.

Classification: C, Xn, N. R21/22, 34, 36/38, 41, 43, 50/53, 62, 63

4: FIRST AID MEASURES

Eyes: Irrigate immediately with copious quantities of water for 15 minutes,

Eyelids should be held away from the eyeball to ensure thorough rinsing.

Obtain medical attention if irritation persists.

Skin: Wash thoroughly with soap and water or suitable skin cleanser as soon as

possible. Remove contaminated clothing. Obtain medical advice if skin

disorder develop.

Inhalation: Move to fresh air. Obtain medical attention if needed.

Ingestion: Immediately give plenty of water (if possible charcoal slurry). If a person

vomits when lying on his back, place him in a recovery position. Administer oxygen or artificial respiration if needed. Do not induce

vomiting. Obtain medical advice.

General: Symptoms of poisoning may even occur after several hours; therefore

medical observation for at least 48 hours after the accident.

5: FIRE FIGHTING MEASURES

Flash Point: > 150°C.

Special Exposure Hazards: In case of fire toxic fumes will be formed (amines), carbon oxides and

nitrogen oxides.

Extinguishing Media: CO₂, extinguishing powder or water jet. Fight larger fires with water jet or

alcohol-resistant foam. For safety reasons do not use Water with a full

water jet.

Personal Protective Equipment: Wear protective clothing and use self-contained breathing apparatus.



6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Ensure adequate ventilation immediately issue NO SMOKING and NO

NAKED FLAMES warnings. Wear suitable protective clothing, gloves and

eye/face protection.

Environmental Precautions: Prevent entry into drains, sewers and water courses.

Decontamination Procedures: Soak up with inert absorbent like sand. Gather into labeled containers.

Dispose off as applicable regulations.

7: HANDLING AND STORAGE

Handling: Maintain good standards of personal hygiene. Avoid skin and eye contact.

Do not eat, drink or smoke whilst using this product. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory

equipment.

Storage: Keep container tightly closed in a cool dry area away from sources of heat

and out of direct sunlight to avoid pressure build up. Store in conformity with local fire regulations. Store away from sources of ignition. Keep away

from food containers. Store at 15 - 25°C.

8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ingestion: Prevent eating, drinking or smoking in the area of product use.

Eye Contact: Safety glasses or chemical goggles.

Skin Contact: Impervious gloves (e.g. PVC).

Inhalation: When mist occurs during spraying operations, wear suitable respiratory

protective equipment.

Respiratory Protection: In case of insufficient ventilation, wear suitable equipment.

Engineering Controls: Use only in well ventilated areas. Local exhaust ventilation is

recommended.

9: PHYSICAL AND CHEMICAL PROPERTIES

Form: Viscous liquid

Colour: Brown

Odour: Mild amines

Flash Point (closed cup) ($^{\circ}$ C): > 200

Boiling Point (°C): Not applicable

Explosive Properties (%): Not applicable

Freezing Point (°C): Not applicable

Relative Density (@25°C): 0.95 - 1.05

Water Solubility: Insoluble

Issue No.: 01 **Rev. No.:** 00 Quickmast EP500 - Hardener **Page** 3 of 6



10: STABILITY AND REACTIVITY

Stability: Stable if used as directed.

Conditions to Avoid: Temperature above 35°C.

Chemical Incompatibility: Strong acids. Strong alkalis. Strong oxidizing agents.

Hazardous Decomposition Products: Thermal decomposition yield oxides of carbon, nitrogen compounds.

11: TOXICOLOGICAL INFORMATION

The following toxicological assessment is based on knowledge of the toxicity of the product's components. Expected oral LD50, rat > 1000mg/kg.

Classified as skin sensitizer.

Health Effects

On Eyes: Strong caustic effect.

On Skin: Corrosive - causes burns. May cause sensitization.

By Inhalation: Harmful by inhalation. May cause respiratory irritation.

By Ingestion: Harmful if swallowed. May cause irritation of mouth, throat and digestive

tract. Ingestion of significant amounts may result in severe systemic

effects.

Chronic: Repeated and prolonged skin contact will result in severe irritation leading

to burns.

12: ECOLOGICAL INFORMATION

Environmental Assessment: When used and disposed as intended, no adverse environmental effects

are foreseen.

Mobility: Mobile liquid. Insoluble in water.

Degradability: Not readily biodegradable.

Bioaccumulation: Not Known.

Acute Fish Toxicity: Expected to be ecotoxic to fish/daphnia/algae.

13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

Unused Product: Dispose off through an authorized waste contractor to a licensed site.

Used/ Contaminated Product: As for unused product. Packaging: As for unused product.



14: TRANSPORT INFORMATION



UN Number: 2735

Transport Name: Amines, liquid, corrosive, n.o.s. or Polyamines, liquid, corrosive, n.o.s.

Transport Type:		Class:	Pack Group:	Marine Pollutant
At Sea	IMO	8	II	Yes
Air Transport	IATA/ICAO	8	II	
At land	RID/ADR	8	II	



15: REGULATORY INFORMATION

Hazard Label Data:

Xn







Harmful

Corrosive

Dangerous for the environment

Risk Phrases:

R21/22 Harmful in contact with skin and if swallowed.

R34 Causes burns.

R36/38 Irritating to eyes and skin.

R41 Risk of serious damage to eyes.

R43 May cause sensitization by skin contact.

R50/53 Very toxic to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.

R62 Possible risk of impaired fertility.

R63 Possible risk of harm to the unborn child.

Safety Phrases:

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with

plenty of water and seek medical advice.

S28 After contact with skin, wash immediately with plenty of

water.

S36/37/39 Wear suitable protective clothing, gloves and eye/face

protection.

S45 In case of accident or if you feel unwell, seek medical

advice immediately (show the label where possible).

16: OTHER INFORMATION

Issue Date: 04/09/2008 Revised Date: 24.05.2018

Disclaimer: The information contained herein is derived from the best available sources and is

believed to be accurate. However, no guarantee is expressed or implied regarding

the accuracy of the data given in the use of this product.

Issue No.: 01 **Rev. No.:** 00 Quickmast EP500 - Hardener **Page** 6 of 6