

# Material SAFETY DATA SHEET Quickmast EP500F - Hardener

## 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name:	Quickmast EP500F - Hardener	
Description:	•	e component high performance le and stone adhesive and grout rrow joints between tiles.
Manufacturer:	Ayla Construction Chemicals	
	P.O. Box 1117, Amman 11118 Jorda	an
	Tel. + 962 6 5338891	Fax: + 962 6 5338829
	www.dcp-int.com	
Date Prepared:	27.04.17	
MSDS Number:	DCP/10/01/35-H	

## 2: COMPOSITION / INFORMATION ON INGREDIENTS

00

Composition:	Epoxy resin hardening	agent, inert fillers and additives.		
Hazardous Ingredient(s)	Symbol	Risk Phrases	CAS No.	%
Polyaminoamide adduct Phenol, methylstyrenated Polyoxypropylendiamin Nonylphenol 2-piperazin-1-ylethylamine Triethylene tetramine 4,4'-methylenedianiline	Xi Xi C, Xn, Xi C, Xn, N C, Xn C, Xn, Xi T, Xn, N	R41 R38, 43 R22, 34, 41, 52/53, 65 R22, 34, 62, 63, 50/53 R21/22, 34, 43, 52/53 R21, 34, 43, 52/53 R39, 43, 45, 48, 68, 41/53	- 68512-30-1 9046-10-0 25154-52-3 140-31-8 112-24-3 101-77-9	$15 - 30 \\ 15 - 20 \\ 5 - 15 \\ 1 - 10 \\ 1 - 10 \\ 1 - 10 \\ 1 - 5$
4,4'-Isopropylidenediphenol, oligomeric reaction products w 1-chloro-2,3-epoxypropane Xylene	Xi, N ith Xn, Xi	R36/38, 43, 51/53	25068-38-6 1330-20-7	1 - 5 1 - 5

Refer to Section 8 for Occupational Exposure Limits.



## **3: HAZARDS IDENTIFICATION**

Hazard Information:	Harmful in contact with skin and if swallowed. Causes burns. Irritating to eyes and skin. Risk of serious damage to eyes. May cause sensitization by skin contact. Possible risk of impaired fertility. Possible risk of harm to the unborn child. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Classification:	C, Xn, N. R21/22, 34, 36/38, 41, 43, 50/53, 62, 63
4: FIRST AID MEASURES	
Eyes:	Irrigate immediately with copious quantities of water for 15 minutes, Eyelids should be held away from the eyeball to ensure thorough rinsing. Obtain medical attention if irritation persists.
Skin:	Wash thoroughly with soap and water or suitable skin cleanser as soon as possible. Remove contaminated clothing. Obtain medical advice if skin disorder develop.
Inhalation:	Move to fresh air. Obtain medical attention if needed.
Ingestion:	Immediately give plenty of water (if possible charcoal slurry). If a person vomits when lying on his back, place him in a recovery position. Administer oxygen or artificial respiration if needed. Do not induce vomiting. Obtain medical advice.
General:	Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

### 5: FIRE FIGHTING MEASURES

Flash Point:	> 150°C.
Special Exposure Hazards:	In case of fire toxic fumes will be formed (amines), carbon oxides and nitrogen oxides.
Extinguishing Media:	CO <sub>2</sub> , extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam. For safety reasons do not use Water with a full water jet.
Personal Protective Equipment:	Wear protective clothing and use self-contained breathing apparatus.



#### **6: ACCIDENTAL RELEASE MEASURES**

Personal Precautions:	Ensure adequate ventilation immediately issue NO SMOKING and NO NAKED FLAMES warnings. Wear suitable protective clothing, gloves and eye/face protection.
Environmental Precautions:	Prevent entry into drains, sewers and water courses.
Decontamination Procedures:	Soak up with inert absorbent like sand. Gather into labeled containers. Dispose off as applicable regulations.

#### 7: HANDLING AND STORAGE

Handling:	Maintain good standards of personal hygiene. Avoid skin and eye contact. Do not eat, drink or smoke whilst using this product. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory equipment.
Storage:	Keep container tightly closed in a cool dry area away from sources of heat

and out of direct sunlight to avoid pressure build up. Store in conformity with local fire regulations. Store away from sources of ignition. Keep away from food containers. Store at 15 - 25°C.

#### 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ingestion:	Prevent eating, drinking or smoking in the area of product use.
Eye Contact:	Safety glasses or chemical goggles.
Skin Contact:	Impervious gloves (e.g. PVC).
Inhalation:	When mist occurs during spraying operations, wear suitable respiratory protective equipment.
Respiratory Protection:	In case of insufficient ventilation, wear suitable equipment.
Engineering Controls:	Use only in well ventilated areas. Local exhaust ventilation is recommended.

#### 9: PHYSICAL AND CHEMICAL PROPERTIES

Issue No.: 01 Rev. No.:	00	Quickmast EP500F - Hardener	Page 3 of 6
Water Solubility:	Insoluble		
Relative Density (@25°C):	0.95 – 1.05		
Freezing Point (°C):	Not applicable		
Explosive Properties (%):	Not applicable		
Boiling Point (°C):	Not applicable		
Flash Point (closed cup) (°C):	> 200		
Odour:	Mild amines		
Colour:	Brown		
Form:	Viscous liquid		



## **10: STABILITY AND REACTIVITY**

Stability:	Stable if used as directed.
Conditions to Avoid:	Temperature above 35°C.
Chemical Incompatibility:	Strong acids. Strong alkalis. Strong oxidizing agents.

Hazardous Decomposition Products: Thermal decomposition yield oxides of carbon, nitrogen compounds.

#### **11: TOXICOLOGICAL INFORMATION**

The following toxicological assessment is based on knowledge of the toxicity of the product's components. Expected oral LD50, rat > 1000mg/kg. Classified as skin sensitizer.

#### **Health Effects**

On Eyes:	Strong caustic effect.
On Skin:	Corrosive - causes burns. May cause sensitization.
By Inhalation:	Harmful by inhalation. May cause respiratory irritation.
By Ingestion:	Harmful if swallowed. May cause irritation of mouth, throat and digestive tract. Ingestion of significant amounts may result in severe systemic effects.
Chronic:	Repeated and prolonged skin contact will result in severe irritation leading to burns.

#### **12: ECOLOGICAL INFORMATION**

Environmental Assessment:	When used and disposed as intended, no adverse environmental effects are foreseen.
Mobility:	Mobile liquid. Insoluble in water.
Degradability:	Not readily biodegradable.
Bioaccumulation:	Not Known.
Acute Fish Toxicity:	Expected to be ecotoxic to fish/daphnia/algae.

#### **13: DISPOSAL CONSIDERATION**

Disposal must be in accordance with local and national legislation.

Unused Product:	Dispose off through an authorized waste contractor to a licensed site.
Used/ Contaminated Product:	As for unused product.
Packaging:	As for unused product.



## **14: TRANSPORT INFORMATION**



## UN Number:

2735

Transport Name:

Amines, liquid, corrosive, n.o.s. or Polyamines, liquid, corrosive, n.o.s.

Transport Type:		Class:	Pack Group:	Marine Pollutant
At Sea	IMO	8	II	Yes
Air Transport	IATA/ICAO	8	II	
At land	RID/ADR	8	II	



## **15: REGULATORY INFORMATION**

Hazard Label Data:	Xn Harmful	Corrosive Dangerous for the environment	
Risk Phrases:			
	R21/22	Harmful in contact with skin and if swallowed.	
	R34	Causes burns.	
	R36/38	Irritating to eyes and skin.	
	R41	Risk of serious damage to eyes.	
	R43	May cause sensitization by skin contact.	
	R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.	
	R62	Possible risk of impaired fertility.	
	R63	Possible risk of harm to the unborn child.	
Safety Phrases:			
	S24/25	Avoid contact with skin and eyes.	
	S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.	
	S28	After contact with skin, wash immediately with plenty of water.	
	S36/37/39	Wear suitable protective clothing, gloves and eye/face protection.	
	S45	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).	

## **16: OTHER INFORMATION**

Issue Date:27/04/2017Revised Date:Disclaimer:The information contained herein is derived from the best available sources and is<br/>believed to be accurate. However, no guarantee is expressed or implied regarding<br/>the accuracy of the data given in the use of this product.

**Rev. No.:** 00