

Material SAFETY DATA SHEET Quickmast EP550 - Base

1: PRODUCT AND COMPANY IDENTIFICATION

Product Name:	Quickmast EP550 - Base
Description:	Base component of three part epoxy tile adhesive
Manufacturer:	Don Construction Chemicals India LTD
	Tel. +914426185340/41/42
	www.dcp-int.com
Date Prepared:	11.05.14
MSDS Number:	DCP-IND/10/01-B

2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition:	Modified epoxy resin, r			
Hazardous Ingredient(s)	Symbol	Risk Phrases	CAS No.	%
Bisphenol-A epoxy resin Alkyl(C12-C14)glycidylether	Xi Xi, N	R36/38, 43 R36/38, 43, 51/53	25068-38-6 68609-97-2	> 85 < 15

Refer to Section 8 for Occupational Exposure Limits.

3: HAZARDS IDENTIFICATION

Hazard Information:	Irritating to eyes and respiratory system. May cause sensitization by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Classification:	Xi, N. R36/38, 43, 51/53.
4: FIRST AID MEASURES	
Eyes:	Irrigate immediately with copious quantities of water for 15 minutes, Eyelids should be held away from the eyeball to ensure thorough rinsing. Obtain medical attention if irritation persists.
Skin:	Wash thoroughly with soap and water or suitable skin cleanser as soon as possible. Remove contaminated clothing. Obtain medical advice if skin disorder develops.
Inhalation:	Move to fresh air. Obtain medical attention if needed.
Ingestion:	Immediately give plenty of water (if possible charcoal slurry). If a person vomits when lying on his back, place him in a recovery position. Do not induce vomiting. Obtain medical advice.
Issue No.: 01 Rev. No.:	00 Quickmast EP550 - Base Page 1 of 5



5: FIRE FIGHTING MEASURES

Flash Point:	> 150°C.
Special Exposure Hazards:	Formation of toxic gases is possible during heating or in case of fire.
Extinguishing Media:	Foam, dry powder, carbon dioxide, water spray jet.
Personal Protective Equipment:	Wear protective clothing and use self-contained breathing apparatus.

6: ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Put on adequate protective equipment.
Environmental Precautions:	Keep away from drains, surface-water, ground-water and soil.
Decontamination Procedures:	Collect as much as possible in a container for disposal. Soak up the remainder with inert absorbent. Disposal according to local regulations.

7: HANDLING AND STORAGE

Handling:	Do not breathe vapour. Avoid contact with skin and eyes.
Storage:	Keep in a dry cool ventilated place. Direct sunshine should be avoided. Keep away from ignition sources – No smoking. Keep container tightly closed. Keep away from food, drinks and animal food.

8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ingestion:	Prevent eating, drinking or smoking in the area of product use.						
Eye Contact:	Safety glasses or chemical goggles.						
Skin Contact:	Impervious gloves (e.g. PVC).						
Inhalation:	When mist occurs during spraying operations, wear suitable respiratory protective equipment.						
Respiratory Protection:	In case of insufficient ventilation, wear suitable equipment.						
Engineering Controls:	Use only in well ventilated areas. Local exhaust ventilation is recommended.						



9: PHYSICAL AND CHEMICAL PROPERTIES

Form:	Viscous liquid
Colour:	White
Odour:	Weak
Flash Point (closed cup) (°C):	> 150
Boiling Point (°C):	Not applicable
Explosive Properties (%):	Not applicable
Freezing Point (°C):	Not applicable
Relative Density (@25°C):	1.145 – 1.185
Water Solubility:	Insoluble

10: STABILITY AND REACTIVITY

Stability:	Stable.
Conditions to Avoid:	Excessive heating. Direct sunshine should be avoided. Electric discharge.
Chemical Incompatibility:	Strong acid, strong base, strong oxidizer and amines.
Hazardous Decomposition Products:	Formation of toxic gases is possible during heating or in case of fire.

11: TOXICOLOGICAL INFORMATION

The following toxicological assessment is based on knowledge of the toxicity of the product's components. Expected oral LD50, rat > 3000 mg/kg

Health Effects

On Eyes:	Irritant.
On Skin:	Irritant.
By Inhalation:	Irritant.
By Ingestion:	Irritant.
Chronic:	Not applicable.

12: ECOLOGICAL INFORMATION

Environmental Assessment:	When used and disposed off as intended, no adverse environmental effects are foreseen.
Mobility:	Not applicable.
Degradability:	Not biodegradable.
Bioaccumulation:	Not applicable.
Acute Fish Toxicity:	Toxic to aquatic organisms.

Issue No.:	01	Rev. No.:	00	Quickmast EP550 - Base	Page	3 of 5



13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

Unused Product:	Dispose off through an authorized waste contractor to a licensed site.
Used/ Contaminated Product:	As for unused product.
Packaging:	May be steam cleaned and recycled.

14: TRANSPORT INFORMATION



UN/SI Number: Transport Name:

Environmentally hazardous substance, liquid, n.o.s.

Transport Type:		Class:	Pack Group:	Marine Pollutant
At Sea	IMO	9	III	No
Air Transport	IATA/ICAO	9	III	
At land	RID/ADR	9	III	



15: REGULATORY INFORMATION

Hazard Label Data:	Xi	Ν
	Irritant	Dangerous for the environment
Contains:	Modified epoxy	resin.
Risk Phrases:		
	R36/38	Irritating to eyes and respiratory system.
	R43	May cause sensitization by skin contact.
	R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Safety Phrases:		
	S24	Avoid contact with skin.
	S28	After contact with skin, wash immediately with plenty of water.
	S37/39	Wear suitable gloves and eye/face protection.
	S60	This material and its container must be disposed of as hazardous waste.

16: OTHER INFORMATION

Issue Date:	11/05/2014	Revised Date:
Disclaimer:		rived from the best available sources and is guarantee is expressed or implied regarding se of this product.

Issue No.:	01	Rev. No.:	00	Quickmast EP550 - Base Page	5 of 5