

Material SAFETY DATA SHEET Quickmast EP550 - Hardener

1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Quickmast EP550 - Hardener

Chemical Family: Hardener component of three part epoxy tile adhesive

Manufacturer: Don Construction Chemicals India LTD

Tel. +914426185340/41/42

www.dcp-int.com

Date Prepared: 11.05.14

MSDS Number: DCP-IND/10/01-H

2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition: Epoxy curing agent.

Hazardous ingredient(s)SymbolRisk PhrasesCAS No.%Polyamide resinXiR36/38, 43, 52/53-> 852,4,6-tris(dimethylaminomethyl)phenolXnR22, 36/3890-72-2< 15</td>

Refer to Section 8 for Occupational Exposure Limits.

3: HAZARDS IDENTIFICATION

Hazard information: Harmful if swallowed.

Irritating to eyes and respiratory system. May cause sensitization by skin contact.

Harmful to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Classification: Xn. R22, 36/38, 43, 52/53.



4: FIRST AID MEASURES

Eyes: Irrigate immediately with copious quantities of water for 15 minutes,

Eyelids should be held away from the eyeball to ensure thorough rinsing.

Obtain medical attention if irritation persists.

Skin: Wash thoroughly with soap and water or suitable skin cleanser as soon as

possible. Remove contaminated clothing. Obtain medical advice if skin

disorder develop.

Inhalation: Move to fresh air. Obtain medical attention if needed.

Ingestion: Immediately give plenty of water (if possible charcoal slurry). If a person

vomits when lying on his back, place him in a recovery position. Administer oxygen or artificial respiration if needed. Do not induce

vomiting. Obtain medical advice.

5: FIRE FIGHTING MEASURES

Flash point: > 200°C.

Special Exposure Hazards: In case of fire toxic fumes will be formed (amines), Carbon oxides and

Nitrogen oxides.

Extinguishing media: Powder, carbon dioxide, foam, water mist (only large amounts).

Personal protective equipment: Wear protective clothing and use self-contained breathing apparatus.

6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Put on adequate protective equipment.

Environmental Precautions: Keep away from drains, surface-water, ground-water and soil.

Decontamination Procedures: Collect as much as possible in a container for disposal. Cover the

remainder with inert absorbent. Disposal according to local regulations.

7: HANDLING AND STORAGE

Handling: Do not breathe vapour. Avoid contact with skin and eyes.

Storage: Keep in a dry cool ventilated place. Direct sunshine should be avoided.

Keep away from ignition sources - No smoking.

Keep container tightly closed.

Keep away from food, drinks and animal food. Keep at temperatures between 2°C and 40°C.

Issue No.: 01 **Rev. No.:** 00 Quickmast EP550 - Hardener **Page** 2 of 5



8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ingestion: Prevent eating, drinking or smoking in the area of product use.

Eye contact: Safety glasses or chemical goggles.

Skin contact: Impervious gloves (e.g. PVC).

Inhalation: When mist occurs during spraying operations, wear suitable respiratory

protective equipment.

Respiratory protection: In case of insufficient ventilation, wear suitable equipment.

Engineering controls: Use only in well ventilated areas. Local exhaust ventilation is

recommended.

9: PHYSICAL AND CHEMICAL PROPERTIES

Form: Viscous liquid

Colour: White

Odour: Mild amines

Flash Point (closed cup) (°C): > 200

Boiling point ($^{\circ}$ C): Not applicable Explosive Properties (%): Not applicable Freezing point ($^{\circ}$ C): Not applicable Relative Density (@25 $^{\circ}$ C): 0.95 – 1.00 Water Solubility: Insoluble

10: STABILITY AND REACTIVITY

Stability: Stable.

Conditions to Avoid: Excessive heating. Direct sunshine should be avoided.

Chemical incompatibility: Acids, Reacts violently with oxidizing agents.

Hazardous Decomposition Products: Noxious fumes, carbon oxides, nitrogen oxides.



11: TOXICOLOGICAL INFORMATION

The following toxicological assessment is based on knowledge of the toxicity of the product's components. Expected oral LD50, rat >15 g/kg

Health Effects

On Eyes: Irritant.
On Skin: Irritant.
By Inhalation: Irritant.
By Ingestion: Irritant.

Chronic: Not applicable.

12: ECOLOGICAL INFORMATION

Environmental Assessment: When used and disposed off as intended, no adverse environmental

effects are foreseen.

Mobility: Not applicable.

Degradability: Not applicable.

Bioaccumulation: Bioaccumulative potential.

Acute fish toxicity: May cause long-term adverse effects in the aquatic environment.

13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

Unused Product: Dispose off through an authorized waste contractor to a licensed site.

Used/ Contaminated Product: As for unused product.

Packaging: May be steam cleaned and recycled.

14: TRANSPORT INFORMATION

This product is **not** classified as dangerous for transport.



15: REGULATORY INFORMATION

Hazard Label Data: Xr

*

Harmful

Contains: Polyamide resin

Risk Phrases:

R22 Harmful if swallowed.

R36/38 Irritating to eyes and respiratory system.

R43 May cause sensitization by skin contact.

R52/53 Harmful to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.

Safety Phrases:

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with

plenty of water and seek medical advice.

S36/37/39 Wear suitable protective clothing, gloves and eye/face

protection.

16: OTHER INFORMATION

Issue Date: 11/05/2014 Revised Date:

Disclaimer: The information contained herein is derived from the best available sources and is

believed to be accurate. However, no guarantee is expressed or implied regarding

the accuracy of the data given in the use of this product.

Issue No.: 01 Rev. No.: 00 Quickmast EP550 - Hardener Page 5 of 5