

Material SAFETY DATA SHEET Quickmast SB - Base

1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Quickmast SB - Base

Description: Base component of two parts epoxy adhesive

Manufacturer: **Don Construction Products**

P.O. Box 24839, Doha, Qatar

Tel. + 974 4 411 4004 Fax: + 974 4 411 4014

www.dcp-int.com

Date Prepared: 28.05.2008

MSDS Number: DCP/09/04/16-B

2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition: Epoxy resin, pigment.

Hazardous Ingredient(s) Symbol Risk Phrases CAS No. %
Epoxy resin Xi, N R36/38, 43, 51/53. 25068-38-6 60

(Number average molecular weight <700)

Refer to Section 8 for Occupational Exposure Limits.

3: HAZARDS IDENTIFICATION

Hazard Information: Irritating to eyes and skin.

May cause sensitization by skin contact.

Toxic to aquatic organism, may cause long-term affects in the aquatic

environment.

Classification: Xi, N. R36/38, 43, 51/53

4: FIRST AID MEASURES

Eyes: Irrigate immediately with copious quantities of water for 15 minutes.

Obtain medical attention if irritation persists.

Skin: Wash immediately with soap and water or suitable skin cleanser. Obtain

medical advice if skin disorders develop.

Inhalation: Remove from exposure. If feeling unwell obtain medical attention.

Ingestion: Obtain medical attention. DO NOT induce vomiting. Beware of aspiration

if vomiting occurs.

Tssue No.:	01	Doy No. 1 01	Quickmact CB Raco	Dago 1 of F
i issue no.:	U I	Rev. No.: ()]	Ouickmast SB - Base	Page 1 of 5



5: FIRE FIGHTING MEASURES

Flash Point: > 150°C.

Lower Explosive Limit: Not applicable.

Extinguishing Media: Carbon dioxide, powder, foam or water.

Personal Protective Equipment: Self-contained breathing apparatus.

6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Wear suitable protective clothing, gloves and eye/face protection.

Environmental Precautions: Prevent entry into drains, sewers and water courses.

Decontamination Procedures: Soak up with inert absorbent and remove by best available means. Gather

into containers. Dispose off as waste.

7: HANDLING AND STORAGE

Handling: Maintain good standards of personal hygiene. Avoid skin and eye contact.

Do not eat, drink or smoke whilst using this product. Ensure adequate

ventilation.

Storage: Keep containers dry and tightly closed.

8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ingestion: Prevent eating, drinking or smoking in the area of product use.

Eye Contact: Safety glasses/goggles.

Skin Contact: Impervious gloves (e.g. PVC). Plastic apron. Change contaminated clothing and

clean before re-use.

Respiratory Protection: No specific ventilation requirements noted.

Engineering Controls: None assigned.

Issue No.: 01 **Rev. No.:** 01 Quickmast SB - Base **Page** 2 of 5



9: PHYSICAL AND CHEMICAL PROPERTIES

Form: Paste
Colour: White
Odour: Mild

pH (concentrate):

Boiling Point (°C):

Not applicable

Flash Point (closed cup) ($^{\circ}$ C): > 150

Autoflammability (°C): Not determined

Explosive Properties (%): Not known Relative Density (@25°C): 1.35 - 1.55 Water Solubility: Insoluble

10: STABILITY AND REACTIVITY

Stability: Stable: reacts with compounds containing amino, hydroxyl or carboxyl

groups to give stable, cross linked materials.

Conditions to Avoid: None Known.

Chemical Incompatibility: Strong acids. Strong alkalis. Strong oxidizing agents.

Hazardous Decomposition Products: Thermal decomposition yields oxides of carbon and irritant fumes.

11: TOXICOLOGICAL INFORMATION

The following toxicological assessment is based on knowledge of the toxicity of the product's components. Expected oral LD50, rat > 2 g/kg. Classified as a skin sensitizer.

Health Effects

On Eyes: Causes transient irritation.

On Skin: Irritation. May cause sensitization. By Inhalation: May Cause respiratory irritation.

By Ingestion: May cause irritation of mouth, throat and digestive tract.

Chronic: Repeated and prolonged skin contact may lead to skin disorders.

Issue No.: 01 **Rev. No.:** 01 Quickmast SB - Base **Page** 3 of 5



12: ECOLOGICAL INFORMATION

Environmental Assessment: When used and disposed off as intended, no adverse environmental

affects are foreseen.

Mobility: Viscous liquid. Insoluble in water.

Degradability: Not readily biodegradable.

Bioaccumulation: Has the potential to bioaccumulate.

Acute Fish Toxicity: Expected to be ecotoxic to fish/daphnia/algae.

13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

Unused Product: Dispose off through an authorized waste contractor to a licensed site. May

be reacted with hardener component to give an inert polymeric material.

Used/ Contaminated Product: As for unused product.

Packaging: Must be disposed off through an authorized waste contractor.

14: TRANSPORT INFORMATION



UN Number: 3082

Transport Name: Environmentally hazardous substance, liquid n.o.s. (Epoxy resin).

Transport Type:		Class:	Pack Group:	Marine Pollutant
At Sea	IMO	9	III	No
Air Transport	IATA/ICAO	9	III	
At land	RID/ADR	9	III	

Issue No.: 01 **Rev. No.:** 01 Quickmast SB - Base **Page** 4 of 5



15: REGULATORY INFORMATION

Hazard Label Data: Xi N





Irritant

Dangerous for the environment

Named Ingredients: Epoxy resin (Number average molecular weight < 700).

UN Number: 3082

Risk Phrases:

R36/38 Irritating to eyes and skin.

R43 May cause sensitization by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term

adverse in the aquatic environment.

Safety Phrases:

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with

plenty of water and seek medical advice.

S37/39 Wear suitable gloves and eye/face protection.

16: OTHER INFORMATION

Issue Date: 28.05.08 Revised Date: 06.04.2020

Disclaimer: The information contained herein is derived from the best available sources and is

believed to be accurate. However, no guarantee is expressed or implied regarding

the accuracy of the data given in the use of this product.

Issue No.: 01 **Rev. No.:** 01 Quickmast SB - Base **Page** 5 of 5