

# Repcoat S Primer

Silane/siloxane based hydrophobic primer



## Description

Repcoat S Primer is a penetrating hydrophobic silane/siloxane based primer. It is used as a primer for Repcoat S acrylic based protective coating. When applied, it reacts with concrete and masonry surfaces producing a clear hydrophobic barrier that prevents the passage of water and hence protects exposed reinforced concrete structures from attack by chloride ions.

## Applications

- ▲ Deep penetration into substrate.
- ▲ Very good reduction of water and chloride intrusion.
- ▲ Breathable, allows for water vapour release.

## Method of Use

### Surface Preparation

Surface must be clean, sound and free from oil, grease, curing compound, or any contamination. Any contaminants should be removed by light grit blasting.

Surfaces containing slight surface imperfection or blowholes should be filled with a skim coat of cementitious repair mortar such as Cemfair PF. Deep holes and defected areas should be repaired with cementitious products from DCP-Repair range.

### Application

Repcoat S Primer should be spray or brush applied at the rate of 0.2 litre per square meter.

Repcoat S Primer should be left to cure for 5 hours at 25°C before the application of Repcoat S.

### Cleaning

Tools and equipment can be cleaned with DCP-solvent when wet. Hardened materials must be cleaned mechanically.

### Packaging

Repcoat S Primer is available in 18 and 200 litre drums.

### Technical Properties:

Specific gravity:	0.85 ± 0.02
VOC: ASTM D2369	< 750 g/ltr

### Coverage

0.2 litre/m<sup>2</sup> per coat.

### Storage

Repcoat S Primer should be stored under cover at an ambient temperature range of 10 - 25°C.

### Shelf Life

Repcoat S Primer has a shelf life of 12 months from date of manufacture if stored in proper conditions and sealed drums.

If these conditions are exceeded, DCP Technical Department should be contacted for advise.

### Cautions

#### Health and safety

Care should be taken during use and storage to avoid contact with skin, eyes and mouth. Wear suitable protective clothing, gloves and eye/face protection.

Should accidental skin contact occur, remove immediately with plenty of clean water. If swallowed, seek medical attention immediately - do not induce vomiting.

For further information refer to the Material Safety Data Sheet.

#### Fire

Repcoat S Primer is flammable. Ensure adequate ventilation. Do not use near a naked flame and do not smoke during use.

*Flash Point:* > 36°C.

# Repcoat S Primer

## More from Don Construction Products

A wide range of construction chemical products are manufactured by DCP which include:

- ▲ Concrete admixtures.
- ▲ Surface treatments
- ▲ Grouts and anchors.
- ▲ Concrete repair.
- ▲ Flooring systems.
- ▲ Protective coatings.
- ▲ Sealants.
- ▲ Waterproofing.
- ▲ Adhesives.
- ▲ Tile adhesives and grouts.
- ▲ Building products.
- ▲ Structural strengthening.


### Note:

We endeavor to ensure that any advice, recommendation or information we may give in product literature is accurate and correct. However, due to the fact that we have no direct or continuous control over where or how the products are applied, DCP cannot accept any liability either directly or indirectly arising from the use of DCP products, whether or not in accordance with any advice, specification, recommendation or information given by us.

[www.dcp-int.com](http://www.dcp-int.com)

 expertise

 quality

 full range