

Material SAFETY DATA SHEET Repcoat ZR471 - Base

PRODUCT AND COMPANY IDENTIFICATION 1:

Product Name: Repcoat ZR471 - Base

Description: Base component of two component epoxy based zinc rich primer for steel

Manufacturer: **Don Construction Products/Jordan**

P.O. Box 1117, Amman 11118 Jordan

Tel. + 962 6 5338891 Fax: + 962 6 5338829

www.dcp-int.com

MSDS Number: Date: 07.08.2024 DCP/04/05/086-B

COMPOSITION / INFORMATION ON INGREDIENTS 2:

Composition: Epoxy resin, solvent, inert fillers.

Symbol Hazardous Ingredient(s) Risk Phrases CAS No. % Epoxy resin Xi, N R36/38, 43, 51/53 25068-38-6 20-45 (Number average molecular weight <700) Xylene Xn R10, 20/21, 38 1330-20-7 10-25 Zinc dust 7440-66-6 10-20 R50/53 N solvent Xn,F R10 64742-95-6 < 15

Refer to Section 8 for Occupational Exposure Limits.

HAZARDS IDENTIFICATION 3:

Hazard Information: Flammable.

> Harmful by inhalation and in contact with skin. Irritating to eyes, respiratory system and skin.

May cause sensitization by skin contact.

Toxic to aquatic organism, may cause long-term affects in the aquatic

Environment.

Classification: Xn, F, N. R10, 20/21, 36/37/38, 43, 51/53.

Issue No.: 01 Rev. No.: 00 Repcoat ZR471 - Base Page 1 of 6



4: FIRST AID MEASURES

Eyes: Irrigate immediately with copious quantities of water for 15 minutes.

Obtain medical attention urgently.

Skin: Wash immediately with soap and water or suitable skin cleanser. Remove

contaminated clothes and shoes. Obtain medical advice if skin disorders

develop.

Inhalation: Remove from exposure; obtain medical attention if respiratory irritation

develops or if breathing becomes difficult.

Ingestion: Rinse mouth thoroughly. Drink plenty of water. Do not induce vomiting.

Obtain medical attention. Beware of aspiration if vomiting occurs.

5: FIRE FIGHTING MEASURES

Flash Point (Closed Cup): 42°C.

Extinguishing Media: Carbon dioxide, powder, foam or water fog - Do not use water jets.

Personal Protective Equipment: Self-contained breathing apparatus.

Special Exposure Hazards: Toxic fumes. Carbon oxides.

6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Immediately issue NO SMOKING and NO NAKED FLAMES warnings, Wear

suitable protective clothing, gloves and eye/face protection.

Environmental Precautions: Prevent entry into drains, sewers and water courses.

Decontamination Procedures: Soak up with inert absorbent such as sand. Gather into labeled

containers. Dispose off as applicable regulations.

7: HANDLING AND STORAGE

Handling: Maintain good standards of personal hygiene. Avoid skin and eye contact.

Do not eat, drink or smoke whilst using this product. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory

equipment.

Storage: Keep container tightly closed in a cool dry area away from sources of heat

and out of direct sunlight to avoid pressure build up. Store in conformity

with local fire regulations. Store away from sources of ignition.

Issue No.: 01 **Rev. No.:** 00 Repcoat ZR471 – Base **Page** 2 of 6



8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Eye Protection: Safety glasses/goggles.

Skin Protection: Impervious gloves (e.g. PVC). Suitable protective clothing.

Respiratory Protection: Organic chemical cartridge respirator.

Hygiene Measures: Change contaminated clothing and clean before re-use.

Engineering Controls: Use only in well ventilated areas. Local exhaust ventilation is

recommended.

Exposure Guidelines: OSHA PEL STEL

Xylene 100ppm 150ppm

9: PHYSICAL AND CHEMICAL PROPERTIES

Form: Viscous liquid "free from impurities"

Colour: Various
Odour: Aromatic

pH (concentrate): Not applicable

Boiling Point (°C): 135 - 150

Flash Point (closed cup) (°C): 42

Autoflammability (°C): Not applicable Explosive Properties (%): Not Known Relative Density (@25°C): 1.3-1.5 Water Solubility: Insoluble

10: STABILITY AND REACTIVITY

Stability: Contains volatile solvent. Stable: reacts with compounds containing

amino, hydroxyl or carboxyl groups to give stable, cross linked materials.

Conditions to Avoid: Any source of ignition. And temperatures above 35°C. Chemical Incompatibility: Strong acids. Strong alkalis. Strong oxidizing agents.

Hazardous Decomposition Products: Thermal decomposition yield oxides of carbon, toxic fumes.

Issue No.: 01 **Rev. No.:** 00 Repcoat ZR471 – Base **Page** 3 of 6



11: TOXICOLOGICAL INFORMATION

The following toxicological assessment is based on knowledge of the toxicity of the product's components. Acute Oral effect LD50 > 2000mg/kg.

Health Effects

On Eyes: Irritant.

On Skin: Moderate irritation.

By Inhalation: May cause respiratory irritation.

By Ingestion: May cause irritation of mouth, throat and digestive tract.

Chronic: Repeated and prolonged skin contact may lead to skin disorders.

12: ECOLOGICAL INFORMATION

Environmental Assessment: Contains volatile organic compounds.

Mobility: Viscous liquid. Contains volatile components.

Degradability: Not readily biodegradable.

Bioaccumulation: Not expected to be bioaccumulate.

Acute Fish Toxicity: Ecotoxic to fish/daphnia/algae.

13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

Unused Product: Dispose off through an authorized waste contractor to a licensed site.

Used/ Contaminated Product: As for unused product.

Packaging: Must be disposed off through an authorized waste contractor.

Issue No.: 01 **Rev. No.:** 00 Repcoat ZR471 – Base **Page** 4 of 6



14: TRANSPORT INFORMATION



UN Number: 1866

Transport Name: Resin solution, flammable. Contains xylene.

Transport Type:		Class:	Pack Group:	Marine Pollutant
At Sea	IMDG	3.3	II	No
Air Transport	ICAO/IATA	3	II	
At land	ADR/RID	3	Item 31c	



15: REGULATORY INFORMATION

Hazard Label Data: Xn N

*



Harmful Dangerous for the environment

Named Ingredients: Epoxy resin (Number average molecular weight <700).

Xylene

UN Number: 1866

Risk Phrases:

R10 Flammable.

R20/21 Harmful by inhalation and in contact with skin.
R36/37/38 Irritating to eyes, respiratory system and skin.

R43 May cause sensitization by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term

adverse in the aquatic environment.

Safety Phrases:

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with

plenty of water and seek medical advice.

S36/37/39 Wear suitable protective clothing, gloves and eye/face

protection.

16: OTHER INFORMATION

Disclaimer: The information contained herein is derived from the best available sources and is

believed to be accurate. However, no guarantee is expressed or implied regarding

the accuracy of the data given in the use of this product.

Issue No.: 01 **Rev. No.:** 00 Repcoat ZR471 – Base **Page** 6 of 6