

# Sealguard 600

Elastomeric acrylic waterproof coating for roofs



## Description

Sealguard 600 is an acrylic based elastomeric, waterproof coating for roofs and walls. Sealguard 600 is suitable for application on several substrates such as on concrete, masonry, plaster and terrazzo tiles.

## Applications

Sealguard 600 is designed for use as a waterproof coating in:

- ▲ Sloped roofs and vertical walls.
- ▲ Over existing terrazzo tiles.
- ▲ Over roof polyurethane foam.

## Advantages

- ▲ Elastomeric.
- ▲ Single component, easy to apply.
- ▲ Good resistance against UV.
- ▲ Does not support the growth of fungus.
- ▲ Easy maintenance.
- ▲ Economical.
- ▲ Environmentally friendly, water based system.

## Method of Use

### Application

Sealguard 600 can be applied by brush, roll, or airless spray machine. The first coat of Sealguard 600 should be applied at the rate of 1.5 - 2.0 m<sup>2</sup>/kg and allowed to cure for 4 - 12 hours depending on ambient temperature.

The second coat should be applied perpendicular to the first coat at the same rate above, and allowed to cure. For heavy pedestrian traffic, it is recommended to use fibreglass scrim reinforcement, embedded firmly in the second coat while wet, and a third coat should be applied.

### Notes:

- ▲ Sealguard 600 should not be applied at ambient temperatures below 5°C and dropping. Sealguard 600 should not be applied on surfaces expected to suffer from rising dampness or relative humidity greater than 75%.

## Technical Properties:

Appearance:	Thick liquid
Specific gravity:	1.4 ± 0.1
Solid content:	60 ± 5%
Elongation: ASTM D412	≥ 150%
Tensile strength: ASTM D412	≥ 1.0 MPa
Minimum application temperature:	5°C
Overcoating time:	Minimum 4 hr
VOC: ASTM D2369	≤ 50 g/ltr

- ▲ It is recommended to protect Sealguard 600 by in situ cement screed, tiles, non-woven geotextile, insulation board, or other means, this becomes a mandatory when applying the black colour of Sealguard 600 over exposed areas.

## Cleaning

All tools should be washed and cleaned immediately after use with clean water.

## Packaging

Sealguard 600 is available in 5 and 20 kg packs.

## Coverage

1.5 - 2.0 m<sup>2</sup>/kg per coat.

**DCP Saudi Co.**  
*Riyadh Offices:*  
Exit 9, Al Izdehar, Beside ACDelco Petrol Station  
  
*Jeddah Offices:*  
Al-Henaki Business Center, Tower C



# Sealguard 600

## Storage

Sealguard 600 has a shelf life of 12 months from date of manufacture if stored at temperatures between 5°C and 40°C.

If these conditions are exceeded, contact DCP Technical Department for advice.

## Cautions

### Health and Safety

As with all acrylic paints, care should be taken during use and storage to avoid contact with skin, eyes and mouth. Wear suitable protective clothing, gloves and eye/face protection.

Should accidental skin contact occur, remove immediately with plenty of clean water. If swallowed, seek medical attention immediately - do not induce vomiting.

For further information, refer to the Material Safety Data Sheet.

## Fire

Sealguard 600 is nonflammable.

## More from Don Construction Products

A wide range of construction chemical products are manufactured by DCP which include:

- ▲ Concrete admixtures.
- ▲ Surface treatments
- ▲ Grouts and anchors.
- ▲ Concrete repair.
- ▲ Flooring systems.
- ▲ Protective coatings.
- ▲ Sealants.
- ▲ Waterproofing.
- ▲ Adhesives.
- ▲ Tile adhesives and grouts.
- ▲ Building products.
- ▲ Structural strengthening.

### DCP Saudi Co.

#### Riyadh Offices:

Exit 9, Al Izdehar, Beside ACDelco Petrol Station

#### Jeddah Offices:

Al-Henaki Business Center, Tower C

### Note:

We endeavour to ensure that any information, advice or recommendation we may give in product literature is accurate and correct. However, because we have no control over where and how products are applied, we cannot accept any liability arising from the use of the products.

-  expertise
-  quality
-  full range

