



Material SAFETY DATA SHEET

Setseal 100C

1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: **Setseal 100C**
Description: Acrylic cement modified one component waterproof coating
Manufacturer: **Ayla for Building Materials Industry & Trade**
Al-Karadeh, Arsat Al-Hindia, Baghdad
Tel.: +964 790 1488 730
www.dcp-int.com
Date Prepared: 14.11.14
MSDS Number: DCP/08/02/41

2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition: Cement, silica sand, polymers.

| Hazardous Ingredient(s) | Symbol | Risk Phrases | CAS No. | % |
|-------------------------|--------|--------------|------------|---------|
| Portland cement | Xi | R36/37/38 | 65997-15-1 | 20 - 50 |

Refer to Section 8 for Occupational Exposure Limits.

3: HAZARDS IDENTIFICATION

Hazard Information: Irritating to eyes and skin.
May cause long-term adverse effects in the aquatic environment.
Classification: Xi. R36/38, 53.

4: FIRST AID MEASURES

Eyes: Irrigate immediately with copious quantities of water for 15 minutes, lifting the upper and lower eyelids intermittently to remove all particles. Obtain medical attention if irritation persists.
Skin: Wash thoroughly with soap and water or suitable skin cleanser as soon as possible. Obtain medical advice if skin disorder develops.
Inhalation: Remove from exposure, if breathing is difficult, administer oxygen. If not breathing, give artificial respiration. Obtain medical attention if needed.
Ingestion: Rinse mouth with water. Dilute by giving 1 or 2 glasses of water. Do not induce vomiting. Never give anything by mouth to an unconscious person. See a medical doctor immediately.



5: FIRE FIGHTING MEASURES

Flash Point: None.
Special Exposure Hazards: None.
Extinguishing Media: Water, water fog, carbon dioxide (CO₂), dry chemical.
Personal Protective Equipment: Wear full protective clothing and self-contained breathing apparatus.

6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Wear rubber boots in addition to the recommended protective clothing.
Environmental Precautions: Prevent large quantities of this product from contacting vegetation or waterways; large spills could kill vegetation and fish.
Decontamination Procedures: This product, if spilled, can be recovered and re-used if contamination does not present a problem. Vacuum or sweep up the material. If the spilled product is unusable due to contamination, consult state or federal environmental agencies for acceptable disposal procedures and locations.

7: HANDLING AND STORAGE

Handling: Avoid skin and eye contact. Avoid breathing dust. Avoid dust formation.
Storage: Store in a cool dry area, away from acids.

8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ingestion: Prevent eating, drinking or smoking in the area of product use.
Eye Contact: Safety glasses or chemical goggles.
Skin Contact: Impervious gloves (e.g. PVC).
Inhalation: When mist occurs during spraying operations, wear suitable respiratory protective equipment.
Respiratory Protection: In case of insufficient ventilation, wear suitable equipment.
Engineering Controls: No specific ventilation requirement noted.
Exposure Guidelines: None assigned.

| Name | OSHA PEL (8-Hour TWA) | ACGIH TLV-TWA |
|-------------------|--|---------------------------------|
| Cement – Portland | 5 mg respirable dust/m ³ 15 mg total dust/m ³ | 10 mg total dust/m ³ |



9: PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--------------------------------|----------------|
| Form: | Solid |
| Colour: | Grey |
| Odour: | None |
| Flash Point (closed cup) (°C): | Not applicable |
| Boiling Point (°C): | Not applicable |
| Explosive Properties (%): | Not applicable |
| Freezing Point (°C): | Not applicable |
| Relative Density (@25°C): | 1.80 – 1.90 |
| Water Solubility: | Soluble |

10: STABILITY AND REACTIVITY

| | |
|-----------------------------------|--|
| Stability: | Stable. |
| Conditions to Avoid: | Humidity. |
| Chemical Incompatibility: | Aluminium powder, acids, fluorine, molten lithium, ammonium salts. |
| Hazardous Decomposition Products: | Heated to decomposition, it emits fumes of sodium oxide. |

11: TOXICOLOGICAL INFORMATION

Health Effects

| | |
|----------------|---|
| On Eyes: | Irritating and may injure eye tissue if not removed promptly. |
| On Skin: | Irritation. May cause sensitization. |
| By Inhalation: | Irritant. |
| By Ingestion: | May cause irritation of mouth, throat and digestive tract. |
| Chronic: | Repeated and prolonged skin contact may lead to skin disorders. |

12: ECOLOGICAL INFORMATION

| | |
|---------------------------|--|
| Environmental Assessment: | When used and disposed off as intended, no adverse environmental effects are foreseen. |
| Mobility: | Mobile liquid. |
| Degradability: | Not readily biodegradable. |
| Bioaccumulation: | Not expected to be bioaccumulate. |
| Acute Fish Toxicity: | Expected to be ecotoxic to daphnia magna and bluegill sunfish. |

13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

Unused Product: Dispose off through an authorized waste contractor to a licensed site.

Used/ Contaminated Product: As for unused product.

Packaging: May be steam cleaned and recycled.

14: TRANSPORT INFORMATION

This product is **not** classified as dangerous for transport.

15: REGULATORY INFORMATION

Hazard Label Data:

Xi



Irritant

Risk Phrases:

R36/37//38 Irritating to eyes, respiratory system and skin

Safety Phrases:

S22 Do not breathe dust.
 S24/25 Avoid contact with skin and eyes.
 S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
 S36/37/39 Wear suitable protective clothing, gloves and eye/face protection.

16: OTHER INFORMATION

Issue Date: 14/11/2014 Revised Date:

Disclaimer: The information contained herein is derived from the best available sources and is believed to be accurate. However, no guarantee is expressed or implied regarding the accuracy of the data given in the use of this product.