

Material SAFETY DATA SHEET Setseal 200C

1: PRODUCT AND COMPANY IDENTIFICATION

Product Name:	Setseal 200C	
Description:	Acrylic cement modified one compo	nent waterproof coating
Manufacturer:	Ayla Construction Chemicals	
	P.O. Box 1117, Amman 11118 Jorda	an
	Tel. + 962 6 5338891	Fax: + 962 6 5338829
	www.dcp-int.com	
Date Prepared:	14.11.14	
MSDS Number:	DCP/08/02/78	

2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition:	Cement, Silica sand, Polymers.			
Hazardous Ingredient(s)	Symbol	Risk Phrases	CAS No.	%
Portland cement	Xi	R36/37/38	65997-15-1	15 - 45

Refer to Section 8 for Occupational Exposure Limits.

3: HAZARDS IDENTIFICATI	3: HAZARDS IDENTIFICATION		
Hazard Information:	Irritating to eyes and skin. May cause long-term adverse effects in the aquatic environment.		
Classification:	Xi. R36/38, 53.		
4: FIRST AID MEASURES			
Eyes:	Irrigate immediately with copious quantities of water for 15 minutes, lifting the upper and lower eyelids intermittently to remove all particles. Obtain medical attention if irritation persists.		
Skin:	Wash thoroughly with soap and water or suitable skin cleanser as soon as possible. Obtain medical advice if skin disorder develops.		
Inhalation:	Remove from exposure, if breathing is difficult, administer oxygen. If not breathing, give artificial respiration. Obtain medical attention if needed.		
Ingestion:	Rinse mouth with water. Dilute by giving 1 or 2 glasses of water. Do not induce vomiting. Never give anything by mouth to an unconscious person. See a medical doctor immediately.		

Issue No.:	01	Rev. No.: 00	Setseal 200C	Page 1 of 4



5: FIRE FIGHTING MEASURES

Flash Point:	None.
Special Exposure Hazards:	None.
Extinguishing Media:	Water, water fog, carbon dioxide (CO ₂), dry chemical.
Personal Protective Equipment:	Wear full protective clothing and self-contained breathing apparatus.

6: ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Wear rubber boots in addition to the recommended protective clothing.
Environmental Precautions:	Prevent large quantities of this product from contacting vegetation or waterways; large spills could kill vegetation and fish.
Decontamination Procedures:	This product, if spilled, can be recovered and re-used if contamination does not present a problem. Vacuum or sweep up the material. If the spilled product is unusable due to contamination, consult state or federal environmental agencies for acceptable disposal procedures and locations.

7: HANDLING AND STORAGE

Handling:	Avoid skin and eye contact. Avoid breathing dust. Avoid dust formation.
Storage:	Store in a cool dry area, away from acids.

8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ingestion:	Prevent eating, drinking or smoking in the area of product use.
Eye Contact:	Safety glasses or chemical goggles.
Skin Contact:	Impervious gloves (e.g. PVC).
Inhalation:	When mist occurs during spraying operations, wear suitable respiratory protective equipment.
Respiratory Protection:	In case of insufficient ventilation, wear suitable equipment.
Engineering Controls:	No specific ventilation requirement noted.
Exposure Guidelines:	None assigned.

Name	OSHA PEL (8-Hour TWA)	ACGIH TLV-TWA
Cement – Portland	5 mg respirable dust/m ³ 15 mg total dust/m ³	10 mg total dust/m ³

Issue No.:	01	Rev. No.:	00	Setseal 200C	Page	2 of 4



9: PHYSICAL AND CHEMICAL PROPERTIES

Form:	Solid
Colour:	Grey
Odour:	None
Flash Point (closed cup) (°C):	Not applicable
Boiling Point (°C):	Not applicable
Explosive Properties (%):	Not applicable
Freezing Point (°C):	Not applicable
Relative Density (@25°C):	1.75 – 1.85
Water Solubility:	Soluble

10: STABILITY AND REACTIVITY

Stability:	Stable.
Conditions to Avoid:	Humidity.
Chemical Incompatibility:	Aluminium powder, acids, fluorine, molten lithium, ammonium salts.
Hazardous Decomposition Products:	Heated to decomposition, it emits fumes of sodium oxide.

11: TOXICOLOGICAL INFORMATION

Health Effects

On Eyes:	Irritating and may injure eye tissue if not removed promptly.		
On Skin:	Irritation. May cause sensitization.		
By Inhalation:	Irritant.		
By Ingestion:	May cause irritation of mouth, throat and digestive tract.		
Chronic:	Repeated and prolonged skin contact may lead to skin disorders.		

12: ECOLOGICAL INFORMATION

Environmental Assessment:	When used and disposed off as intended, no adverse environmental effects are foreseen.		
Mobility:	Mobile liquid.		
Degradability:	Not readily biodegradable.		
Bioaccumulation:	Not expected to be bioaccumulate.		
Acute Fish Toxicity:	Toxicity: Expected to be ecotoxic to daphnia magnia and bluegill sunfish.		

Issue No.:	01	Rev. No.:	00	Setseal 200C Page	3 of 4



13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

Unused Product:	Dispose off through an authorized waste contractor to a licensed site.		
Used/ Contaminated Product:	As for unused product.		
Packaging:	May be steam cleaned and recycled.		

14: TRANSPORT INFORMATION

This product is **not** classified as dangerous for transport.

15: REGULATORY INFORMATION

Hazard Label Data:



Irritant

R36/37//38

Risk Phrases:

Safety Phrases:

S22	Do not breathe dust.
S24/25	Avoid contact with skin and eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S36/37/39	Wear suitable protective clothing, gloves and eye/face protection.

Irritating to eyes, respiratory system and skin

16: OTHER INFORMATION

Issue Date:	14/11/2014	Revised Date:
Disclaimer:		rived from the best available sources and is guarantee is expressed or implied regarding se of this product.

Setseal 200C

Issue No.:	01	Rev. No.:	00	