

Material SAFETY DATA SHEET Setseal C - Liquid

1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Setseal C - Liquid

Chemical Family: Liquid component of two parts elastomeric cementitious coating

Manufacturer: Don Construction Chemicals India LTD

Tel. +914426185340/41/42

www.dcp-int.com

Date Prepared: 21.10.13

MSDS Number: DCP-IND/08/02-L

2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition: Water, styrene acrylic copolymer.

Hazardous ingredient(s)SymbolRisk PhrasesCAS No.%Water--7732-18-540 - 60Styrene acrylic copolymer--25586-20-330 - 50

Refer to Section 8 for Occupational Exposure Limits.

3: HAZARDS IDENTIFICATION

No significant hazard.

4: FIRST AID MEASURES

Eyes: Irrigate immediately with copious quantities of water for 15 minutes.

Obtain medical attention if irritation persists.

Skin: Wash thoroughly with soap and water or suitable skin cleanser as soon as

possible.

Inhalation: Remove from exposure – unlikely to occur.

Ingestion: Wash out mouth with water. Don't induce vomiting. Obtain medical

attention.

Issue No.: 01 Rev. No.: 00 Setseal C - Liquid Page 1 of 4



5: FIRE FIGHTING MEASURES

Flash point: None.

Special Exposure Hazards: Material can splatter above 100°C. Polymer film can burn. Irritant fumes. Extinguishing media: Carbon dioxide, powder, foam or water fog – Do not use water jets.

Personal protective equipment: Self-contained breathing apparatus.

6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Wear suitable protective clothing, gloves and eye/face protection. Mixed

with component A, the mixture can be irritating to the eyes and skin.

Environmental Precautions: Prevent entry into drains, sewers and water courses.

Decontamination Procedures: Soak up with inert absorbent or container and remove by best available

means. Gather into containers.

7: HANDLING AND STORAGE

Handling: Avoid skin and eye contact.

Storage: Store in cool and dry area. Protect from frost.

8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ingestion: Prevent eating, drinking or smoking in the area of product use.

Eye contact: Safety glasses/goggles.

Skin contact: Impervious gloves (e.g. PVC).

Respiratory protection: In case of insufficient ventilation wear suitable equipment. Change

contaminated clothing and clean before re-use.

Engineering controls: No specific ventilation requirement noted.

Exposure guidelines: None assigned.

Issue No.: 01 Rev. No.: 00 Setseal C - Liquid Page 2 of 4



9: PHYSICAL AND CHEMICAL PROPERTIES

Form: Liquid
Colour: White
Odour: Acrylic
pH (concentrate): 7.0 – 9.0
Boiling Point (°C): 100°C

Flash Point (closed cup) (°C):

Autoflammability (°C): Not determined

Explosive Properties (%):

Vapor Pressure (KPa @20°C):

Relative Density (@25°C):

Under Solubility:

Not known

2.3 (water)

1.015 – 1.030

Emulsifiable

10: STABILITY AND REACTIVITY

Stability: Stable.

Conditions to Avoid: Temperature below 2°C.

Chemical incompatibility: None known.

Hazardous Decomposition Products: Thermal decomposition may yield acrylic monomers.

None

11: TOXICOLOGICAL INFORMATION

The following toxicological assessment is based on knowledge of the toxicity of the product's components. Expected oral LD50, rat > 2000 mg/kg.

Health Effects

On Eyes: May cause transient irritation.

On Skin: Unlikely to irritate on brief occasional exposure.

By Inhalation: Low volatility makes inhalation unlikely at ambient temperatures.

By Ingestion: Low order of acute toxicity. May cause irritation of mouth, throat and

digestive tract.

Issue No.: 01 Rev. No.: 00 Setseal C - Liquid Page 3 of 4



12: ECOLOGICAL INFORMATION

Environmental Assessment: When used and disposed off as intended, no adverse environmental

effects are foreseen.

Mobility: Mobile liquid. Emulsifiable in water.

Degradability: Inherently biodegradable.

Bioaccumulation: Not expected to be bioaccumulative.

Acute fish toxicity: Not expected to be ecotoxic to fish/ daphnia/ algae.

13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

Unused Product: Dispose off in an approved manner. Do not empty into drains, sewers or

water courses.

Used/ Contaminated Product: As for unused product.

Packaging: May be steam cleaned and recycled.

14: TRANSPORT INFORMATION

This product is **not** classified as dangerous for transport.

15: REGULATORY INFORMATION

Hazard Label Data:

This product is **not** classified as dangerous for supply.

Safety Phrases:

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with plenty

of water and seek medical advice.

16: OTHER INFORMATION

Issue Date: 21/10/2013 Revised Date:

Disclaimer: The information contained herein is derived from the best available sources and is

believed to be accurate. However, no guarantee is expressed or implied regarding

the accuracy of the data given in the use of this product.

Issue No.: 01 Rev. No.: 00 Setseal C - Liquid Page 4 of 4