

# Setseal CR300

Highly concentrated water based paraffin dispersion concrete curing compound



## Description

Setseal CR300 is a high solids water based wax emulsion curing compound formulated from selected materials to form a low viscosity curing compound with outstanding moisture retention characteristics.

Setseal CR300 is supplied as clear and white pigmented colours, the clear colour is a white liquid, which forms a wet white film when applied to concrete surfaces, this dries to form a transparent film. The white pigment colour is a white milky liquid, which forms a white film after drying and reflect 65 - 80% of the sunlight providing the recommended coverage has been maintained.

## Applications

Setseal CR300 is used mainly for newly cast concrete and cementitious surfaces to retain sufficient moisture to ensure full hydration of the cement. Typical application areas include:

- ▲ Runways and roads.
- ▲ Roof decks.
- ▲ Retaining walls.
- ▲ Irrigation canals.
- ▲ Concrete floors.
- ▲ Concrete tanks.

## Advantages

- ▲ Helps achieving concrete desired strengths.
- ▲ Minimizes potential surface cracking and shrinkage.
- ▲ Promotes a harder dust free surface.
- ▲ Single component.
- ▲ Can be spray applied to reduce labor cost.

## Standards

Setseal CR300 complies with the following standards:

- ▲ CRD-C 300-90 Specifications for Membrane-Forming Compounds for Curing Concrete.
- ▲ AASHTO M148 and ASTM C309, Type I & II, Class A.
- ▲ Setseal CR300 is suitable for use in contact with potable water when tested in accordance to BS 6920.

## Technical Properties:

Specific gravity:	1.01 ± 0.02
Viscosity:	110 ± 20 cP
Moisture loss: CRD-C 302	≤ 0.030 g/cm <sup>2</sup> (@ 5 m <sup>2</sup> /ltr)
VOC:	≤ 15 g/ltr

## Method of Use

Setseal CR300 should be spray applied as soon as possible to the fresh concrete, provided that the surface water has evaporated. Do not apply if bleed water is forming, or is present on the concrete surface.

Stir Setseal CR300 well before use to ensure even pigment dispersion. Setseal CR300 should be spray applied, the spray nozzle should be held approximately 450 mm from the concrete surface and passed back and forth to ensure complete coverage. Pump pressure should be maintained to give an even, fine spray.

The applied film should be protected from rain for at least 3 hours; care should be taken to ensure that the film is not broken.

In case of formed concrete, Setseal CR300 should be applied immediately after de-shuttering. In such a case the concrete surface must be dampened with clean water prior application of Setseal CR300.

Dry surfaces may prevent correct film formation and cause absorption of the Setseal CR300 into the concrete surface, which may lead to staining and difficulty in later degradation and removal.

## Remarks

- ▲ It is important that the complete removal of the Setseal CR300 is ensured prior to the application of any surface finishes or additional surface treatments.
- ▲ Setseal CR300 can be removed by using high pressure steam, water jetting or light sand blasting.
- ▲ It is recommended to use Setseal A/AW where the concrete is to receive a coating or further surface treatment.
- ▲ Setseal CR300 minimum application temperature is 5°C.

# Setseal CR300

## Cleaning

Tools and equipment can be cleaned with soaped water when wet. Dried Setseal CR300 should be removed with DCP Solvent.

## Packaging

Setseal CR300 is available in 25 litre pails and 200 litre drums.

## Coverage

The recommended coverage rate is 4 - 5 m<sup>2</sup>/litre.

## Storage

Store in a dry area out of direct sunlight between 5°C and 35°C.

## Shelf Life

Setseal CR300 has a shelf life of 12 months from date of manufacture for the clear version, and 9 months for the pigmented, if stored in proper conditions in un-opened drums.

If these conditions are exceeded, DCP Technical Department should be contacted for advise.

## Cautions

### Health and Safety

Setseal CR300 is not classified as hazardous material. In case of accidental splashes to the eyes, rinse with clean water and seek medical advise. Suitable protective gloves and goggles should be worn.

For further information refer to the Material Safety Data Sheet.

## Fire

Setseal CR300 is nonflammable. DCP Solvent is flammable. Ensure adequate ventilation. Do not use near a naked flame and do not smoke during use.

*Flash Point:*  
DCP Solvent: 37°C.

## from Don Construction Products

A wide range of construction chemical products are manufactured by DCP which include:

- ▲ Concrete admixtures.
- ▲ Surface treatments
- ▲ Grouts and anchors.
- ▲ Concrete repair.
- ▲ Flooring systems.
- ▲ Protective coatings.
- ▲ Sealants.
- ▲ Waterproofing.
- ▲ Adhesives.
- ▲ Tile adhesives and grouts.
- ▲ Building products.
- ▲ Structural strengthening.



### Note:

We endeavor to ensure that any advice, recommendation or information we may give in product literature is accurate and correct. However, due to the fact that we have no direct or continuous control over where or how the products are applied, DCP cannot accept any liability either directly or indirectly arising from the use of DCP products, whether or not in accordance with any advice, specification, recommendation or information given by us.

