

Setseal CR300

Highly concentrated water based paraffin dispersion concrete curing compound



Description

Setseal CR300 is a high solids water based wax emulsion curing compound formulated from selected materials to form a low viscosity curing compound with outstanding moisture retention characteristics.

Setseal CR300 is supplied as clear and white pigmented colours, the clear colour is a white liquid, which forms a wet white film when applied to concrete surfaces, this dries to form a transparent film. The white pigment colour is a white milky liquid, which forms a white film after drying and reflect 65 - 80% of the sunlight providing the recommended coverage has been maintained.

Applications

Setseal CR300 is used mainly for newly cast concrete and cementitious surfaces, especially in exterior projects, to retain sufficient moisture and ensure full hydration of the cement. Typical application areas include:

- ▲ Runways and roads.
- ▲ Roof decks.
- ▲ Retaining walls.
- ▲ Irrigation canals.
- ▲ Concrete floors.
- ▲ Concrete tanks.

Advantages

- ▲ Helps achieving concrete desired strengths.
- ▲ Minimizes potential surface cracking and shrinkage.
- ▲ Promotes a harder dust free surface.
- ▲ Single component.
- ▲ Can be spray applied to reduce labor cost.

Standards

Setseal CR300 complies with the following standards:

- ▲ CRD-C 300-90 Specifications for Membrane-Forming Compounds for Curing Concrete.
- ▲ AASHTO M148 and ASTM C309, Type I & II, Class A.

Technical Properties:

| | |
|-----------------------------|--|
| Specific gravity: | 1.01 ± 0.02 |
| Viscosity: | 110 ± 20 cP |
| Moisture loss: CRD-C 302 | ≤ 0.030 g/cm ³ @ 204 sq ft./gal (5m ² /ltr) |
| VOC: | ≤ 15 g/ltr |

Method of Use

Setseal CR300 should be spray applied as soon as possible to the fresh concrete, provided that the surface water has evaporated. Do not apply if bleed water is forming, or is present on the concrete surface.

Stir Setseal CR300 well before use to ensure even pigment dispersion. Setseal CR300 should be spray applied, the spray nozzle should be held approximately 18" (457 mm) from the concrete surface and passed back and forth to ensure complete coverage. Pump pressure should be maintained to give an even, fine spray.

The applied film should be protected from rain for at least 3 hours; care should be taken to ensure that the film is not broken. In case of formed concrete, Setseal CR300 should be applied immediately after de-shuttering. In such a case the concrete surface must be dampened with clean water prior application of Setseal CR300.

Dry surfaces may prevent correct film formation and cause absorption of the Setseal CR300 into the concrete surface, which may lead to staining and difficultly in later degradation and removal.

Remarks

- ▲ It is important that the complete removal of the Setseal CR300 is ensured prior to the application of any surface finishes or additional surface treatments.
- ▲ Setseal CR300 can be removed by using high pressure steam, water jetting or light sand blasting.
- ▲ It is recommended to use Setseal A/AW where the concrete is to receive a coating or further surface treatment.
- ▲ Setseal CR300 minimum application temperature is 41°F (5°C).

Setseal CR300

Cleaning

Tools and equipment can be cleaned with soaped water when wet. Dried Setseal CR300 should be removed with DCP Solvent.

Packaging

Setseal CR300 is available in 5 gal (18.9 litre pails), 55 gal (208.2 litre drums) and 275 gal (1041 litre totes).

Coverage

The recommended coverage rate is 200 ft²/ gal (4.9m²/ litre).

Storage

Store in a dry area out of direct sunlight between 41°F and 95°F (5°C and 35°C).

Shelf Life

Setseal CR300 has a shelf life of 12 months from date of manufacture for the clear version, and 9 months for the pigmented, if stored in proper conditions in un-opened drums.

If these conditions are exceeded, DCP Technical Department should be contacted for advise.

Cautions

Health and Safety

Setseal CR300 is not classified as hazardous material. In case of accidental splashes to the eyes, rinse with clean water and seek medical advise. Suitable protective gloves and goggles should be worn.

For further information refer to the Material Safety Data Sheet.

Fire

Setseal CR300 is nonflammable. DCP Solvent is flammable. Ensure adequate ventilation. Do not use near a naked flame and do not smoke during use.

Flash Point:

DCP Solvent: 99°F (37°C).

from Don Construction Products

A wide range of construction chemical products are manufactured by DCP which include:

- ▲ Concrete admixtures.
- ▲ Surface treatments
- ▲ Grouts and anchors.
- ▲ Concrete repair.
- ▲ Flooring systems.
- ▲ Protective coatings.
- ▲ Sealants.
- ▲ Waterproofing.
- ▲ Adhesives.
- ▲ Tile adhesives and grouts.
- ▲ Building products.
- ▲ Structural strengthening.

Don Construction Products Inc.
2826 Lineberger Industrial Dr.
Lancaster, SC 2970
USA



Note:

We endeavour to ensure that any information, advice or recommendation we may give in product literature is accurate and correct. However, because we have no control over where and how products are applied, we cannot accept any liability arising from the use of the products.

