

Material SAFETY DATA SHEET Setseal FLX Plus - Liquid

1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Setseal FLX Plus - Liquid

Description: Liquid component of two parts elastomeric cementitious coating

Manufacturer: Ayla Construction Chemicals

P.O. Box 1117, Amman 11118 Jordan

Tel. + 962 6 5338891 Fax: + 962 6 5338829

www.dcp-int.com

Date Prepared: 24.07.14

MSDS Number: DCP/08/02/47-L

2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition: Acrylic copolymer, water.

Hazardous Ingredient(s): None of the ingredients of this product are classified as hazardous.

Refer to Section 8 for Occupational Exposure Limits.

3: HAZARDS IDENTIFICATION

No significant hazard.

4: FIRST AID MEASURES

Eyes: Irrigate immediately with copious quantities of water for 15 minutes.

Obtain medical attention if irritation persists.

Skin: Wash thoroughly with soap and water or suitable skin cleanser as soon as

possible.

Inhalation: Remove from exposure – unlikely to occur.

Ingestion: Wash out mouth with water. Don't induce vomiting. Obtain medical

attention.

5: FIRE FIGHTING MEASURES

Flash Point: None.

Special Exposure Hazards: Material can splatter above 100°C. Polymer film can burn. Irritant fumes.

Extinguishing Media: Carbon dioxide, powder, foam or water fog – Do not use water jets.

Personal Protective Equipment: Self-contained breathing apparatus.

Issue No.: 01 **Rev. No.:** 00 Setseal FLX Plus - Liquid **Page** 1 of 4



6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Wear suitable protective clothing, gloves and eye/face protection.

Environmental Precautions: Prevent entry into drains, sewers and water courses.

Decontamination Procedures: Soak up with inert absorbent or container and remove by best available

means. Gather into containers.

7: **HANDLING AND STORAGE**

Handling: Avoid skin and eye contact.

Storage: Store in cool and dry area. Protect from frost.

EXPOSURE CONTROLS AND PERSONAL PROTECTION 8:

Ingestion: Prevent eating, drinking or smoking in the area of product use.

Eye Contact: Safety glasses/goggles.

Skin Contact: Impervious gloves (e.g. PVC).

Respiratory Protection: In case of insufficient ventilation wear suitable equipment. Change

contaminated clothing and clean before re-use.

Engineering Controls: No specific ventilation requirement noted.

None

Exposure Guidelines: None assigned.

9: PHYSICAL AND CHEMICAL PROPERTIES

Form: Liquid Colour: White Odour: Acrylic pH (concentrate): 7 - 9Boiling Point (°C): 100°C Flash Point (closed cup) (°C):

Autoflammability (°C): Not determined

Explosive Properties (%): Not known Vapor Pressure (KPa @20°C): 2.3 (water)

Relative Density (@25°C): 1.025

Water Solubility: Emulsifiable

00 Issue No.: 01 Rev. No.: Setseal FLX Plus - Liquid 2 of 4 Page



10: STABILITY AND REACTIVITY

Stability: Stable.

Conditions to Avoid: Temperature below 2°C.

Chemical Incompatibility: None known.

Hazardous Decomposition Products: Thermal decomposition may yield acrylic monomers.

11: TOXICOLOGICAL INFORMATION

The following toxicological assessment is based on knowledge of the toxicity of the product's components. Expected oral LD50, rat > 2000 mg/kg.

Health Effects

On Eyes: May cause transient irritation.

On Skin: Unlikely to irritate on brief occasional exposure.

By Inhalation: Low volatility makes inhalation unlikely at ambient temperatures.

By Ingestion: Low order of acute toxicity. May cause irritation of mouth, throat and

digestive tract.

12: ECOLOGICAL INFORMATION

Environmental Assessment: When used and disposed off as intended, no adverse environmental

effects are foreseen.

Mobility: Mobile liquid. Emulsifiable in water.

Degradability: Inherently biodegradable.

Bioaccumulation: Not expected to be bioaccumulative.

Acute Fish Toxicity: Not expected to be ecotoxic to fish/ daphnia/ algae.

13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

Unused Product: Dispose off in an approved manner. Do not empty into drains, sewers or

water courses.

Used/ Contaminated Product: As for unused product.

Packaging: May be steam cleaned and recycled.

14: TRANSPORT INFORMATION

This product is **not** classified as dangerous for transport.

Issue No.: 01 **Rev. No.:** 00 Setseal FLX Plus - Liquid **Page** 3 of 4



15: REGULATORY INFORMATION

Hazard Label Data:

This product is **not** classified as dangerous for supply.

Safety Phrases:

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with

plenty of water and seek medical advice.

16: OTHER INFORMATION

Issue Date: 24/07/2014 Revised Date:

Disclaimer: The information contained herein is derived from the best available sources and is

believed to be accurate. However, no guarantee is expressed or implied regarding

the accuracy of the data given in the use of this product.

Issue No.: 01 **Rev. No.:** 00 Setseal FLX Plus - Liquid **Page** 4 of 4