

# Setseal® Mulch Glue Xtreme

High performance, ultra concentrated mulch glue for landscapes



## DESCRIPTION

Setseal Mulch Glue Xtreme is a water-based emulsion, specifically designed to bind mulches and gravels, reduce washout and prevent erosion.

Setseal Mulch Glue Xtreme imparts remarkable stabilization, simplifying the process of clearing leaves and debris and ensuring that mulch remains securely in place. It comes ready to use, non-toxic and environmentally sound.

## APPLICATIONS

Setseal Mulch Glue Xtreme is designed for spray application to stabilize landscaping materials. This product works well with both fine materials (shredded mulch, pine straw, small pea gravel) and coarse materials (rubber mulch, large bark, large gravel).

Typical application areas include:

- » Driveways and pathways.
- » Sloped landscapes.
- » Gardens and flower beds.
- » Around trees and plants.

## ADVANTAGES

- » Ready to use.
- » Environmentally friendly.
- » Fast setting, completely set within 6 - 24 hr.
- » Effective for up to 24 months.
- » Low maintenance.
- » UV resistant.
- » Simple, easy and fast application.
- » Non- toxic and pet friendly.
- » Suitable for a variety of mulch types.

## METHOD OF USE

### SURFACE PREPARATION

Before applying Setseal Mulch Glue Xtreme, protect walls and any other areas not intended for application. Ensure the surface is dry to maximize adherence. Avoid application if rain is expected within the next 24 hours. For optimal performance, apply the product in temperatures of 50°F (10°C) or above.

## TECHNICAL PROPERTIES @ 73°F (23°C):

Color:	Milky white, colorless when cured
Density:	1.05 g/ml
Overcoating time:	1 - 2 hr
Full cure:	3 - 7 days
VOC:	≤ 20 g/ltr

## APPLICATION

Setseal Mulch Glue Xtreme should be diluted using the rates in the following table. After adding relevant parts of water and Setseal Mulch Glue Xtreme, mix well before use to address any potential settling. For uniform coverage, spray in broad, even strokes, applying the product generously across the mulch areas.

Parts Water (2 parts by weight)	Parts Mulch Glue Xtreme (1 part by weight)
1/2 gal	32 oz.
1 gal	64 oz.
2 gal	128 oz.

## CLEANING

All tools should be washed and cleaned immediately after use with clean water. Hardened material can only be removed mechanically.

## PACKAGING

Setseal Mulch Glue Xtreme is available in 32 fl oz., 64 fl oz. and 1 gal jugs.



# Setseal® Mulch Glue Xtreme

## CONSUMPTION

The following table outlines the estimated consumption rates for each specified area. Actual coverage may vary depending on surface texture, porosity, application method, and environmental conditions.

	Coverage rate (for diluted material)	Square feet (per coat)
<b>Mulch or Pea Gravel</b> (apply 2 coats)	1 gal	200 sq ft.
<b>Rubber Mulch or Large Mulch</b> (apply 2 - 3 coats)	1 gal	200 sq ft.
<b>Pine Straw</b> (apply 1 coat)	1 gal	250 sq ft.

## STORAGE

Store in a dry area and away from direct sunlight. Do not allow the product to freeze.

## SHELF LIFE

Setseal Mulch Glue Xtreme has a shelf life of 12 months from date of manufacture if stored in proper conditions and unopened packs. The effectiveness of this product may be adversely affected.

If these conditions are exceeded, contact DCP Technical Department for advice.

## CAUTIONS

## HEALTH AND SAFETY

Setseal Mulch Glue Xtreme is classified as a hazardous material. In case of accidental splashes to the eyes, immediately flush with plenty of water and seek medical attention. Suitable protective gloves and goggles should be worn.

For further information, refer to the Material Safety Data Sheet.

## FIRE

Setseal Mulch Glue Xtreme is water based and nonflammable.

## WARRANTY

Unless expressly stated otherwise in the Sales Documents, the Limited Warranty shall expire on the expiry date listed on the Product's label or packaging. The full text of DCP's limited warranty is found in DCP's standard terms and conditions of sale (the "Terms"), which are available at [DCP Website/USA – Terms & Conditions](#). DCP's limited warranty is in all cases subject to, and conditioned upon, the Terms.

## MORE FROM DON CONSTRUCTION PRODUCTS

A wide range of construction chemical products are manufactured by DCP which include:

- » Concrete admixtures.
- » Surface treatments
- » Grouts and anchors.
- » Concrete repair.
- » Flooring systems.
- » Protective coatings.
- » Sealants.
- » Waterproofing.
- » Adhesives.
- » Tile adhesives and grouts.
- » Building products.
- » Structural strengthening.

## Don Construction Products Inc.

Lancaster, SC 2970, USA

[info.usa@dcp-int.com](mailto:info.usa@dcp-int.com)

[www.dcp-int.com](http://www.dcp-int.com)

### Note:

We endeavour to ensure that any information, advice or recommendation we may give in product literature is accurate and correct. However, because we have no control over where and how products are applied, we cannot accept any liability arising from the use of the products.

[www.dcp-int.com](http://www.dcp-int.com)

DCP Building Excellence

02-0052-US-A-2025