

Material SAFETY DATA SHEET Strongcoat Conductive Basecoat - Hardener

1: PRODUCT AND COMPANY IDENTIFICATION

Product Name:	Strongcoat Conductive Basecoat- Hardener			
Description:	Hardener component of water dispe	ersed epoxy coating		
Manufacturer:	Don Construction Products			
	P.O. Box 24839, Doha, Qatar			
	Tel. + 974 4 411 4004	Fax: + 974 4 411 40	14	
	www.dcp-int.com			
Date:	07.11.2023	MSDS Number:	DCP/05/04/12-H	

2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition:	Epoxy curing agent, water and fillers.			
Hazardous Ingredient(s)	Symbol	Risk Phrases	CAS No.	%
Polyaminoamide	Xi, N	R38, 41, 51/53		< 20

Refer to Section 8 for Occupational Exposure Limits.

HAZADDS IDENTIFICATION

2.

3: HAZARDS IDENTIFICAT			
Hazard Information:	Irritating to skin. Risk of serious damage to the eyes. Toxic to aquatic organisms, may cause long-term adverse in the aquatic environment.		
Classification:	Xi, N. R38, 41, 51/53		
4: FIRST AID MEASURES			
Eyes:	Irrigate immediately with copious quantities of water for 15 minutes. Obtain medical attention immediately.		
Skin:	Wash immediately with soap and water or suitable skin cleanser. Remove contaminated clothes and shoes. Obtain medical advice if irritation persists.		
Inhalation:	Remove from exposure, obtain medical attention if respiratory irritation develops or if breathing becomes difficult.		
Ingestion:	Drink plenty of water. Do not induce vomiting. Obtain medical attention. Beware of aspiration if vomiting occurs.		
Issue No.: 01 Rev. No.:	00 Strongcoat Conductive Basecoat – Page 1 of 5 Hardener		



5: FIRE FIGHTING MEASURES

Flash Point (Closed Cup):	> 100°C.
Extinguishing Media:	Carbon dioxide, powder, foam or water.
Personal Protective Equipment:	Self-contained breathing apparatus. Standard aluminized suit.
Special Exposure Hazards:	Carbon oxides, nitrogen oxides, ammonia and organic acid vapors.

6: ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Wear suitable protective clothing, gloves and eye/face protection.	
Environmental Precautions:	Prevent entry into drains, sewers and water courses.	
	Soak up with inert absorbent like sand. Gather into labeled containers. Dispose off as applicable regulations.	

7: HANDLING AND STORAGE

Handling:Maintain good standards of personal hygiene. Avoid skin and eye contact.
Do not eat, drink or smoke whilst using this product. Ensure adequate
ventilation.Storage:Keep container tightly closed in a cool dry area. Keep away from food
containers.

8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Eye Protection:	Tightly sealed safety glasses/goggles.		
Skin Protection:	Impervious gloves (e.g. PVC). Suitable protective clothing.		
Respiratory Protection:	Breathing filters apparatus.		
Hygiene Measures:	Change contaminated clothing and clean before re-use.		
Engineering Controls:	Use only in well ventilated area. Local exhaust ventilation is recommended.		
Exposure Guidelines:	None assigned.		



9: PHYSICAL AND CHEMICAL PROPERTIES

Form:	Thixotropic liquid
Colour:	Black
Odour:	Ammoniacal
pH (concentrate):	Alkaline
Boiling Point (°C):	> 100
Flash Point (closed cup) (°C):	> 100
Autoflammability (°C):	Autoignition temperature >150
Relative Density (@25°C):	1.00 - 1.10
Water Solubility:	Dispersible

10: STABILITY AND REACTIVITY

Stability:	Stable if used as directed.
Conditions to Avoid:	Any source of ignition. Temperature below 0°C.
Chemical Incompatibility:	Strong acids. Strong alkalis. Strong oxidizing agents.
Hazardous Decomposition Products:	Thermal decomposition yield oxides of carbon, nitrogen compounds.

11: TOXICOLOGICAL INFORMATION

The following toxicological assessment is based on knowledge of the toxicity of the product's components. Expected oral LD50, rat > 5000 mg/kg. Classified as skin sensitizer.

Health Effects

On Eyes:	Severe irritation.
On Skin:	Irritation.
By Inhalation:	No Data.
By Ingestion:	May cause irritation of mouth, throat and digestive tract.
Chronic:	Repeated and prolonged skin contact will result in severe irritation.

12: ECOLOGICAL INFORMATION

Environmental Assessment:	When used and disposed as intended, no adverse environmental effects are foreseen.		
Mobility:	Mobile liquid. Insoluble in water.		
Degradability:	Not readily biodegradable.		
Bioaccumulation:	Not Known.		
Acute Fish Toxicity:	Not Known.		
Issue No.: 01 Rev. No.:	00 Strongcoat Conductive Basecoat – Page 3 of 5 Hardener		



13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

Unused Product:	Classified as a special waste. May be reacted with base component to give an inert polymeric material.
Used/ Contaminated Product:	Classified as a special waste. Dispose off through an authorized waste contractor to a licensed site.
Packaging:	Must be disposed off through an authorized waste contractor.

14: TRANSPORT INFORMATION



UN Number:

3082

Transport Name:

Environmentally Hazardous substance, liquid n.o.s

Transport Type:		Class:	Pack Group:	Marine Pollutant
At Sea	IMO	Not dangerous		No
Air Transport	IATA/ICAO	Not dangerous		
At land	RID/ADR	9	III	

Issue No.:	01	Rev. No.:	00	Strongcoat Conductive Basecoat – Pa	ge	4 of 5
				Hardener		



15: REGULATORY INFORMATION

Hazard Label Data:	Xi	N Dangerous for
		the environment
UN Number:	3082	
Risk Phrases:	R38	Irritating to skin.
	R41	Risk of serious damage to the eyes.
	R51/53	Toxic to aquatic organisms, may cause long-term adverse in the aquatic environment.
Safety Phrases:		
	S24/25	Avoid contact with skin and eyes.
	S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
	S37/38/39	Wear suitable protective clothing, gloves and eye/face protection.

16: OTHER INFORMATION

Disclaimer:

The information contained herein is derived from the best available sources and is believed to be accurate. However, no guarantee is expressed or implied regarding the accuracy of the data given in the use of this product.