

Material SAFETY DATA SHEET Strongcoat Conductive Topcoat - Hardener

1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Strongcoat Conductive Topcoat - Hardener

Description: Hardener component of conductive epoxy flooring system

Manufacturer: **Don Construction Chemicals India LTD**

Tel. +914426185340/41/429

www.dcp-int.com

Date Prepared: 22.10.2013

MSDS Number: DCP-IND/05/04-H

2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition: Epoxy curing agent, diluent and solvent.

Hazardous Ingredient(s) Risk Phrases CAS No. % Symbol C, Xn R21/22, 34, 43, 52/53 30 - 40 Epoxy curing agent 2855-13-2 **Epoxy Diluent** 25 - 35 R20/22 100-51-6 Xn 64742-95-6 Solvent R10 5 - 7

Refer to Section 8 for Occupational Exposure Limits.

3: HAZARDS IDENTIFICATION

Hazard Information: Flammable.

Harmful by inhalation, in contact with skin and if swallowed.

Causes burns.

May cause sensitization by skin contact.

Harmful to aquatic organism, may cause long-term affects in the aquatic

environment.

Classification: C, F, R10, 20/21/22, 34, 43, 52/53

Issue No.: 01 **Rev. No.:** 00 Strongcoat Conductive Topcoat – **Page** 1 of 6 Hardener



4: FIRST AID MEASURES

Eyes: Irrigate immediately with copious quantities of water for 15 minutes.

Obtain medical attention immediately.

Skin: Wash immediately with soap and water or suitable skin cleanser. Remove

contaminated clothes and shoes. Obtain medical advice if irritation

persists.

Inhalation: Remove from exposure; obtain medical attention if respiratory irritation

develops or if breathing becomes difficult.

Ingestion: Drink plenty of water. Do not induce vomiting. Obtain medical attention.

Beware of aspiration if vomiting occurs.

5: FIRE FIGHTING MEASURES

Flash Point (Closed Cup): 23°C

Extinguishing Media: Carbon dioxide, powder, foam or water.

Personal Protective Equipment: Self-contained breathing apparatus. Standard aluminized suit.

Special Exposure Hazards: Toxic fumes. Nitrogen compounds.

6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Immediately issue NO SMOKING and NO NAKED FLAMES warnings. Wear

suitable protective clothing, gloves and eye/face protection.

Environmental Precautions: Prevent entry into drains, sewers and water courses.

Decontamination Procedures: Soak up with inert absorbent like sand. Gather into labeled containers.

Dispose off as applicable regulations.

7: HANDLING AND STORAGE

Handling: Maintain good standards of personal hygiene. Avoid skin and eye contact.

Do not eat, drink or smoke whilst using this product. Ensure adequate ventilation. In case of insufficient ventilation, wear suitable respiratory

equipment.

Storage: Keep container tightly closed in a cool dry area away from sources of heat

and out of direct sunlight to avoid pressure build up. Store in conformity with local fire regulations. Store away from sources of ignition. Keep away

from food containers.

Issue No.: 01 **Rev. No.:** 00 Strongcoat Conductive Topcoat – **Page** 2 of 6 Hardener



8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Eye Protection: Tightly sealed safety glasses/goggles.

Skin Protection: Impervious gloves (e.g. PVC). Suitable protective clothing.

Respiratory Protection: Breathing filters apparatus.

Hygiene Measures: Change contaminated clothing and clean before re-use.

Engineering Controls: Use only in well ventilated area. Local exhaust ventilation is

recommended.

Exposure Guidelines: None assigned.

9: PHYSICAL AND CHEMICAL PROPERTIES

Form: Liquid

Colour: Yellowish to clear
Odour: sharp Aromatic

Boiling Point (°C): > 115

Flash Point (closed cup) (°C): 23

Autoflammability (°C): Autoignition temperature > 300

Explosive Properties (%): Lower Explosive Limit (LEL): 1.0% (by volume)

Upper Explosive Limit (UEL): 11.5% (by volume)

Relative Density (@25°C): 0.95 - 1.05

Water Solubility: Partially soluble

10: STABILITY AND REACTIVITY

Stability: Contains volatile solvent. Stable if used as directed.

Conditions to Avoid: Any source of ignition. Temperature above 35°C.

Chemical Incompatibility: Strong acids. Strong alkalis. Strong oxidizing agents.

Hazardous Decomposition Products: Thermal decomposition yield oxides of carbon, nitrogen compounds.



11: TOXICOLOGICAL INFORMATION

The following toxicological assessment is based on knowledge of the toxicity of the product's components. Expected oral LD50, rat >1030 mg/kg.

Classified as skin sensitizer.

Health Effects

On Eyes: Strong caustic effect.

On Skin: Corrosive - causes burns. May cause sensitization.

By Inhalation: Harmful by inhalation. May cause respiratory irritation.

By Ingestion: Harmful if swallowed. May cause irritation of mouth, throat and digestive

tract. Ingestion of significant amounts may result in severe systemic

effects.

Chronic: Repeated and prolonged skin contact will result in severe irritation leading

to burns.

12: ECOLOGICAL INFORMATION

Environmental Assessment: When used and disposed as intended, no adverse environmental effects

are foreseen.

Mobility: Mobile liquid. Insoluble in water.

Degradability: Not readily biodegradable.

Bioaccumulation: Not Known.

Acute Fish Toxicity: Expected to be ecotoxic to fish/daphnia/algae.

13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

Unused Product: Classified as a special waste. May be reacted with base component to give

an inert polymeric material.

Used/ Contaminated Product: Classified as a special waste. Dispose off through an authorized waste

contractor to a licensed site.

Packaging: Must be disposed off through an authorized waste contractor.

Issue No.: 01 **Rev. No.:** 00 Strongcoat Conductive Topcoat – **Page** 4 of 6 Hardener



14: TRANSPORT INFORMATION



UN Number: 2924

Transport Name: Flammable liquid, corrosive, n.o.s. (xylene/isophorone diamine mixture).

Transport Type:		Class:	Pack Group:	Marine Pollutant
At Sea	IMO	3.3	III	No
Air Transport	IATA/ICAO	3	III	
At land	RID/ADR	3	III	

Issue No.: 01 **Rev. No.:** 00 Strongcoat Conductive Topcoat – **Page** 5 of 6 Hardener



15: REGULATORY INFORMATION

Hazard Label Data:



Flammable

Corrosive

Named Ingredients: Isophorone diamine.

Xylene

F

UN Number: 2924

Risk Phrases: R10 Flammable.

R20/21/22 Harmful by inhalation, in contact with skin and if

swallowed.

R34 Causes burns.

R43 May cause sensitization by skin contact.

R52/53 Harmful to aquatic organisms, may cause long-term

adverse in the aquatic environment.

Safety Phrases:

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with

plenty of water and seek medical advice.

S37/39 Wear suitable gloves and eye/face protection.

S45 In case of accident or if you feel unwell, seek medical

advice immediately (show the label where possible).

16: OTHER INFORMATION

Issue Date: 22/10/2013 Revised Date:

Disclaimer: The information contained herein is derived from the best available sources and is

believed to be accurate. However, no guarantee is expressed or implied regarding

the accuracy of the data given in the use of this product.

Issue No.: 01 **Rev. No.:** 00 Strongcoat Conductive Topcoat – **Page** 6 of 6 Hardener