



# Material SAFETY DATA SHEET

## Strongcoat EU500 - Hardener

### 1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: **Strongcoat EU500 - Hardener**

Description: Hardener component of three part high strength self-smoothing epoxy underlay

Manufacturer: **Don Construction Chemicals India LTD**  
Tel. +914426185340/41/42  
[www.dcp-int.com](http://www.dcp-int.com)

Date Prepared: 13.10.14

MSDS Number: DCP-IND/05/04-H

### 2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition: Epoxy resin hardening agent epoxy resin.

Hazardous Ingredient(s)	Symbol	Risk Phrases	CAS No.	%
Light aromatic solvent naphtha 3-aminomethyl-	F, Xn	R10a, 36/37/38	64742-95-6	20 – 35
3,5,5-trimethylcyclohexylamine	Xn, C	R21/22, 34, 43, 52/53	2855-13-2	15 – 25
Polyamide resin	Xi	R36/38, 43, 52/53	-	15 – 25
2,4,6-tris(dimethylaminomethyl)phenol	Xn, Xi	R22, 36/38	90-72-2	15 – 25
Methylene dianiline	Xn, T, N	R23/24/25, 43, 52/53	101-77-9	< 10

Refer to Section 8 for Occupational Exposure Limits.

### 3: HAZARDS IDENTIFICATION

Hazard Information: Flammable.  
Toxic by inhalation, in contact with skin and if swallowed.  
Causes burns.  
Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Classification: T, F, C. R10, 23/24/25, 34, 52/53.



#### 4: FIRST AID MEASURES

Eyes:	Irrigate immediately with copious quantities of water for 15 minutes, Eyelids should be held away from the eyeball to ensure thorough rinsing. Obtain medical attention if irritation persists.
Skin:	Wash thoroughly with soap and water or suitable skin cleanser as soon as possible. Remove contaminated clothing. Obtain medical advice if skin disorder develops.
Inhalation:	Move to fresh air. Obtain medical attention if needed.
Ingestion:	Immediately give plenty of water (if possible charcoal slurry). If a person vomits when lying on his back, place him in a recovery position. Do not induce vomiting. Obtain medical advice.

#### 5: FIRE FIGHTING MEASURES

Flash Point:	> 40 °C.
Special Exposure Hazards:	Formation of toxic gases is possible during heating or in case of fire.
Extinguishing Media:	CO <sub>2</sub> , extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.
Personal Protective Equipment:	Wear protective clothing and use self-contained breathing apparatus.

#### 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Put on adequate protective equipment.
Environmental Precautions:	Keep away from drains, surface-water, ground-water and soil.
Decontamination Procedures:	Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Disposal according to local regulations.

#### 7: HANDLING AND STORAGE

Handling:	Do not breathe vapour. Avoid contact with skin and eyes.
Storage:	Keep in a dry cool ventilated place. Direct sunshine should be avoided. Keep away from ignition sources – No smoking. Keep container tightly closed. Keep away from food, drinks and animal food.



## 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ingestion:	Prevent eating, drinking or smoking in the area of product use.
Eye Contact:	Safety glasses or chemical goggles.
Skin Contact:	Impervious gloves (e.g. PVC).
Inhalation:	When mist occurs during spraying operations, wear suitable respiratory protective equipment.
Respiratory Protection:	In case of insufficient ventilation, wear suitable equipment.
Engineering Controls:	Use only in well ventilated areas. Local exhaust ventilation is recommended.

## 9: PHYSICAL AND CHEMICAL PROPERTIES

Form:	Viscous liquid
Colour:	Brown
Odour:	Amine like
Flash Point (closed cup) (°C):	> 40
Boiling Point (°C):	Not applicable
Explosive Properties (%):	Not applicable
Freezing Point (°C):	Not applicable
Relative Density (@25°C):	1.75 – 1.85
Water Solubility:	Insoluble

## 10: STABILITY AND REACTIVITY

Stability:	Stable.
Conditions to Avoid:	Excessive heating. Direct sunshine should be avoided. Electric discharge.
Chemical Incompatibility:	Strong acid, strong base, strong oxidizer and amines.
Hazardous Decomposition Products:	Formation of toxic gases is possible during heating or in case of fire.



## 11: TOXICOLOGICAL INFORMATION

The following toxicological assessment is based on knowledge of the toxicity of the product's components.  
Expected oral LD50, rat > 100 mg/kg.

### Health Effects

On Eyes:	Strong caustic effect.
On Skin:	Caustic effect on skin and mucous membranes.
By Inhalation:	Irritant.
By Ingestion:	Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.
Chronic:	Not applicable.

## 12: ECOLOGICAL INFORMATION

Environmental Assessment:	When used and disposed off as intended, no adverse environmental effects are foreseen.
Mobility:	Not applicable.
Degradability:	Not applicable
Bioaccumulation:	Not applicable.
Acute Fish Toxicity:	Very toxic for aquatic organisms.

## 13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

Unused Product:	Dispose off through an authorized waste contractor to a licensed site.
Used/ Contaminated Product:	As for unused product.
Packaging:	May be steam cleaned and recycled.

## 14: TRANSPORT INFORMATION




UN Number: 1263

Transport Name: Paint, 3, PG III, Flammable liquid.

Transport Type:		Class:	Pack Group:	Marine Pollutant
At Sea	IMO/IMDG	3	III	No
Air Transport	IATA	3	III	
At land	RID/ADR	3	III	

## 15: REGULATORY INFORMATION

### Hazard Label Data:



### Contains:

3-aminomethyl-3,5,5-trimethylcyclohexylamine  
 2,4,6-tris(dimethylaminomethyl)phenol  
 Polyamide resin  
 Light aromatic solvent naphtha  
 Methylene dianiline

### Risk Phrases:

R10	Flammable
R23/24/25	Toxic by inhalation, in contact with skin and if swallowed.
R34	Causes burns.
R52/53	Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

### Safety Phrases:

S24/25	Avoid contact with skin and eyes.
S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S28	After contact with skin, wash immediately with plenty of water.
S36/37/39	Wear suitable protective clothing, gloves and eye/face protection.
S45	In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).
S57	Use appropriate container to avoid environmental contamination.
S60	This material and its container must be disposed of as hazardous waste.

## 16: OTHER INFORMATION

Issue Date: 13/10/2014

Revised Date:

### Disclaimer:

The information contained herein is derived from the best available sources and is believed to be accurate. However, no guarantee is expressed or implied regarding the accuracy of the data given in the use of this product.