

Material SAFETY DATA SHEET Strongcoat Epoxy - Base

1: PRODUCT AND COMPANY IDENTIFICATION

Product Name:	Strongcoat Epoxy - Base	
Description:	Base component of high build epoxy	coating system
Manufacturer:	DCP Saudi Co	
	P.O. Box 66241, Riyadh 11576 Kingo	lom of Saudi Arabia
	Tel. + 966 11 4612003	Fax: + 966 11 2792059
	www.dcp-int.com	
Date Prepared:	10.11.2021	
MSDS Number:	DCP/06/03/46-B	

2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition:	Epoxy resin, epoxy diluent, pigment.			
Hazardous Ingredient(s)	Symbol	Risk Phrases	CAS No.	%
Epoxy resin (Number average molecular weight < 700)	Xi, N	R36/38, 43, 51/53	25068-38-6	40

Refer to Section 8 for Occupational Exposure Limits.

3: HAZARDS IDENTIFICATION

Hazard Information:	Irritating to eyes and skin. May cause sensitization by skin contact. Toxic to aquatic organism, may cause long-term affects in the aquatic environment.
Classification:	Xi, N. R36/38, 43, 51/53
4: FIRST AID MEASURES	
Eyes:	Irrigate immediately with copious quantities of water for 15 minutes. Obtain medical attention urgently.
Skin:	Wash immediately with soap and water or suitable skin cleanser. Remove contaminated clothes and shoes. Obtain medical advice if skin disorders develop.
Inhalation:	Remove from exposure, obtain medical attention if respiratory irritation develops or if breathing becomes difficult.
Ingestion:	Rinse mouth thoroughly. Drink plenty of water. Do not induce vomiting. Obtain medical attention. Beware of aspiration if vomiting occurs.
Issue No.: 01 Rev. No.:	00 Strongcoat Epoxy – Base Page 1 of 5



5: FIRE FIGHTING MEASURES

Flash Point (Closed Cup):	> 200°C.
Extinguishing Media:	Carbon dioxide, powder, foam or water.
Personal Protective Equipment:	Self-contained breathing apparatus.
Special Exposure Hazards:	Toxic fumes. Carbon oxides.

6: ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Wear suitable protective clothing, gloves and eye/face protection.
Environmental Precautions:	Prevent entry into drains, sewers and water courses.
Decontamination Procedures:	Soak up with inert absorbent such as sand. Gather into labeled containers. Dispose off as applicable regulations.

7: HANDLING AND STORAGE

Handling:	Maintain good standards of personal hygiene. Avoid skin and eye contact. Do not eat, drink or smoke whilst using this product. Ensure adequate ventilation.
Storage:	Keep container tightly closed in a cool dry area.

8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Eye Protection:	Safety glasses/goggles.
Skin Protection:	Impervious gloves (e.g. PVC). Suitable protective clothing.
Respiratory Protection:	Organic chemical cartridge respirator, if needed.
Hygiene Measures:	Change contaminated clothing and clean before re-use.
Engineering Controls:	No specific ventilation requirements noted.
Exposure Guidelines:	None assigned.

Issue No.:	01	Rev. No.:	00	Strongcoat Epoxy – Base	Page 2 of 5



9: PHYSICAL AND CHEMICAL PROPERTIES

Form:	Liquid
Colour:	White/blue/grey
Odour:	Mild
pH (concentrate):	Not applicable
Boiling Point (°C):	> 200
Flash Point (closed cup) (°C):	> 200
Autoflammability (°C):	Not determined
Explosive Properties (%):	Not Known
Vapor Pressure (KPa @20°C):	0.1
Relative Density (@25°C):	1.75
Water Solubility:	Insoluble

10: STABILITY AND REACTIVITY

Stability:	Stable: reacts with compounds containing amino, hydroxyl or carboxyl groups to give stable, cross linked materials.
Conditions to Avoid:	None Known.
Chemical Incompatibility:	Strong acids. Strong alkalis. Strong oxidizing agents.
Hazardous Decomposition Products:	Thermal decomposition yield oxides of carbon, toxic fumes.

11: TOXICOLOGICAL INFORMATION

The following toxicological assessment is based on knowledge of the toxicity of the product's components. Acute Oral effect LD50 > 5000 mg/kg. Classified as moderate sensitizer.

Health Effects

On Eyes:	Slight irritation (rabbit).
On Skin:	Moderate irritation (rabbit).
By Inhalation:	May cause respiratory irritation.
By Ingestion:	May cause irritation of mouth, throat and digestive tract.
Chronic:	Repeated and prolonged skin contact may lead to skin disorders.



12: ECOLOGICAL INFORMATION

Environmental Assessment:	When used and disposed as intended, no adverse environmental effects are foreseen.
Mobility:	Viscous liquid. Insoluble in water.
Degradability:	Not readily biodegradable.
Bioaccumulation:	Not expected to be bioaccumulate.
Acute Fish Toxicity:	Ecotoxic to fish/daphnia/algae.

13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

Unused Product:	Dispose off through an authorized waste contractor to a licensed site.
Used/ Contaminated Product:	As for unused product.
Packaging:	Must be disposed off through an authorized waste contractor.

14: TRANSPORT INFORMATION



UN Number:

3082

Transport Name:

Environmentally hazardous substance, liquid n.o.s (Epoxy resin).

Transport Type:		Class:	Pack Group:	Marine Pollutant
At Sea	IMO	9	III	No
Air Transport	IATA/ICAO	9	III	
At land	RID/ADR	9	III	



15: REGULATORY INFORMATION

Hazard Label Data:	Xi Trritant	N Dangerous for the environment	
Named Ingredients:	Epoxy resin (Number average molecular weight < 700)		
UN Number:	3082		
Risk Phrases:			
	R36/38	Irritating to eyes and skin.	
	R43	May cause sensitization by skin contact.	
	R51/53	Toxic to aquatic organisms, may cause long-term adverse in the aquatic environment.	
Safety Phrases:			
	S24/25	Avoid contact with skin and eyes.	
	S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.	
	S37/39	Wear suitable gloves and eye/face protection.	
16: OTHER INFORMATION			

10.11.2021

Issue Date:

Disclaimer:

The information contained herein is derived from the best available sources and is believed to be accurate. However, no guarantee is expressed or implied regarding the accuracy of the data given in the use of this product.

Revised Date:

Issue No.:	01	Rev. No.:	00	Strongcoat Epoxy – Base	Page 5 of 5