

Material SAFETY DATA SHEET Strongcoat HR130 - Base

1: PRODUCT AND COMPANY IDENTIFICATION

Product Name:	Strongcoat HR130 - Base		
Description:	Base component of two part heat resistant epoxy coating		
Manufacturer:	Don Construction Products		
	P.O. Box 24839, Doha, Qatar		
	Tel. + 974 4 411 4004	Fax: + 974 4 411 4014	
	www.dcp-int.com		
Date Prepared:	26.05.14		
MSDS Number:	DCP/06/03/07-B		

2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition:	Modified epoxy resin, nonreactive additives, fillers and pigments.			
Hazardous Ingredient(s)	Symbol	Risk Phrases	CAS No.	%
Bisphenol-A epoxy resin Alkyl (C12-C14)glycidylether	Xi Xi, N	R36/38, 43 R36/38, 43, 51/53	25068-38-6 68609-97-2	20 – 45 < 10

Refer to Section 8 for Occupational Exposure Limits.

3: HAZARDS IDENTIFICATION

Hazard Information:	Irritating to eyes and respiratory system. May cause sensitization by skin contact. Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Classification:	Xi, N. R36/38, 43, 51/53.



4: FIRST AID MEASURES

Eyes:	Irrigate immediately with copious quantities of water for 15 minutes, Eyelids should be held away from the eyeball to ensure thorough rinsing. Obtain medical attention if irritation persists.
Skin:	Wash thoroughly with soap and water or suitable skin cleanser as soon as possible. Remove contaminated clothing. Obtain medical advice if skin disorder develops.
Inhalation:	Move to fresh air. Obtain medical attention if needed.
Ingestion:	Immediately give plenty of water (if possible charcoal slurry). If a person vomits when lying on his back, place him in a recovery position. Do not induce vomiting. Obtain medical advice.

5: FIRE FIGHTING MEASURES

Flash Point:	> 150°C.
Special Exposure Hazards:	Formation of toxic gases is possible during heating or in case of fire.
Extinguishing Media:	Foam, dry powder, carbon dioxide, water spray jet.
Personal Protective Equipment:	Wear protective clothing and use self-contained breathing apparatus.

6: ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Put on adequate protective equipment.
Environmental Precautions:	Keep away from drains, surface-water, ground-water and soil.
Decontamination Procedures:	Collect as much as possible in a container for disposal. Soak up the remainder with inert absorbent. Disposal according to local regulations.

7: HANDLING AND STORAGE

Handling:	Do not breathe vapour. Avoid contact with skin and eyes.
Storage:	Keep in a dry cool ventilated place. Direct sunshine should be avoided. Keep away from ignition sources – No smoking. Keep container tightly closed. Keep away from food, drinks and animal food.



٦

8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ingestion:	Prevent eating, drinking or smoking in the area of product use.			
Eye Contact:	Safety glasses or chemical goggles.			
Skin Contact:	Impervious gloves (e.g. PVC).			
Inhalation:	When mist occurs during spraying operations, wear suitable respiratory protective equipment.			
Respiratory Protection:	In case of insufficient ventilation, wear suitable equipment.			
Engineering Controls:	Use only in well ventilated areas. Local exhaust ventilation is recommended.			

9: PHYSICAL AND CHEMICAL PROPERTIES

Form:	Viscous liquid
Colour:	Various
Odour:	Weak
Flash Point (closed cup) (°C):	> 150
Boiling Point (°C):	Not applicable
Explosive Properties (%):	Not applicable
Freezing Point (°C):	Not applicable
Relative Density (@25°C):	1.55 – 1.65
Water Solubility:	Insoluble

10: STABILITY AND REACTIVITY

Stability:	Stable.
Conditions to Avoid:	Excessive heating. Direct sunshine should be avoided. Electric discharge.
Chemical Incompatibility:	Strong acid, strong base, strong oxidizer and amines.
Hazardous Decomposition Products:	Formation of toxic gases is possible during heating or in case of fire.

Issue No.:	01	Rev. No.:	00	Strongcoat HR130 - Base	Page 3 of 6



11: TOXICOLOGICAL INFORMATION

The following toxicological assessment is based on knowledge of the toxicity of the product's components. Expected oral LD50, rat > 3000 mg/kg.

Health Effects

On Eyes:	Irritant.
On Skin:	Irritant.
By Inhalation:	Irritant.
By Ingestion:	Irritant.
Chronic:	Not applicable.

12: ECOLOGICAL INFORMATION

Environmental Assessment:	When used and disposed off as intended, no adverse environmental effects are foreseen.
Mobility:	Not applicable.
Degradability:	Not biodegradable.
Bioaccumulation:	Not applicable.
Acute Fish Toxicity:	Toxic to aquatic organisms.

13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

Unused Product:	Dispose off through an authorized waste contractor to a licensed site.
Used/ Contaminated Product:	As for unused product.
Packaging:	May be steam cleaned and recycled.

	Issue No.:	01	Rev. No.:	00	Strongcoat HR130 - Base Page	4 of 6
--	------------	----	-----------	----	------------------------------	--------



14: TRANSPORT INFORMATION



UN/SI Number:

Transport Name:

Environmentally hazardous substance, liquid, n.o.s.

Transport Type:		Class:	Pack Group:	Item:	Marine Pollutant:
At Sea	IMO	9	111		No
Air Transport	IATA/ICAO	9	111		
At land	RID/ADR	9	111		

15: REGULATORY INFORMATION

Hazard Label Data:	Xi Trritant	N Dangerous for the environment
Contains:	Modified epoxy	resin.
Risk Phrases:		
	R36/38	Irritating to eyes and respiratory system.
	R43	May cause sensitization by skin contact.
	R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
Safety Phrases:		
	S24	Avoid contact with skin.
	S28	After contact with skin, wash immediately with plenty of water.
	S37/39	Wear suitable gloves and eye/face protection.
	S60	This material and its container must be disposed of as hazardous waste.

Issue No.: 01 Rev. No.: 00 Strongcoat HR130 - Base Page 5 of 6



16: OTHER INFORMATION

Issue Date:

te: 26/05/2014

Revised Date:

Disclaimer: The information contained herein is derived from the best available sources and is believed to be accurate. However, no guarantee is expressed or implied regarding the accuracy of the data given in the use of this product.