

Material SAFETY DATA SHEET Strongcoat Primer - Hardener

1: PRODUCT AND COMPANY IDENTIFICATION

Product Name:	Strongcoat Primer - Hardener	
Description:	Hardener component of two part epoxy primer	
Manufacturer:	DCP Saudi Co	
	P.O. Box 66241, Riyadh 11576 King	dom of Saudi Arabia
	Tel. + 966 11 4612003	Fax: + 966 11 2792059
	www.dcp-int.com	
Date Prepared:	12.06.08	
MSDS Number:	DCP/05/04/45-H	

2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition:	Epoxy resin hardening a	agent.		
Hazardous Ingredient(s)	Symbol	Risk Phrases	CAS No.	%
Polyoxypropylendiamin Nonylphenol 3-aminomethyl-	C Xn, C, N	R34 R22, 34, 62, 50/53, 63	9046-10-0 25154-52-3	25 – 50 25 – 50
3,5,5-trimethylcyclohexylamine m-phenylenebis(methylamine)	Xn, C Xn, C	R21/22, 34, 43, 52/53 R20/22, 34, 43, 52/53	2855-13-2 1477-55-0	10 – 25 10 – 25

Refer to Section 8 for Occupational Exposure Limits.

3: HAZARDS IDENTIFICATION

Hazard Information:	Harmful by inhalation, in contact with skin and if swallowed. Causes burns. May cause sensitization by skin contact. Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Possible risk of impaired fertility. Possible risk of harm to the unborn child.
Classification:	Xn, N, C. R20/21/22, 34, 43, 50/53, 62, 63.



4: FIRST AID MEASURES

Eyes:	Irrigate immediately with copious quantities of water for 15 minutes, Eyelids should be held away from the eyeball to ensure thorough rinsing. Obtain medical attention if irritation persists.
Skin:	Wash thoroughly with soap and water or suitable skin cleanser as soon as possible. Remove contaminated clothing. Obtain medical advice if skin disorder develops.
Inhalation:	Move to fresh air. Obtain medical attention if needed.
Ingestion:	Immediately give plenty of water (if possible charcoal slurry). If a person vomits when lying on his back, place him in a recovery position. Do not induce vomiting. Obtain medical advice.

5: FIRE FIGHTING MEASURES

Flash Point:	> 100°C.
Special Exposure Hazards:	Formation of toxic gases is possible during heating or in case of fire.
Extinguishing Media:	$\ensuremath{\text{CO}}_2$, extinguishing powder or water jet. Fight larger fires with water jet or alcohol-resistant foam.
Personal Protective Equipment:	Wear protective clothing and use self-contained breathing apparatus.

6: ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Put on adequate protective equipment.
Environmental Precautions:	Keep away from drains, surface-water, ground-water and soil.
Decontamination Procedures:	Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Disposal according to local regulations.

7: HANDLING AND STORAGE

Handling:	Do not breathe vapour. Avoid contact with skin and eyes.
Storage:	Keep in a dry cool ventilated place. Direct sunshine should be avoided. Keep away from ignition sources – No smoking. Keep container tightly closed. Keep away from food, drinks and animal food.



8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ingestion:	Prevent eating, drinking or smoking in the area of product use.
Eye Contact:	Safety glasses or chemical goggles.
Skin Contact:	Impervious gloves (e.g. PVC).
Inhalation:	When mist occurs during spraying operations, wear suitable respiratory protective equipment.
Respiratory Protection:	In case of insufficient ventilation, wear suitable equipment.
Engineering Controls:	Use only in well ventilated areas. Local exhaust ventilation is recommended.

9: PHYSICAL AND CHEMICAL PROPERTIES

Form:	Liquid
Colour:	Yellow
Odour:	Amine like
Flash Point (closed cup) (°C):	> 100
Boiling Point (°C):	Not applicable
Explosive Properties (%):	Not applicable
Freezing Point (°C):	Not applicable
Relative Density (@25°C):	0.96 – 1.00
Water Solubility:	Difficult to mix

10: STABILITY AND REACTIVITY

Stability:	Stable.
Conditions to Avoid:	Excessive heating. Direct sunshine should be avoided. Electric discharge.
Chemical Incompatibility:	Strong acid, strong base, strong oxidizer and amines.
Hazardous Decomposition Products:	Formation of toxic gases is possible during heating or in case of fire.

	Issue No.:	01	Rev. No.:	01	Strongcoat Primer - Hardener	Page	3 of 6
--	------------	----	-----------	----	------------------------------	------	--------



11: TOXICOLOGICAL INFORMATION

The following toxicological assessment is based on knowledge of the toxicity of the product's components. Expected oral LD50, rat > 100 mg/kg.

Health Effects

On Eyes:	Strong caustic effect.
On Skin:	Caustic effect on skin and mucous membranes.
By Inhalation:	Irritant.
By Ingestion:	Swallowing will lead to a strong caustic effect on mouth and throat and to the danger of perforation of esophagus and stomach.
Chronic:	Not applicable.

12: ECOLOGICAL INFORMATION

Environmental Assessment:	When used and disposed off as intended, no adverse environmental effects are foreseen.
Mobility:	Not applicable.
Degradability:	Not applicable.
Bioaccumulation:	Not applicable.
Acute Fish Toxicity:	Very toxic for aquatic organisms.

13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

Unused Product:	Dispose off through an authorized waste contractor to a licensed site.
Used/ Contaminated Product:	As for unused product.
Packaging:	May be steam cleaned and recycled.

Issue No.:	01	Rev. No.:	01	Strongcoat Primer - Hardener	Page	4 of 6
133ue No	01	Kev. NO	01	Strungcuat i filler - fiardener	Faye	4010



14: TRANSPORT INFORMATION



UN/SI Number:

Transport Name:

Amines, liquid, corrosive n.o.s (Polyoxypropylendiamin)

Transport Type:		Class:	Pack Group:	Item:	Marine Pollutant:
At Sea	IMO	8	П		Yes
Air Transport	IATA/ICAO	8	II		
At land	RID/ADR	8	II		

Issue No.: 01 Rev. No.: 01 Strongcoat Primer - Hardener Page 5 of							
	Issue No.:	01	Rev. No.:	01	Strongcoat Primer - Hardener	Page	5 of 6



15: REGULATORY INFORMATION

Hazard Label Data: Xn N C	
Harmful Dangerous for the environment	
Contains: Polyoxypropylendiamin Nonylphenol 3-aminomethyl-3,5,5-trimethylcyclohexylamine Methylamine	
Risk Phrases:	
R20/21/22 Harmful by inhalation, in co swallowed.	ontact with skin and if
R34 Causes burns.	
R43 May cause sensitization by skin	contact.
R50/53 Very toxic to aquatic organism adverse effects in the aquatic e	
R62 Possible risk of impaired fertility	у.
R63 Possible risk of harm to the unk	oorn child.
Safety Phrases:	
S24/25 Avoid contact with skin and eye	es.
S26 In case of contact with eyes plenty of water and seek medic	
S28 After contact with skin, wash in water.	mmediately with plenty of
S36/37/39 Wear suitable protective cloth protection.	ing, gloves and eye/face
S45 In case of accident or if you advice immediately (show the l	
S57 Use appropriate container contamination.	to avoid environmental
S60 This material and its contained hazardous waste.	r must be disposed of as
16: OTHER INFORMATION	
Logue Deter 12/0/ /2000 Deviced Date:	

Issue No.: 01	Rev. No .: 01	Strongcoat Primer - Hardener	Page 6 of 6
Disclaimer:	believed to be accurat	ined herein is derived from the best ava e. However, no guarantee is expressed ita given in the use of this product.	
Issue Date:	12/06/2008	Revised Date:	09.11.2014