

Material SAFETY DATA SHEET Strongcoat Primer - Hardener

1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Strongcoat Primer - Hardener

Description: Hardener component of two part epoxy primer

Manufacturer: Ayla for Building Materials Industry & Trade

Al-Karadeh, Arsat Al-Hindia, Baghdad

Tel.: +964 790 1488 730

www.dcp-int.com

Date Prepared: 12.06.08

MSDS Number: DCP/05/04/45-H

2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition: Epoxy resin hardening agent.

Hazardous Ingredient(s)	Symbol	Risk Phrases	CAS No.	%
Polyoxypropylendiamin	С	R34	9046-10-0	25 – 50
Nonylphenol	Xn, C, N	R22, 34, 62, 50/53, 63	25154-52-3	25 – 50
3-aminomethyl-				
3,5,5-trimethylcyclohexylamine	Xn, C	R21/22, 34, 43, 52/53	2855-13-2	10 – 25
m-phenylenebis(methylamine)	Xn, C	R20/22, 34, 43, 52/53	1477-55-0	10 – 25

Refer to Section 8 for Occupational Exposure Limits.

3: HAZARDS IDENTIFICATION

Hazard Information: Harmful by inhalation, in contact with skin and if swallowed.

Causes burns.

May cause sensitization by skin contact.

Very toxic to aquatic organisms, may cause long-term adverse effects in

the aquatic environment. Possible risk of impaired fertility.

Possible risk of harm to the unborn child.

Classification: Xn, N, C. R20/21/22, 34, 43, 50/53, 62, 63.

Issue No.: 01 Rev. No.: 01 Strongcoat Primer - Hardener Page 1 of 7



4: FIRST AID MEASURES

Eyes: Irrigate immediately with copious quantities of water for 15 minutes,

Eyelids should be held away from the eyeball to ensure thorough rinsing.

Obtain medical attention if irritation persists.

Skin: Wash thoroughly with soap and water or suitable skin cleanser as soon as

possible. Remove contaminated clothing. Obtain medical advice if skin

disorder develops.

Inhalation: Move to fresh air. Obtain medical attention if needed.

Ingestion: Immediately give plenty of water (if possible charcoal slurry). If a person

vomits when lying on his back, place him in a recovery position. Do not

induce vomiting. Obtain medical advice.

5: FIRE FIGHTING MEASURES

Flash Point: > 100°C.

Special Exposure Hazards: Formation of toxic gases is possible during heating or in case of fire.

Extinguishing Media: CO₂, extinguishing powder or water jet. Fight larger fires with water jet or

alcohol-resistant foam.

Personal Protective Equipment: Wear protective clothing and use self-contained breathing apparatus.

6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Put on adequate protective equipment.

Environmental Precautions: Keep away from drains, surface-water, ground-water and soil.

Decontamination Procedures: Absorb with liquid-binding material (sand, diatomite, acid binders,

universal binders, sawdust). Disposal according to local regulations.

7: HANDLING AND STORAGE

Handling: Do not breathe vapour. Avoid contact with skin and eyes.

Storage: Keep in a dry cool ventilated place. Direct sunshine should be avoided.

Keep away from ignition sources – No smoking.

Keep container tightly closed.

Keep away from food, drinks and animal food.

Issue No.: 01 **Rev. No.:** 01 Strongcoat Primer - Hardener **Page** 2 of 7



8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ingestion: Prevent eating, drinking or smoking in the area of product use.

Eye Contact: Safety glasses or chemical goggles.

Skin Contact: Impervious gloves (e.g. PVC).

Inhalation: When mist occurs during spraying operations, wear suitable respiratory

protective equipment.

Respiratory Protection: In case of insufficient ventilation, wear suitable equipment.

Engineering Controls: Use only in well ventilated areas. Local exhaust ventilation is

recommended.

9: PHYSICAL AND CHEMICAL PROPERTIES

Form: Liquid
Colour: Yellow
Odour: Amine like

Flash Point (closed cup) (°C): > 100

Boiling Point (°C):

Explosive Properties (%):

Not applicable

Freezing Point (°C):

Not applicable

Not applicable

Not applicable

Not applicable

Not applicable

Difficult to mix

10: STABILITY AND REACTIVITY

Stability: Stable.

Conditions to Avoid: Excessive heating. Direct sunshine should be avoided. Electric discharge.

Chemical Incompatibility: Strong acid, strong base, strong oxidizer and amines.

Hazardous Decomposition Products: Formation of toxic gases is possible during heating or in case of fire.

Issue No.: 01 **Rev. No.:** 01 Strongcoat Primer - Hardener **Page** 3 of 7



11: TOXICOLOGICAL INFORMATION

The following toxicological assessment is based on knowledge of the toxicity of the product's components. Expected oral LD50, rat > 100 mg/kg.

Health Effects

On Eyes: Strong caustic effect.

On Skin: Caustic effect on skin and mucous membranes.

By Inhalation: Irritant.

By Ingestion: Swallowing will lead to a strong caustic effect on mouth and throat and to

the danger of perforation of esophagus and stomach.

Chronic: Not applicable.

12: ECOLOGICAL INFORMATION

Environmental Assessment: When used and disposed off as intended, no adverse environmental

effects are foreseen.

Mobility: Not applicable.

Degradability: Not applicable.

Bioaccumulation: Not applicable.

Acute Fish Toxicity: Very toxic for aquatic organisms.

13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

Unused Product: Dispose off through an authorized waste contractor to a licensed site.

Used/ Contaminated Product: As for unused product.

Packaging: May be steam cleaned and recycled.

Issue No.: 01 Rev. No.: 01 Strongcoat Primer - Hardener Page 4 of 7



14: TRANSPORT INFORMATION





UN/SI Number: 2735

Transport Name: Amines, liquid, corrosive n.o.s (Polyoxypropylendiamin)

Transport Type:		Class:	Pack Group:	Item:	Marine Pollutant:
At Sea	IMO	8	П		Yes
Air Transport	IATA/ICAO	8	11		
At land	RID/ADR	8	П		



15: REGULATORY INFORMATION

Hazard Label Data:

Xn

N







Harmful

Dangerous for the environment

Corrosive

Contains:

Polyoxypropylendiamin

Nonylphenol

3-aminomethyl-3,5,5-trimethylcyclohexylamine

Methylamine

Risk Phrases:

R20/21/22 Harmful by inhalation, in contact with skin and if

swallowed.

R34 Causes burns.

R43 May cause sensitization by skin contact.

R50/53 Very toxic to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.

R62 Possible risk of impaired fertility.

R63 Possible risk of harm to the unborn child.

Safety Phrases:

S24/25 Avoid contact with skin and eyes.

S26 In case of contact with eyes, rinse immediately with

plenty of water and seek medical advice.

S28 After contact with skin, wash immediately with plenty of

water.

S36/37/39 Wear suitable protective clothing, gloves and eye/face

protection.

S45 In case of accident or if you feel unwell, seek medical

advice immediately (show the label where possible).

Use appropriate container to avoid environmental

contamination.

S60 This material and its container must be disposed of as

hazardous waste.

16: OTHER INFORMATION

Issue Date: 12/06/2008 Revised Date: 09.11.2014

Disclaimer: The information contained herein is derived from the best available sources and is

believed to be accurate. However, no guarantee is expressed or implied regarding

the accuracy of the data given in the use of this product.

Issue No.: 01 Rev. No.: 01 Strongcoat Primer - Hardener Page 6 of 7

