

Material SAFETY DATA SHEET Strongcoat Primer ML- Base

1: PRODUCT AND COMPANY IDENTIFICATION

Product Name: Strongcoat Primer ML- Base

Description: Base component of two part epoxy primer

Manufacturer: **Don Construction Products**

P.O. Box 24839, Doha, Qatar

Tel. + 974 4 411 4004 Fax: + 974 4 411 4014

www.dcp-int.com

Date Prepared: 15.12.2020

MSDS Number: DCP/05/04/70-B

2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition: Modified epoxy resin, nonreactive additives.

Hazardous Ingredient(s) Symbol Risk Phrases CAS No. % Bisphenol-A epoxy resin Xi R36/38, 43 25068-38-6 > 85 Alkyl(C₁₂-C₁₄)glycidylether Xi, N R36/38, 43, 51/53 68609-97-2 < 15

Refer to Section 8 for Occupational Exposure Limits.

3: HAZARDS IDENTIFICATION

Hazard Information: Irritating to eyes and respiratory system.

May cause sensitization by skin contact.

Toxic to aquatic organisms, may cause long-term adverse effects in the

aquatic environment.

Classification: Xi, N. R36/38, 43, 51/53.

4: FIRST AID MEASURES

Eyes: Irrigate immediately with copious quantities of water for 15 minutes,

Eyelids should be held away from the eyeball to ensure thorough rinsing.

Obtain medical attention if irritation persists.

Skin: Wash thoroughly with soap and water or suitable skin cleanser as soon as

possible. Remove contaminated clothing. Obtain medical advice if skin

disorder develops.

Inhalation: Move to fresh air. Obtain medical attention if needed.

Ingestion: Immediately give plenty of water (if possible charcoal slurry). If a person

vomits when lying on his back, place him in a recovery position. Do not

induce vomiting. Obtain medical advice.

Issue No.: 01 **Rev. No.:** 00 Strongcoat Primer ML - Base **Page** 1 of 5



5: FIRE FIGHTING MEASURES

Flash Point: > 150°C.

Special Exposure Hazards: Formation of toxic gases is possible during heating or in case of fire.

Extinguishing Media: Foam, dry powder, carbon dioxide, water spray jet.

Personal Protective Equipment: Wear protective clothing and use self-contained breathing apparatus.

6: ACCIDENTAL RELEASE MEASURES

Personal Precautions: Put on adequate protective equipment.

Environmental Precautions: Keep away from drains, surface-water, ground-water and soil.

Decontamination Procedures: Collect as much as possible in a container for disposal. Soak up the

remainder with inert absorbent. Disposal according to local regulations.

7: HANDLING AND STORAGE

Handling: Do not breathe vapour. Avoid contact with skin and eyes.

Storage: Keep in a dry cool ventilated place. Direct sunshine should be avoided.

Keep away from ignition sources – No smoking.

Keep container tightly closed.

Keep away from food, drinks and animal food.

8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Ingestion: Prevent eating, drinking or smoking in the area of product use.

Eye Contact: Safety glasses or chemical goggles.

Skin Contact: Impervious gloves (e.g. PVC).

Inhalation: When mist occurs during spraying operations, wear suitable respiratory

protective equipment.

Respiratory Protection: In case of insufficient ventilation, wear suitable equipment.

Engineering Controls: Use only in well ventilated areas. Local exhaust ventilation is

recommended.



9: PHYSICAL AND CHEMICAL PROPERTIES

Form: Liquid

Colour: Yellowish clear

Odour: Weak

Flash Point (closed cup) (°C): 75

Boiling Point ($^{\circ}$ C): Not applicable Explosive Properties ($^{\circ}$ C): Not applicable Freezing Point ($^{\circ}$ C): Not applicable Relative Density ($^{\circ}$ 25 $^{\circ}$ C): 1.10-1.20

Water Solubility: Insoluble

10: STABILITY AND REACTIVITY

Stability: Stable.

Conditions to Avoid: Excessive heating. Direct sunshine should be avoided. Electric discharge.

Chemical Incompatibility: Strong acid, strong base, strong oxidizer and amines.

Hazardous Decomposition Products: Formation of toxic gases is possible during heating or in case of fire.

11: TOXICOLOGICAL INFORMATION

The following toxicological assessment is based on knowledge of the toxicity of the product's components. Expected oral LD50, rat > 3000 mg/kg.

Health Effects

On Eyes: Irritant.
On Skin: Irritant.
By Inhalation: Irritant.
By Ingestion: Irritant.

Chronic: Not applicable.

12: ECOLOGICAL INFORMATION

Environmental Assessment: When used and disposed off as intended, no adverse environmental

effects are foreseen.

Mobility: Not applicable.

Degradability: Not biodegradable.

Bioaccumulation: Not applicable.

Acute Fish Toxicity: Toxic to aquatic organisms.

Tssue No.:	01	Rev. No.: 00	Strongcoat Primer ML - Base	Page 3 of 5
I ISSUE NO.:	U I	Rev. No.: ()()	SHOUGGAL PHINELIML - DASE	Page 5015



13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

Unused Product: Dispose off through an authorized waste contractor to a licensed site.

Used/ Contaminated Product: As for unused product.

Packaging: May be steam cleaned and recycled.

14: TRANSPORT INFORMATION



UN/SI Number: 3082

Transport Name: Environmentally hazardous substance, liquid, n.o.s.

Transport Type:		Class:	Pack Group:	Item:	Marine Pollutant:
At Sea	IMO	9	III		No
Air Transport	IATA/ICAO	9	III		
At land	RID/ADR	9	III		



15: REGULATORY INFORMATION

Hazard Label Data:

Xi



Irritant

Dangerous for the environment

Contains: Modified epoxy resin.

Risk Phrases:

R36/38 Irritating to eyes and respiratory system.
R43 May cause sensitization by skin contact.

R51/53 Toxic to aquatic organisms, may cause long-term

adverse effects in the aquatic environment.

Safety Phrases:

S24 Avoid contact with skin.

S28 After contact with skin, wash immediately with plenty of

water

S37/39 Wear suitable gloves and eye/face protection.

S60 This material and its container must be disposed of as

hazardous waste.

16: OTHER INFORMATION

Issue Date: 15.12.2020 Revised Date:

Disclaimer: The information contained herein is derived from the best available sources and is

believed to be accurate. However, no guarantee is expressed or implied regarding

the accuracy of the data given in the use of this product.