

Material SAFETY DATA SHEET Strongcoat Topping - Base

1: PRODUCT AND COMPANY IDENTIFICATION

Product Name:	Strongcoat Topping - Base	
Description:	Base component of two parts trowel applied	d epoxy flooring
Manufacturer:	Don Construction Products	
	P.O. Box 24839, Doha, Qatar	
	Tel. + 974 4 411 4004	Fax: + 974 4 411 4014
	www.dcp-int.com	
Date Prepared:	04.06.2008	
MSDS Number:	DCP/05/04/19-B	

2: COMPOSITION / INFORMATION ON INGREDIENTS

Composition:	Epoxy resin, inert f	illers.		
Hazardous Ingredient(s)	Symbol	Risk Phrases	CAS No.	%
Epoxy resin (Number average molecular weight < 700)	Xi, N	R36/38, 43, 51/53	25068-38-6	80

Refer to Section 8 for Occupational Exposure Limits.

3: HAZARDS IDENTIFICATION

Hazard Information:	Irritating to eyes and skin. May cause sensitization by skin contact. Toxic to aquatic organism, may cause long-term affects in the aquatic environment.
Classification:	Xi, N. R36/38, 43, 51/53

4: FIRST AID MEASURES

Skin: Wash immediately with soap and water or suitable skin clean contaminated clothes and shoes. Obtain medical advice if s develop. Inhalation: Remove from exposure, obtain medical attention if respirat develops or if breathing becomes difficult. Ingestion: Rinse mouth thoroughly. Drink plenty of water. Do not indu Obtain medical attention. Beware of aspiration if vomiting occ	ongcoat Topping – Base	00 Strongcoat Topping – Base	Page 1 of 5
Skin:Wash immediately with soap and water or suitable skin clean contaminated clothes and shoes. Obtain medical advice if s develop.Inhalation:Remove from exposure, obtain medical attention if respirat			•
Skin: Wash immediately with soap and water or suitable skin clean contaminated clothes and shoes. Obtain medical advice if s		•	espiratory irritation
obtain medical attention digently.	•	contaminated clothes and shoes. Obtain medical advic	
Eyes: Irrigate immediately with copious quantities of water for		Irrigate immediately with copious quantities of water Obtain medical attention urgently.	er for 15 minutes.



5: FIRE FIGHTING MEASURES

Flash Point (Closed Cup):	> 200°C
Extinguishing Media:	Carbon dioxide, powder, foam or water.
Personal Protective Equipment:	Self-contained breathing apparatus.
Special Exposure Hazards:	Toxic fumes. Carbon oxides.

6: ACCIDENTAL RELEASE MEASURES

Personal Precautions:	Wear suitable protective clothing, gloves and eye/face protection.
Environmental Precautions:	Prevent entry into drains, sewers and water courses.
Decontamination Procedures:	Soak up with inert absorbent such as sand. Gather into labeled containers. Dispose off as applicable regulations.

7: HANDLING AND STORAGE

Handling:Maintain good standards of personal hygiene. Avoid skin and eye contact.
Do not eat, drink or smoke whilst using this product. Ensure adequate
ventilation.

Storage: Keep container tightly closed in a cool dry area.

8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

Eye Protection:	Safety glasses/goggles.
Skin Protection:	Impervious gloves (e.g. PVC). Suitable protective clothing.
Respiratory Protection:	Organic chemical cartridge respirator, if needed.
Hygiene Measures:	Change contaminated clothing and clean before re-use.
Engineering Controls:	No specific ventilation requirements noted.
Exposure Guidelines:	None assigned.

Issue No.:	01	Rev. No.:	00	Strongcoat Topping – Base	Page	2 of 5



9: PHYSICAL AND CHEMICAL PROPERTIES

Form:	Liquid
Colour:	Straw colour
Odour:	Mild
pH (concentrate):	Not applicable
Boiling Point (°C):	> 200
Flash Point (closed cup) (°C):	> 200
Autoflammability (°C):	Not determined
Explosive Properties (%):	Not Known
Vapor Pressure (KPa @20°C):	0.001
Relative Density (@25°C):	1.185
Water Solubility:	Insoluble

10: STABILITY AND REACTIVITY

Stability:	Stable: reacts with compounds containing amino, hydroxyl or carboxyl groups to give stable, cross linked materials.
Conditions to Avoid:	None Known.
Chemical Incompatibility:	Strong acids. Strong alkalis. Strong oxidizing agents.
Hazardous Decomposition Products:	Thermal decomposition yield oxides of carbon, toxic fumes.

11: TOXICOLOGICAL INFORMATION

The following toxicological assessment is based on knowledge of the toxicity of the product's components. Acute Oral effect LD50 > 5000 mg/kg. Classified as moderate sensitizer.

Health Effects

On Eyes:	Slight irritation (rabbit).
On Skin:	Moderate irritation (rabbit).
By Inhalation:	May cause respiratory irritation.
By Ingestion:	May cause irritation of mouth, throat and digestive tract.
Chronic:	Repeated and prolonged skin contact may lead to skin disorders.



12: ECOLOGICAL INFORMATION

Environmental Assessment:	When used and disposed as intended, no adverse environmental effects are foreseen.
Mobility:	Mobile liquid. Insoluble in water.
Degradability:	Not readily biodegradable.
Bioaccumulation:	Not expected to be bioaccumulate.
Acute Fish Toxicity:	Ecotoxic to fish/daphnia/algae.

13: DISPOSAL CONSIDERATION

Disposal must be in accordance with local and national legislation.

Unused Product:	Dispose off through an authorized waste contractor to a licensed site.
Used/ Contaminated Product:	As for unused product.
Packaging:	Must be disposed off through an authorized waste contractor.

14: TRANSPORT INFORMATION



UN Number:

3082

Transport Name:

Environmentally hazardous substance, liquid n.o.s (Epoxy resin).

Transport Type:		Class:	Pack Group:	Marine Pollutant
At Sea	IMO	9	Ш	No
Air Transport	IATA/ICAO	9	Ш	
At land	RID/ADR	9	Ш	

Issue No.:	01	Rev. No.:	00	Strongcoat Topping – Base Page	e 4 of 5



15: REGULATORY INFORMATION

Hazard Label Data:	Xi Vi Irritant	N Dangerous for the environment
Named Ingredients:	Epoxy resin (N	umber average molecular weight < 700)
UN Number:	3082	
Risk Phrases:		
	R36/38	Irritating to eyes and skin.
	R43	May cause sensitization by skin contact.
	R51/53	Toxic to aquatic organisms, may cause long-term adverse in the aquatic environment.
Safety Phrases:		
	S24/25	Avoid contact with skin and eyes.
	S26	In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
	S37/39	Wear suitable gloves and eye/face protection.
16: OTHER INFORMAT	ΓΙΟΝ	
Issue Date:	04/06/2008	Revised Date:
Disclaimer:	The information contai	ned herein is derived from the best available sources and is

The information contained herein is derived from the best available sources and is believed to be accurate. However, no guarantee is expressed or implied regarding the accuracy of the data given in the use of this product.

Issue No.:	01	Rev. No.:	00	Strongcoat Topping – Base	Page	5 of 5